

Автоматические выключатели AIR

Formula A0A 100 TMF, A0B 100 TMF

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



A0A 100 TMF
100-1000 3p F F

A0A 100 TMF
30-300 3p F F

A0A 100 TMF
63-630 3p F F

Dimensions

Product Net Depth / Length:	60 mm	60 mm	60 mm
Product Net Height:	130 mm	130 mm	130 mm
Product Net Weight:	0.75 kg	0.75 kg	0.75 kg
Product Net Width:	76.2 mm	76.2 mm	76.2 mm

Container Information

Package Level 1 Depth / Length:	110.5 mm	110.5 mm	110.5 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	0.8 kg	0.8 kg	0.8 kg
Package Level 1 Height:	124 mm	124 mm	124 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	136.5 mm	136.5 mm	136.5 mm

Additional Information

Product Main Type:	SACE FORMULA	SACE FORMULA	SACE FORMULA
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Version:	F	F	F

Technical

Electrical Durability:	1500 cycle	1500 cycle	1500 cycle
Mechanical Durability:	Nr. Operations 8500 cycle	Nr. Operations 8500 cycle	Nr. Operations 8500 cycle
Number of Poles:	3	3	3
Rated Current (I_n):	Main Circuit 100 A	Main Circuit 30 A	Main Circuit 63 A
Rated Impulse Withstand Voltage (U_{imp}):	6 kV	6 kV	6 kV
Rated Insulation Voltage (U_i):	690 V	690 V	690 V
Rated Operational Voltage:	415 V AC	415 V AC	415 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA
Rated Uninterrupted Current (I_u):	100 A	100 A	100 A
Release:	TMF	TMF	TMF
Release Type:	TM	TM	TM
Short-Circuit Performance Level:	A	A	A
Standards:	IEC	IEC	IEC
Sub-type:	A0	A0	A0
Terminal Connection Type:	Front	Front	Front



A0A 100 TMF 40-400
3p F F



A0A 100 TMF 80-800
3p F F

Dimensions

Product Net Depth / Length:	60 mm	60 mm
Product Net Height:	130 mm	130 mm
Product Net Weight:	0.75 kg	0.75 kg
Product Net Width:	76.2 mm	76.2 mm

Container Information

Package Level 1 Depth / Length:	110.5 mm	110.5 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	0.8 kg	0.8 kg
Package Level 1 Height:	124 mm	124 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	136.5 mm	136.5 mm

Additional Information

Product Main Type:	SACE FORMULA	SACE FORMULA
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Version:	F	F

Technical

Electrical Durability:	1500 cycle	1500 cycle
Mechanical Durability:	Nr. Operations 8500 cycle	Nr. Operations 8500 cycle
Number of Poles:	3	3
Rated Current (I _n):	Main Circuit 40 A	Main Circuit 80 A
Rated Impulse Withstand Voltage (U _{imp}):	6 kV	6 kV
Rated Insulation Voltage (U _i):	690 V	690 V
Rated Operational Voltage:	415 V AC	415 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 5 kA (380 V AC) 5 kA (415 V AC) 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 7.5 kA (380 V AC) 5 kA (415 V AC) 5 kA
Rated Uninterrupted Current (I _u):	100 A	100 A
Release:	TMF	TMF
Release Type:	TM	TM
Short-Circuit Performance Level:	A	A
Standards:	IEC	IEC
Sub-type:	A0	A0
Terminal Connection Type:	Front	Front



A0B 100 TMF 100-1000 3p F F

A0B 100 TMF 30-300 3p F F

A0B 100 TMF 63-630 3p F F

Dimensions

Product Net Depth / Length:	60 mm	60 mm	60 mm
Product Net Height:	130 mm	130 mm	130 mm
Product Net Weight:	0.75 kg	0.75 kg	0.75 kg
Product Net Width:	76.2 mm	76.2 mm	76.2 mm

Container Information

Package Level 1 Depth / Length:	110.5 mm	110.5 mm	110.5 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	0.8 kg	0.8 kg	0.8 kg
Package Level 1 Height:	124 mm	124 mm	124 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	136.5 mm	136.5 mm	136.5 mm

Additional Information

Product Main Type:	SACE FORMULA	SACE FORMULA	SACE FORMULA
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Version:	F	F	F

Technical

Electrical Durability:	1500 cycle	1500 cycle	1500 cycle
Mechanical Durability:	Nr. Operations 8500 cycle	Nr. Operations 8500 cycle	Nr. Operations 8500 cycle
Number of Poles:	3	3	3
Rated Current (I_n):	Main Circuit 100 A	Main Circuit 30 A	Main Circuit 63 A
Rated Impulse Withstand Voltage (U_{imp}):	6 kV	6 kV	6 kV
Rated Insulation Voltage (U_i):	690 V	690 V	690 V
Rated Operational Voltage:	415 V AC	415 V AC	415 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(240 V AC) 5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 5 kA (380 V AC) 5 kA (415 V AC) 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(240 V AC) 10 kA (380 V AC) 7.5 kA (415 V AC) 7.5 kA	(240 V AC) 10 kA (380 V AC) 7.5 kA (415 V AC) 7.5 kA	(240 V AC) 10 kA (380 V AC) 7.5 kA (415 V AC) 7.5 kA
Rated Uninterrupted Current (I_u):	100 A	100 A	100 A
Release:	TMF	TMF	TMF
Release Type:	TM	TM	TM
Short-Circuit Performance Level:	B	B	B
Standards:	IEC	IEC	IEC
Sub-type:	A0	A0	A0
Terminal Connection Type:	Front	Front	Front



A0B 100 TMF 80-800
3p F F



A0B 100 TMF 40-400 3p
F F

Dimensions

Product Net Depth / Length:	60 mm	60 mm
Product Net Height:	130 mm	130 mm
Product Net Weight:	0.75 kg	0.75 kg
Product Net Width:	76.2 mm	76.2 mm

Container Information

Package Level 1 Depth / Length:	110.5 mm	110.5 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	0.8 kg	0.8 kg
Package Level 1 Height:	124 mm	124 mm

Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	136.5 mm	136.5 mm

Additional Information

Product Main Type:	SACE FORMULA	SACE FORMULA
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Version:	F	F

Technical

Electrical Durability:	1500 cycle	1500 cycle
Mechanical Durability:	Nr. Operations 8500 cycle	Nr. Operations 8500 cycle
Number of Poles:	3	3
Rated Current (I _n):	Main Circuit 80 A	Main Circuit 40 A
Rated Impulse Withstand Voltage (U _{imp}):	6 kV	6 kV
Rated Insulation Voltage (U _i):	690 V	690 V
Rated Operational Voltage:	415 V AC	415 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(240 V AC) 5 kA (380 V AC) 5 kA (415 V AC) 5 kA	(240 V AC) 5 kA (380 V AC) 5 kA (415 V AC) 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(240 V AC) 10 kA (380 V AC) 7.5 kA (415 V AC) 7.5 kA	(240 V AC) 10 kA (380 V AC) 7.5 kA (415 V AC) 7.5 kA
Rated Uninterrupted Current (I _u):	100 A	100 A
Release:	TMF	TMF
Release Type:	TM	TM
Short-Circuit Performance Level:	B	B
Standards:	IEC	IEC
Sub-type:	A0	A0
Terminal Connection Type:	Front	Front



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>