

Автоматические выключатели Emax2 E1.2N-A/MS, E1.2N-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



E1.2N-A/MS 800 4p WMP

E1.2N-A/MS 800 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644859855	8015644859770
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Short-Circuit Performance Level:	N	N

Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A/MS 1200
3p WMP



E1.2N-A/MS 1200
3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644859824	8015644859749
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3

Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnector	Switch Disconnector
Product Type:	Switch Disconnector	Switch Disconnector
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A/MS 1200
4p WMP



E1.2N-A/MS 1200
4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644859862	8015644859787
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 800 Ekip
Dip LI 3p WMP



E1.2N-A 800 Ekip
Dip LI 3p F F



Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm



Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835118	8015644833510
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2N-A 800 Ekip
Dip LI 4p WMP**



**E1.2N-A 800 Ekip
Dip LI 4p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835910	8015644834319
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI

Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 800 Ekip
Dip LSI 3p WMP



E1.2N-A 800 Ekip
Dip LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835125	8015644833527
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 800 Ekip
Dip LSI 4p WMP



E1.2N-A 800 Ekip
Dip LSI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835927	8015644834326
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _N]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 800 Ekip
Dip LSI 4p WMP



E1.2N-A 800 Ekip
Dip LSI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg

Product Net Width:	348 mm	284 mm
--------------------	--------	--------

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835934	8015644834333
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 800 Ekip Hi-Touch LSiG 3p WMP



E1.2N-A 800 Ekip Hi-Touch LSiG 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835194	8015644833596
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue = < 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue = < 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	800 A	800 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V

Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 800 Ekip Hi-Touch LSIG 4p WMP



E1.2N-A 800 Ekip Hi-Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835996	8015644834395
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4

Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	800 A	800 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
--	---	---



**E1.2N-A 800 Ekip
Touch LSIG 3p WMP**



**E1.2N-A 800 Ekip
Touch LSIG 3p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835163	8015644833565

Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



**E1.2N-A 800 Ekip
Touch LSIG 4p WMP**



**E1.2N-A 800 Ekip
Touch LSIG 4p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
-----------------------------	--------	--------

Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835965	8015644834364
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 800 Ekip Hi-Touch LSI 3p WMP



E1.2N-A 800 Ekip Hi-Touch LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835187	8015644833589
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 800 Ekip Hi-Touch LSI 4p WMP



E1.2N-A 800 Ekip Hi-Touch LSI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835989	8015644834388
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
---------------	----	----

Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	800 A	800 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
--	---	---



E1.2N-A 800 Ekip Hi-Touch LSIG 3p WMP



E1.2N-A 800 Ekip Hi-Touch LSIG 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
------------------------------------	--------	--------

Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835194	8015644833596
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 800 Ekip Hi-Touch LSIG 4p WMP



E1.2N-A 800 Ekip Hi-Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835996	8015644834395
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue ≤ 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue ≤ 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A

Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 800 Ekip
Touch LI 4p WMP



E1.2N-A 800 Ekip
Touch LI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835941	8015644834340

Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2

Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 800 Ekip
Touch LI 4p F F



E1.2N-A 800 Ekip
Touch LI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834340	8015644835941
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2N-A 800 Ekip
Touch LSI 4p WMP**



**E1.2N-A 800 Ekip
Touch LSI 4p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835958	8015644834357
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 800 Ekip Touch
LSIG 3p4WMP



E1.2N-A 800 Ekip Touch LSIG 3p
F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835163	8015644833565
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue ≤ 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue ≤ 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2N-A 800 Ekip
Touch LSIG 4p WMP**



**E1.2N-A 800 Ekip
Touch LSIG 4p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835965	8015644834364
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N

Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Dip LI 3p WMP



E1.2N-A 1200 Ekip Dip LI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835217	8015644833619
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour

Number of Poles:	3	3
------------------	---	---

Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Dip LI 4p WMP



E1.2N-A 1200 Ekip Dip LI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836016	8015644834418
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2N-A 1200 Ekip Dip
LSI 3p WMP**



**E1.2N-A 1200 Ekip Dip
LSI 3p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835224	8015644833626
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V

Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Dip LSI
4p WMP



E1.2N-A 1200 Ekip Dip LSI
4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836023	8015644834425
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Dip LSIG 3p WMP

E1.2N-A 1200 Ekip Dip LSIG 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835231	8015644833633
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue = < 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue = < 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL

Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip
Dip LSIG 4p WMP



E1.2N-A 1200 Ekip Dip
LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836030	8015644834432
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour

Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip G Hi-Touch LSIG 3p WMP



E1.2N-A 1200 Ekip G Hi-Touch LSIG 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg

Product Net Width:	278 mm	214 mm
--------------------	--------	--------

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835309	8015644833701
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2N-A 1200 Ekip G
Hi-Touch LSIG 4p F F**



**E1.2N-A 1200 Ekip G Hi-
Touch LSIG 4p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834500	8015644836108
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip G
Touch LSIG 4p WMP



E1.2N-A 1200 Ekip G
Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	11 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836078	8015644834470
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U_r):	600 V	600 V
Release:	Ekip G Touch LSIG	Ekip G Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
--	---	---



E1.2N-A 1200 Ekip Hi-Touch LSI 3p F F



E1.2N-A 1200 Ekip Hi-Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833688	8015644835286
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Hi-Touch LSI 3p WMP



E1.2N-A 1200 Ekip Hi-Touch LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835286	8015644833688
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Hi-Touch LSI 3p WMP



E1.2N-A 1200 Ekip Hi-Touch LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm

Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835293	8015644833695
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Hi-Touch LSIG 4p WMP



E1.2N-A 1200 Ekip Hi-Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836092	8015644834494
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip
Touch LI 3p WMP



E1.2N-A 1200 Ekip Touch
LI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835248	8015644833640
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip
Touch LI 4p WMP



E1.2N-A 1200 Ekip Touch
LI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm

Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836047	8015644834449
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F



E1.2N-A 1200 Ekip Touch LSI 3p WMP

E1.2N-A 1200 Ekip Touch LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835255	8015644833657
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V

Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip
Touch LSI 4p WMP



E1.2N-A 1200 Ekip Touch
LSI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836054	8015644834456
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip Touch LSIG 3p WMP



E1.2N-A 1200 Ekip Touch LSIG 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835262	8015644833664
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue = < 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue = < 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL

Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2N-A 1200 Ekip
Touch LSIG 4p WMP



E1.2N-A 1200 Ekip
Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836061	8015644834463
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information		
Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA		
Interrupting Rating acc. to UL1066:	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>