

Автоматические выключатели Emax2 E1.2S-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



E1.2S-A 250 Ekip Dip LI 4p WMP

E1.2S-A 250 Ekip Dip LI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836115	8015644834517
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Dip
LSI 3p F F



E1.2S-A 250 Ekip Dip LSI
3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833725	8015644835323
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Dip LSI
4p WMP



E1.2S-A 250 Ekip Dip
LSI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
-----------------------------	--------	--------

Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836122	8015644834524
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front

Version:	W	F
----------	---	---

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 250 Ekip Dip
LSIG 3p WMP**



**E1.2S-A 250 Ekip Dip
LSIG 3p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835330	8015644833732
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Dip
LSIG 4p WMP



E1.2S-A 250 Ekip Dip
LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm

Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836139	8015644834531
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front

Version:	W	F
----------	---	---

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Hi-Touch LSIG 3p WMP



E1.2S-A 250 Ekip Hi-Touch LSIG 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835392	8015644833794
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour

Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip G Hi-Touch LSIG 4p WMP



E1.2S-A 250 Ekip G Hi-Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836207	8015644834609
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 250 Ekip G
Touch LSIG 4p WMP**



**E1.2S-A 250 Ekip G
Touch LSIG 4p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836177	8015644834579
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Touch LSI G	Ekip G Touch LSI G
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Hi-Touch LSI 3p WMP



E1.2S-A 250 Ekip Hi-Touch LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835385	8015644833787
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 14 W	at Rated Operating Conditions per Pole 7 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Hi-Touch LSI 4p F F



E1.2S-A 250 Ekip Hi-Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm

Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834586	8015644836184
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Hi-Touch LSIG 3p F F



E1.2S-A 250 Ekip Hi-Touch LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833794	8015644835392
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue ≤ 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue ≤ 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Hi-Touch LSIG 4p F F



E1.2S-A 250 Ekip Hi-Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm



Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834593	8015644836191
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W



Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Touch LI 3p F F

E1.2S-A 250 Ekip Touch LI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833749	8015644835347
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip
Touch LI 4p F F



E1.2S-A 250 Ekip Touch
LI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834548	8015644836146
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip
Touch LSI 3p F F



E1.2S-A 250 Ekip Touch
LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm

Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833756	8015644835354
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S

Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 250 Ekip Touch
LSI 4p F F



E1.2S-A 250 Ekip
Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834555	8015644836153
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4

Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	250 A	250 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
--	---	---



E1.2S-A 250 Ekip Touch
LSIG 3p F F



E1.2S-A 250 Ekip
Touch LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833763	8015644835361
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 250 Ekip Touch
LSIG 4p F F**



**E1.2S-A 250 Ekip
Touch LSIG 4p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834562	8015644836160
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 7 W	at Rated Operating Conditions per Pole 14 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	250 A	250 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Dip LI
3p F F



E1.2S-A 400 Ekip Dip LI
3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833817	8015644835415
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Dip LI
4p F F



E1.2S-A 400 Ekip Dip LI 4p
WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm

Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm
Container Information		
Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834616	8015644836214
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm
Additional Information		
Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W



**E1.2S-A 400 Ekip Dip
LSI 4p F F**



**E1.2S-A 400 Ekip Dip LSI
4p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834623	8015644836221
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V

Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Dip
LSIG 3p F F



E1.2S-A 400 Ekip Dip
LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833831	8015644835439
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Dip
LSIG 4p F F



E1.2S-A 400 Ekip Dip
LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm

Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834630	8015644836238
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _p):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip G
Hi-Touch LSIG 3p F F



E1.2S-A 400 Ekip G Hi-
Touch LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833909	8015644835507
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue = < 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue = < 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2

Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip G
Hi-Touch LSIG 4p F F



E1.2S-A 400 Ekip G Hi-
Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834708	8015644836306

Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 400 Ekip G
Touch LSIG 4p F F**



**E1.2S-A 400 Ekip G
Touch LSIG 4p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834678	8015644836276
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Touch LSI G	Ekip G Touch LSI G
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Hi-Touch LSI 3p F F



E1.2S-A 400 Ekip Hi-Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833886	8015644835484
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



Dimensions

E1.2S-A 400 Ekip Hi-Touch LSIG 3p F F

E1.2S-A 400 Ekip Hi-Touch LSIG 3p WMP

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg



Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833893	8015644835491
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W



Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Hi-Touch LSIG 4p F F



E1.2S-A 400 Ekip Hi-Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834692	8015644836290
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Hi-Touch LSIG 4p F F



E1.2S-A 400 Ekip Hi-Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834692	8015644836290
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information		
Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W
Technical UL/CSA		
Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA



**E1.2S-A 400 Ekip
Touch LI 4p F F**



**E1.2S-A 400 Ekip Touch
LI 4p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834647	8015644836245
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip
Touch LSI 3p F F



E1.2S-A 400 Ekip
Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833855	8015644835453
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip Touch LSI 4p F F



E1.2S-A 400 Ekip Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834654	8015644836252
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	400 A	400 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 400 Ekip Touch
LSIG 3p F F**



**E1.2S-A 400 Ekip
Touch LSIG 3p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833862	8015644835460
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 17 W	at Rated Operating Conditions per Pole 35 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	400 A	400 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V

Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 400 Ekip
Touch LSIG 4p WMP



E1.2S-A 400 Ekip Touch
LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836269	8015644834661
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 35 W	at Rated Operating Conditions per Pole 17 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	400 A	400 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
--	---	---



E1.2S-A 800 Ekip Dip
LI 3p F F



E1.2S-A 800 Ekip Dip LI
3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm

Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833916	8015644835514
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Dip
LI 4p F F



E1.2S-A 800 Ekip Dip LI
4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834715	8015644836313
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4

Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Dip
LSI 3p F F



E1.2S-A 800 Ekip Dip LSI
3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833923	8015644835521
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 800 Ekip Dip
LSI 4p F F**



**E1.2S-A 800 Ekip Dip LSI
4p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834722	8015644836320
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Dip
LSIG 3p F F



E1.2S-A 800 Ekip Dip
LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833930	8015644835538
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Dip
LSIG 4p F F



E1.2S-A 800 Ekip Dip LSIG
4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834739	8015644836337
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip G Hi-Touch LSIG44p F F



E1.2S-A 800 Ekip G Hi-Touch LSIG44p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834807	8015644836405
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip G
Touch LSIG 4p F F



E1.2S-A 800 Ekip G
Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834777	8015644836375
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Touch LSIG	Ekip G Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Hi-Touch LSI 3p F F



E1.2S-A 800 Ekip Hi-Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833985	8015644835583
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Hi-Touch LSI 4p F F



E1.2S-A 800 Ekip Hi-Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834784	8015644836382
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _u]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Hi-Touch LSI 3p4F F



E1.2S-A 800 Ekip Hi-Touch LSI 3p4WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833992	8015644835590
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Hi-Touch LSIG 4p F F



E1.2S-A 800 Ekip Hi-Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834791	8015644836399
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Touch
LI 3p F F



E1.2S-A 800 Ekip Touch LI
3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833947	8015644835545
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Touch LI 4p F F



E1.2S-A 800 Ekip Touch LI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm

Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834746	8015644836344
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip
Touch LSI 3p F F



E1.2S-A 800 Ekip
Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833954	8015644835552
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker

Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip
Touch LSI 4p WMP



E1.2S-A 800 Ekip Touch
LSI 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836351	8015644834753
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece

Package Level 1 Width:	435 mm	435 mm
------------------------	--------	--------

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 118 W	at Rated Operating Conditions per Pole 59 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Touch
LSIG 3p F F



E1.2S-A 800 Ekip
Touch LSIG 3p4WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	38 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644833961	8015644835569
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 800 Ekip Touch
LSIG 4p F F



E1.2S-A 800 Ekip
Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834760	8015644836368
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 59 W	at Rated Operating Conditions per Pole 118 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	800 A	800 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Dip LI
3p F F



E1.2S-A 1200 Ekip Dip LI
3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg

Product Net Width:	214 mm	278 mm
--------------------	--------	--------

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834012	8015644835613
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



**E1.2S-A 1200 Ekip Dip LI
4p WMP**



**E1.2S-A 1200 Ekip Dip LI
4p F F**

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836412	8015644834814
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Dip
LSI 3p WMP



E1.2S-A 1200 Ekip Dip
LSI 3p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	278 mm	214 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644835620	8015644834029
Package Level 1 Gross Weight:	22 kg	16 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour

Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Dip
LSI 4p F F



E1.2S-A 1200 Ekip Dip
LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834821	8015644836429
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Dip
LSIG 3p F F



E1.2S-A 1200 Ekip
Dip LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834036	8015644835637
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL

Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip
Dip LSIG 4p WMP



E1.2S-A 1200 Ekip Dip
LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836436	8015644834838
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour

Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip G Hi-Touch LSIG 4p WMP



E1.2S-A 1200 Ekip G Hi-Touch LSIG 4p F F

Dimensions

Product Net Depth / Length:	281 mm	184 mm
Product Net Height:	363.5 mm	295 mm
Product Net Weight:	14 kg	11 kg
Product Net Width:	348 mm	284 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644836504	8015644834906
Package Level 1 Gross Weight:	25.5 kg	18 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _N]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 250 W	at Rated Operating Conditions per Pole 125 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _N):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Hi-Touch LSIG	Ekip G Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	N/A	Front
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip G
Touch LSIG 4p F F



E1.2S-A 1200 Ekip G
Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	11 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834876	8015644836474
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Touch LSIG	Ekip G Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip G
Touch4LSIG 4p F F



E1.2S-A 1200 Ekip G
Touch4LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	11 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834876	8015644836474
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm

Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip G Touch LSIG	Ekip G Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Hi-Touch LSI 4p F F



E1.2S-A 1200 Ekip Hi-Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834883	8015644836481
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue ≤ 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue ≤ 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2

Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Hi-Touch LSI 3p F F



E1.2S-A 1200 Ekip Hi-Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834098	8015644835699
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2

Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Hi-Touch
LSIG 4p F F



E1.2S-A 1200 Ekip Hi-Touch
LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834890	8015644836498
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC

Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_u]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1200 A	1200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
--	---	---



**E1.2S-A 1200 Ekip
Touch LI43p F F**



**E1.2S-A 1200 Ekip
Touch LI43p WMP**

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834043	8015644835644
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V

Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Hi-Touch LSI 4p F F



E1.2S-A 1200 Ekip Hi-Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834883	8015644836481
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Hi-Touch LSIG 3p F F



E1.2S-A 1200 Ekip Hi-Touch LSIG 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834098	8015644835699
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V

Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Hi-Touch LSIG 4p F F



E1.2S-A 1200 Ekip Hi-Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834890	8015644836498
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Touch
LI 3p F F



E1.2S-A 1200 Ekip
Touch LI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834043	8015644835644
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip Touch
LI 3p F F



E1.2S-A 1200 Ekip
Touch LI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834043	8015644835644
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip
Touch LSI 3p F F



E1.2S-A 1200 Ekip
Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834050	8015644835651
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL

Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip
Touch LSI 4p F F



E1.2S-A 1200 Ekip
Touch LSI 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834852	8015644836450
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %
Number of Poles:	4	4

Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip
Touch LSI[®]G 3p F F



E1.2S-A 1200 Ekip
Touch LSI[®]G 3p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	214 mm	278 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
---------------------------------	--------	--------

Package Level 1 EAN:	8015644834067	8015644835668
Package Level 1 Gross Weight:	16 kg	22 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	365 mm	365 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



E1.2S-A 1200 Ekip
Touch LSIG 4p F F



E1.2S-A 1200 Ekip
Touch LSIG 4p WMP

Dimensions

Product Net Depth / Length:	184 mm	281 mm
Product Net Height:	295 mm	363.5 mm
Product Net Weight:	11 kg	14 kg
Product Net Width:	284 mm	348 mm

Container Information

Package Level 1 Depth / Length:	330 mm	330 mm
Package Level 1 EAN:	8015644834869	8015644836467
Package Level 1 Gross Weight:	18 kg	25.5 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	435 mm	435 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 125 W	at Rated Operating Conditions per Pole 250 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1200 A	1200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V

Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	S	S
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Front	N/A
Version:	F	W

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA
-------------------------------------	---	---



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>