

Автоматические выключатели Emax2 E2.2B-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



E2.2B-A 1600
Ekip Dip LI 3p
WMP



E2.2B-A 1600
Ekip Dip LI 3p F
HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839918	8015644836511
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue ≤ 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue ≤ 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3

Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1600 A	1600 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
--	---	---



**E2.2B-A 1600 Ekip
Dip LI 4p WMP**



**E2.2B-A 1600 Ekip
Dip LI 4p F HR**

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm

Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841614	8015644838218
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI

Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F



E2.2B-A 1600 Ekip
Dip LSI 3p WMP



E2.2B-A 1600 Ekip
Dip LSI 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839925	8015644836528
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F



Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



**E2.2B-A 1600 Ekip
Dip LSI 4p WMP**



**E2.2B-A 1600 Ekip
Dip LSI 4p F HR**

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841621	8015644838225
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4

Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1600 A	1600 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
--	---	---



**E2.2B-A 1600 Ekip
Dip LSI 3p WMP**



**E2.2B-A 1600 Ekip
Dip LSI 3p F HR**

Dimensions

Product Net Depth / Length:	393 mm	270 mm
------------------------------------	--------	--------

Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839932	8015644836535
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Release:	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600 Ekip Hi-Touch LSIG 3p WMP



E2.2B-A 1600 Ekip Hi-Touch LSIG 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
---------------------------------	--------	--------

Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Hi-Touch
LSIG 4p WMP



E2.2B-A 1600
Ekip Hi-Touch
LSIG 4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841690	8015644838294
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F



Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Touch LSIG
3p WMP



E2.2B-A 1600
Ekip Touch LSIG
3p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839963	8015644836566
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue ≤ 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue ≤ 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycl 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3

Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2

Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600 Ekip
Touch LSIG 4p WMP



E2.2B-A 1600 Ekip
Touch LSIG 4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841669	8015644838263
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V

Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI G	Ekip Touch LSI G
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Hi-Touch
LSI 3p WMP



E2.2B-A 1600
Ekip Hi-Touch
LSI 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839987	8015644836580
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL

Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
--	---	---



E2.2B-A 1600
Ekip Hi-Touch
LSI 4p WMP



E2.2B-A 1600
Ekip Hi-Touch
LSI 4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841683	8015644838287

Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2

Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Hi-Touch
LSIG 3p WMP



E2.2B-A 1600
Ekip Hi-Touch
LSIG 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839994	8015644836597
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm



Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F



Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Hi-Touch
LSIG 4p WMP

E2.2B-A 1600
Ekip Hi-Touch
LSIG 4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841690	8015644838294
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour

Neutral Pole Current ([%I _u]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
--	---	---



**E2.2B-A 1600 Ekip
Touch LI 3p WMP**



**E2.2B-A 1600 Ekip
Touch LI 3p F HR**

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839949	8015644836542
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600 Ekip
Touch LI 4p WMP



E2.2B-A 1600 Ekip
Touch LI 4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm

Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841645	8015644838249
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V

Release:	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Touch LSI
3p WMP



E2.2B-A 1600
Ekip Touch LSI
3p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	317 mm	276 mm

Container Information

Package Level 1 Depth / Length:	515 mm	515 mm
Package Level 1 EAN:	8015644839956	8015644836559
Package Level 1 Gross Weight:	59 kg	50 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL

Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Touch LSI
4p WMP



E2.2B-A 1600
Ekip Touch LSI
4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841652	8015644838256
Package Level 1 Gross Weight:	68 kg	63 kg

Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal

Version:

W

F

Technical UL/CSA

Interrupting Rating acc. to
UL1066:

(254 V) 42 kA
(508 V) 42 kA
(635 V) 42 kA

(254 V) 42 kA
(508 V) 42 kA
(635 V) 42 kA



E2.2B-A 1600
Ekip Touch LSIG
3p WMP



E2.2B-A 1600
Ekip Touch LSIG
3p F HR

Dimensions

Product Net Depth / Length:

393 mm

270 mm

Product Net Height:

425 mm

371 mm

Product Net Weight:

49 kg

45 kg

Product Net Width:

317 mm

276 mm

Container Information

Package Level 1 Depth /
Length:

515 mm

515 mm

Package Level 1 EAN:

8015644839963

8015644836566

Package Level 1 Gross Weight:

59 kg

50 kg

Package Level 1 Height:

610 mm

610 mm

Package Level 1 Units:

box 1 piece

box 1 piece

Package Level 1 Width:

515 mm

515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycl 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I _n):	1600 A	1600 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
-------------------------------------	---	---



E2.2B-A 1600
Ekip Touch LSIG
4p WMP

E2.2B-A 1600
Ekip Touch LSIG
4p F HR

Dimensions

Product Net Depth / Length:	393 mm	270 mm
Product Net Height:	425 mm	371 mm
Product Net Weight:	49 kg	45 kg
Product Net Width:	407 mm	366 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644841669	8015644838263
Package Level 1 Gross Weight:	68 kg	63 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	Ue =< 508 V 12000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %
Number of Poles:	4	4

Power Loss:	at Rated Operating Conditions per Pole 260 W	at Rated Operating Conditions per Pole 170 W
Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Rated Current (I_n):	1600 A	1600 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	B	B
Standards:	UL	UL
Sub-type:	E2.2	E2.2
Terminal Connection Type:	N/A	Rear flat Horizontal
Version:	W	F

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
--	---	---



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>