

Автоматические выключатели E2N-A, E2N-A/MS

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E2N-A 1200 PR121/P-LI In=1200A 3p W MP

E2N-A 1200 PR121/P-LI In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR121/P-LI In=1200A 3p W MP
Product ID	1SDA057305R1
EAN	8015644595685
Catalog Description	E2N-A 1200 PR121/P-LI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644595685
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644595685

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2N-A 1200 PR121/P-LSI In=1200A 3p F HR

E2N-A 1200 PR121/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR121/P-LSI In=1200A 3p F HR
Product ID	1SDA057307R1
EAN	8015644595708
Catalog Description	E2N-A 1200 PR121/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595708
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644595708
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
-------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1200 PR122/P-LI In=1200A 3p W MP

E2N-A 1200 PR122/P-LI In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR122/P-LI In=1200A 3p W MP
Product ID	1SDA057317R1
EAN	8015644595807
Catalog Description	E2N-A 1200 PR122/P-LI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595807
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644595807
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1200 PR121/P-LSIG In=1200A 3p W MP

E2N-A 1200 PR121/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR121/P-LSIG In=1200A 3p W MP
Product ID	1SDA057313R1
EAN	8015644595760
Catalog Description	E2N-A 1200 PR121/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595760
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644595760
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1200 PR122/P-LSI In=1200A 3p W MP

E2N-A 1200 PR122/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR122/P-LSI In=1200A 3p W MP
Product ID	1SDA057321R1
EAN	8015644595845
Catalog Description	E2N-A 1200 PR122/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595845
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644595845
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1600 PR123/P-LSIG In=1600A 3p F HR

E2N-A 1600 PR123/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR123/P-LSIG In=1600A 3p F HR
Product ID	1SDA057363R1
EAN	8015644596262
Catalog Description	E2N-A 1600 PR123/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644596262
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644596262

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2N-A 800 PR123/P-LSIG In=800A 3p F HR

E2N-A 800 PR123/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR123/P-LSIG In=800A 3p F HR
Product ID	1SDA060719R1
EAN	8015644632427
Catalog Description	E2N-A 800 PR123/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644632427
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	800 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 800 PR122/P-LSIG In=800A 3p W MP

E2N-A 800 PR122/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR122/P-LSIG In=800A 3p W MP
Product ID	1SDA060713R1
EAN	8015644632366
Catalog Description	E2N-A 800 PR122/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644632366
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	800 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 800 PR122/P-LSIG In=800A 3p F HR

E2N-A 800 PR122/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR122/P-LSIG In=800A 3p F HR
Product ID	1SDA060711R1
EAN	8015644632342
Catalog Description	E2N-A 800 PR122/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632342
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA
	(480 V AC) 50 kA
	(600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2N-A 1600 PR121/P-LSI In=1600A 3p F HR

E2N-A 1600 PR121/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR121/P-LSI In=1600A 3p F HR
Product ID	1SDA057339R1
EAN	8015644596026
Catalog Description	E2N-A 1600 PR121/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644596026
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644596026

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1600 PR121/P-LI In=1600A 3p F HR

E2N-A 1600 PR121/P-LI In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR121/P-LI In=1600A 3p F HR
Product ID	1SDA057335R1
EAN	8015644595982
Catalog Description	E2N-A 1600 PR121/P-LI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595982
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644595982
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1600 PR121/P-LI In=1600A 3p W MP

E2N-A 1600 PR121/P-LI In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR121/P-LI In=1600A 3p W MP
Product ID	1SDA057337R1
EAN	8015644596002
Catalog Description	E2N-A 1600 PR121/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644596002
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644596002

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1200 PR123/P-LSIG In=1200A 3p F HR

E2N-A 1200 PR123/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR123/P-LSIG In=1200A 3p F HR
Product ID	1SDA057331R1
EAN	8015644595944
Catalog Description	E2N-A 1200 PR123/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644595944
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644595944

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1200 PR123/P-LSIG In=1200A 3p W MP

E2N-A 1200 PR123/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR123/P-LSIG In=1200A 3p W MP
Product ID	1SDA057333R1
EAN	8015644595968
Catalog Description	E2N-A 1200 PR123/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644595968
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644595968

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A/MS 800 3p W MP new

E2N-A/MS 800 3p W MP new



General Information

Extended Product Type	E2N-A/MS 800 3p W MP new
Product ID	1SDA061393R1
EAN	8015644639136
Catalog Description	E2N-A/MS 800 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2N-A/MS 800A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639112
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Uninterrupted Current (I_u)	800 A
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A/MS 1600 3p F HR new

E2N-A/MS 1600 3p F HR new



General Information

Extended Product Type	E2N-A/MS 1600 3p F HR new
Product ID	1SDA061387R1
EAN	8015644639075
Catalog Description	E2N-A/MS 1600 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E2N-A/MS 1600A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639075
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Uninterrupted Current (I_u)	1600 A
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A/MS 1600 3p W MP new

E2N-A/MS 1600 3p W MP new



General Information

Extended Product Type	E2N-A/MS 1600 3p W MP new
Product ID	1SDA061389R1
EAN	8015644639099
Catalog Description	E2N-A/MS 1600 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2N-A/MS 1600A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639099
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Uninterrupted Current (I_u)	1600 A
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A/MS 1200 3p F HR new

E2N-A/MS 1200 3p F HR new



General Information

Extended Product Type	E2N-A/MS 1200 3p F HR new
Product ID	1SDA061383R1
EAN	8015644639037
Catalog Description	E2N-A/MS 1200 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E2N-A/MS 800A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639037
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Uninterrupted Current (I_u)	1200 A
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A/MS 1200 3p W MP new

E2N-A/MS 1200 3p W MP new



General Information

Extended Product Type	E2N-A/MS 1200 3p W MP new
Product ID	1SDA061385R1
EAN	8015644639051
Catalog Description	E2N-A/MS 1200 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2N-A/MS 800A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639051
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Uninterrupted Current (I_u)	1200 A
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1200 PR121/P-LSIG In=1200A 3p F HR

E2N-A 1200 PR121/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR121/P-LSIG In=1200A 3p F HR
Product ID	1SDA057311R1
EAN	8015644595746
Catalog Description	E2N-A 1200 PR121/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595746
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644595746
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1200 PR122/P-LI In=1200A 3p F HR

E2N-A 1200 PR122/P-LI In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR122/P-LI In=1200A 3p F HR
Product ID	1SDA057315R1
EAN	8015644595784
Catalog Description	E2N-A 1200 PR122/P-LI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644595784
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644595784

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1200 PR122/P-LSI In=1200A 3p F HR

E2N-A 1200 PR122/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR122/P-LSI In=1200A 3p F HR
Product ID	1SDA057319R1
EAN	8015644595821
Catalog Description	E2N-A 1200 PR122/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595821
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644595821
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_o)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 800 PR121/P-LSIG In=800A 3p F HR

E2N-A 800 PR121/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR121/P-LSIG In=800A 3p F HR
Product ID	1SDA060699R1
EAN	8015644632229
Catalog Description	E2N-A 800 PR121/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644632229
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 800 PR121/P-LSI In=800A 3p W MP

E2N-A 800 PR121/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR121/P-LSI In=800A 3p W MP
Product ID	1SDA060697R1
EAN	8015644632205
Catalog Description	E2N-A 800 PR121/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632205
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR121/P-LI In=800A 3p F HR

E2N-A 800 PR121/P-LI In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR121/P-LI In=800A 3p F HR
Product ID	1SDA060691R1
EAN	8015644632144
Catalog Description	E2N-A 800 PR121/P-LI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644632144
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR121/P-LSI In=800A 3p F HR

E2N-A 800 PR121/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR121/P-LSI In=800A 3p F HR
Product ID	1SDA060695R1
EAN	8015644632182
Catalog Description	E2N-A 800 PR121/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632182
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR121/P-LI In=800A 3p W MP

E2N-A 800 PR121/P-LI In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR121/P-LI In=800A 3p W MP
Product ID	1SDA060693R1
EAN	8015644632168
Catalog Description	E2N-A 800 PR121/P-LI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632168
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1600 PR122/P-LSI In=1600A 3p W MP

E2N-A 1600 PR122/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR122/P-LSI In=1600A 3p W MP
Product ID	1SDA057353R1
EAN	8015644596163
Catalog Description	E2N-A 1600 PR122/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644596163
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644596163

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1600 PR122/P-LSIG In=1600A 3p F HR

E2N-A 1600 PR122/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR122/P-LSIG In=1600A 3p F HR
Product ID	1SDA057355R1
EAN	8015644596187
Catalog Description	E2N-A 1600 PR122/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644596187
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644596187

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1600 PR122/P-LSIG In=1600A 3p W MP

E2N-A 1600 PR122/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR122/P-LSIG In=1600A 3p W MP
Product ID	1SDA057357R1
EAN	8015644596200
Catalog Description	E2N-A 1600 PR122/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN	8015644596200	
Minimum Order Quantity	1 piece	
Customs Tariff Number	85362090	
Dimensions		
Product Net Width	324 mm	
Product Net Height	461 mm	
Product Net Depth / Length	396.5 mm	
Product Net Weight	49 kg	
Container Information		
Package Level 1 EAN	8015644596200	
Additional Information		
Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 215 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CBMP	
Rated Current (I _n)	1600 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	1600 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA	
Rated Uninterrupted Current (I _u)	1600 A	
Release	PR122/P-LSIG	
Release Type	EL	
Short-Circuit Performance Level	N	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Withdrawable Circuit-Breakers	
Version	W	
Technical UL/CSA		
	(240 V AC) 65 kA	
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA	
Certificates and Declarations		
Data Sheet, Technical Information	1SDC200008D0202	
Declaration of Conformity - CE	1SDL000165R0014	
Instructions and Manuals	1SDH000532R0002	

PRODUCT-DETAILS

E2N-A 1600 PR122/P-LSI In=1600A 3p F HR

E2N-A 1600 PR122/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR122/P-LSI In=1600A 3p F HR
Product ID	1SDA057351R1
EAN	8015644596149
Catalog Description	E2N-A 1600 PR122/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644596149
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644596149
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1600 PR121/P-LSIG In=1600A 3p W MP

E2N-A 1600 PR121/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR121/P-LSIG In=1600A 3p W MP
Product ID	1SDA057345R1
EAN	8015644596088
Catalog Description	E2N-A 1600 PR121/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644596088
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644596088
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
-------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1600 PR122/P-LI In=1600A 3p W MP

E2N-A 1600 PR122/P-LI In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR122/P-LI In=1600A 3p W MP
Product ID	1SDA057349R1
EAN	8015644596125
Catalog Description	E2N-A 1600 PR122/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644596125
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644596125
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1600 PR121/P-LSI In=1600A 3p W MP

E2N-A 1600 PR121/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR121/P-LSI In=1600A 3p W MP
Product ID	1SDA057341R1
EAN	8015644596040
Catalog Description	E2N-A 1600 PR121/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644596040
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644596040
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1600 PR122/P-LI In=1600A 3p F HR

E2N-A 1600 PR122/P-LI In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR122/P-LI In=1600A 3p F HR
Product ID	1SDA057347R1
EAN	8015644596101
Catalog Description	E2N-A 1600 PR122/P-LI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644596101
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644596101
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1600 PR121/P-LSIG In=1600A 3p F HR

E2N-A 1600 PR121/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E2N-A 1600 PR121/P-LSIG In=1600A 3p F HR
Product ID	1SDA057343R1
EAN	8015644596064
Catalog Description	E2N-A 1600 PR121/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644596064
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644596064
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 800 PR123/P-LSIG In=800A 3p W MP

E2N-A 800 PR123/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR123/P-LSIG In=800A 3p W MP
Product ID	1SDA060721R1
EAN	8015644632441
Catalog Description	E2N-A 800 PR123/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632441
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1200 PR121/P-LSI In=1200A 3p W MP

E2N-A 1200 PR121/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR121/P-LSI In=1200A 3p W MP
Product ID	1SDA057309R1
EAN	8015644595722
Catalog Description	E2N-A 1200 PR121/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644595722
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644595722

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1200 PR121/P-LI In=1200A 3p F HR

E2N-A 1200 PR121/P-LI In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR121/P-LI In=1200A 3p F HR
Product ID	1SDA057303R1
EAN	8015644595661
Catalog Description	E2N-A 1200 PR121/P-LI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595661
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644595661
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1600 PR123/P-LSIG In=1600A 3p W MP

E2N-A 1600 PR123/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E2N-A 1600 PR123/P-LSIG In=1600A 3p W MP
Product ID	1SDA057365R1
EAN	8015644596286
Catalog Description	E2N-A 1600 PR123/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN		8015644596286
Minimum Order Quantity		1 piece
Customs Tariff Number		85362090

Dimensions		
Product Net Width		324 mm
Product Net Height		461 mm
Product Net Depth / Length		396.5 mm
Product Net Weight		49 kg

Container Information		
Package Level 1 EAN		8015644596286

Additional Information		
Current Type		AC
Electrical Durability	Ue =< 508 V	10000 cycle
	Ue = 508 ... 635 V	10000 cycle
		30 cycles per hour
Mechanical Durability		20000 cycle
		30 cycles per hour
Number of Poles		3
Power Loss	at Rated Operating Conditions per Pole 215 W	
Product Main Type		SACE Emax
Product Name		Air Circuit Breaker
Product Type		CBMP
Rated Current (I _n)		1600 A
Rated Voltage (U _r)		600 V
Rated Operational Current (I _e)		1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC)	65 kA
	(480 V AC)	50 kA
	(600 V AC)	50 kA
Rated Uninterrupted Current (I _u)		1600 A
Release		PR123/P-LSIG
Release Type		EL
Short-Circuit Performance Level		N
Standards		UL 1066
Sub-type		E2
Terminal Connection Type	Withdrawable Circuit-Breakers	
Version		W

Technical UL/CSA		
		(240 V AC) 65 kA
to UL1066		(480 V AC) 50 kA
		(600 V AC) 50 kA

Certificates and Declarations		
Data Sheet, Technical Information		1SDC200008D0202
Declaration of Conformity - CE		1SDL000165R0014
Instructions and Manuals		1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR122/P-LSI In=800A 3p F HR

E2N-A 800 PR122/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR122/P-LSI In=800A 3p F HR
Product ID	1SDA060707R1
EAN	8015644632304
Catalog Description	E2N-A 800 PR122/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632304
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA
	(480 V AC) 50 kA
	(600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR122/P-LI In=800A 3p W MP

E2N-A 800 PR122/P-LI In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR122/P-LI In=800A 3p W MP
Product ID	1SDA060705R1
EAN	8015644632281
Catalog Description	E2N-A 800 PR122/P-LI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632281
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycles Ue = 508 ... 635 V 10000 cycles 30 cycles per hour
Mechanical Durability	20000 cycles 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR121/P-LSIG In=800A 3p W MP

E2N-A 800 PR121/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR121/P-LSIG In=800A 3p W MP
Product ID	1SDA060701R1
EAN	8015644632243
Catalog Description	E2N-A 800 PR121/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632243
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA
	(480 V AC) 50 kA
	(600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 800 PR122/P-LSI In=800A 3p W MP

E2N-A 800 PR122/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E2N-A 800 PR122/P-LSI In=800A 3p W MP
Product ID	1SDA060709R1
EAN	8015644632328
Catalog Description	E2N-A 800 PR122/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644632328
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2N-A 800 PR122/P-LI In=800A 3p F HR

E2N-A 800 PR122/P-LI In=800A 3p F HR



General Information

Extended Product Type	E2N-A 800 PR122/P-LI In=800A 3p F HR
Product ID	1SDA060703R1
EAN	8015644632267
Catalog Description	E2N-A 800 PR122/P-LI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644632267
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2N-A 1200 PR122/P-LSIG In=1200A 3p W MP

E2N-A 1200 PR122/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E2N-A 1200 PR122/P-LSIG In=1200A 3p W MP
Product ID	1SDA057325R1
EAN	8015644595883
Catalog Description	E2N-A 1200 PR122/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644595883
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644595883
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2N-A 1200 PR122/P-LSIG In=1200A 3p F HR

E2N-A 1200 PR122/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E2N-A 1200 PR122/P-LSIG In=1200A 3p F HR
Product ID	1SDA057323R1
EAN	8015644595869
Catalog Description	E2N-A 1200 PR122/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644595869
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644595869

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 50 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 50 kA (600 V AC) 50 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>