

Автоматические выключатели E1B-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E2S-A 800 PR122/P-LSI In=800A 3p F HR

E2S-A 800 PR122/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR122/P-LSI In=800A 3p F HR
Product ID	1SDA061027R1
EAN	8015644635503
Catalog Description	E2S-A 800 PR122/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635503
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR121/P-LSIG In=800A 3p W MP

E2S-A 800 PR121/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR121/P-LSIG In=800A 3p W MP
Product ID	1SDA061021R1
EAN	8015644635442
Catalog Description	E2S-A 800 PR121/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635442
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I_u)	800 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1600 PR121/P-LSIG In=1600A 3p W MP

E2S-A 1600 PR121/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR121/P-LSIG In=1600A 3p W MP
Product ID	1SDA061053R1
EAN	8015644635763
Catalog Description	E2S-A 1600 PR121/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635763
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR122/P-LI In=1600A 3p W MP

E2S-A 1600 PR122/P-LI In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR122/P-LI In=1600A 3p W MP
Product ID	1SDA061057R1
EAN	8015644635800
Catalog Description	E2S-A 1600 PR122/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635800
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W
Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR122/P-LI In=1600A 3p F HR

E2S-A 1600 PR122/P-LI In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR122/P-LI In=1600A 3p F HR
Product ID	1SDA061055R1
EAN	8015644635787
Catalog Description	E2S-A 1600 PR122/P-LI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN	8015644635787	
Minimum Order Quantity	1 piece	
Customs Tariff Number	85362090	
Dimensions		
Product Net Width	296 mm	
Product Net Height	418 mm	
Product Net Depth / Length	302 mm	
Product Net Weight	45 kg	
Container Information		
Package Level 1 EAN	8015644609139	
Additional Information		
Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 115 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CB	
Rated Current (I _n)	1600 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	1600 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Rated Uninterrupted Current (I _u)	1600 A	
Release	PR122/P-LI	
Release Type	EL	
Short-Circuit Performance Level	S	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal	
Version	F	
Technical UL/CSA		
	(240 V AC) 65 kA	
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA	
Certificates and Declarations		
Data Sheet, Technical Information	1SDC200008D0202	
Declaration of Conformity - CE	1SDL000165R0014	
Instructions and Manuals	1SDH000532R0002	

PRODUCT-DETAILS

E2S-A 1600 PR121/P-LSIG In=1600A 3p F HR

E2S-A 1600 PR121/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR121/P-LSIG In=1600A 3p F HR
Product ID	1SDA061051R1
EAN	8015644635749
Catalog Description	E2S-A 1600 PR121/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635749
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _N)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F
Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR121/P-LSI In=1600A 3p W MP

E2S-A 1600 PR121/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR121/P-LSI In=1600A 3p W MP
Product ID	1SDA061049R1
EAN	8015644635725
Catalog Description	E2S-A 1600 PR121/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635725
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1600 PR121/P-LI In=1600A 3p W MP

E2S-A 1600 PR121/P-LI In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR121/P-LI In=1600A 3p W MP
Product ID	1SDA061045R1
EAN	8015644635688
Catalog Description	E2S-A 1600 PR121/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635688
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR123/P-LSIG In=800A 3p W MP

E2S-A 800 PR123/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR123/P-LSIG In=800A 3p W MP
Product ID	1SDA061041R1
EAN	8015644635640
Catalog Description	E2S-A 800 PR123/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635640
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1600 PR121/P-LSI In=1600A 3p F HR

E2S-A 1600 PR121/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR121/P-LSI In=1600A 3p F HR
Product ID	1SDA061047R1
EAN	8015644635701
Catalog Description	E2S-A 1600 PR121/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN	8015644635701	
Minimum Order Quantity	1 piece	
Customs Tariff Number	85362090	
Dimensions		
Product Net Width	296 mm	
Product Net Height	418 mm	
Product Net Depth / Length	302 mm	
Product Net Weight	45 kg	
Container Information		
Package Level 1 EAN	8015644609139	
Additional Information		
Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 115 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CB	
Rated Current (I _n)	1600 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	1600 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Rated Uninterrupted Current (I _u)	1600 A	
Release	PR121/P-LSI	
Release Type	EL	
Short-Circuit Performance Level	S	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal	
Version	F	
Technical UL/CSA		
to UL1066	(240 V AC) 65 kA	
	(480 V AC) 65 kA	
	(600 V AC) 65 kA	
Certificates and Declarations		
Data Sheet, Technical Information	1SDC200008D0202	
Declaration of Conformity - CE	1SDL000165R0014	
Instructions and Manuals	1SDH000532R0002	

PRODUCT-DETAILS

E2S-A 1600 PR121/P-LI In=1600A 3p F HR

E2S-A 1600 PR121/P-LI In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR121/P-LI In=1600A 3p F HR
Product ID	1SDA061043R1
EAN	8015644635664
Catalog Description	E2S-A 1600 PR121/P-LI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN	8015644635664	
Minimum Order Quantity	1 piece	
Customs Tariff Number	85362090	
Dimensions		
Product Net Width	296 mm	
Product Net Height	418 mm	
Product Net Depth / Length	302 mm	
Product Net Weight	45 kg	
Container Information		
Package Level 1 EAN	8015644609139	
Additional Information		
Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 115 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CB	
Rated Current (I _n)	1600 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	1600 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Rated Uninterrupted Current (I _u)	1600 A	
Release	PR121/P-LI	
Release Type	EL	
Short-Circuit Performance Level	S	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal	
Version	F	
Technical UL/CSA		
	(240 V AC) 65 kA	
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA	
Certificates and Declarations		
Data Sheet, Technical Information	1SDC200008D0202	
Declaration of Conformity - CE	1SDL000165R0014	
Instructions and Manuals	1SDH000532R0002	

PRODUCT-DETAILS

E2S-A 800 PR121/P-LI In=800A 3p W MP

E2S-A 800 PR121/P-LI In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR121/P-LI In=800A 3p W MP
Product ID	1SDA061013R1
EAN	8015644635367
Catalog Description	E2S-A 800 PR121/P-LI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635367
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR121/P-LSI In=800A 3p F HR

E2S-A 800 PR121/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR121/P-LSI In=800A 3p F HR
Product ID	1SDA061015R1
EAN	8015644635381
Catalog Description	E2S-A 800 PR121/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635381
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR122/P-LSIG In=1600A 3p W MP

E2S-A 1600 PR122/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR122/P-LSIG In=1600A 3p W MP
Product ID	1SDA061065R1
EAN	8015644635886
Catalog Description	E2S-A 1600 PR122/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635886
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W
Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A/MS 1600 3p W MP new

E2S-A/MS 1600 3p W MP new



General Information

Extended Product Type	E2S-A/MS 1600 3p W MP new
Product ID	1SDA061401R1
EAN	8015644639211
Catalog Description	E2S-A/MS 1600 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2S-A/MS 1600A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639211
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Uninterrupted Current (I_u)	1600 A
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A/MS 1600 3p F HR new

E2S-A/MS 1600 3p F HR new



General Information

Extended Product Type	E2S-A/MS 1600 3p F HR new
Product ID	1SDA061399R1
EAN	8015644639198
Catalog Description	E2S-A/MS 1600 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E2S-A/MS 1600A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639198
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Uninterrupted Current (I_u)	1600 A
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A/MS 1200 3p F HR new

E2S-A/MS 1200 3p F HR new



General Information

Extended Product Type	E2S-A/MS 1200 3p F HR new
Product ID	1SDA061395R1
EAN	8015644639150
Catalog Description	E2S-A/MS 1200 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E2S-A/MS 1200A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644639150
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Uninterrupted Current (I_u)	1200 A
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2S-A/MS 1200 3p W MP new

E2S-A/MS 1200 3p W MP new



General Information

Extended Product Type	E2S-A/MS 1200 3p W MP new
Product ID	1SDA061397R1
EAN	8015644639174
Catalog Description	E2S-A/MS 1200 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2S-A/MS 1200A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639174
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Uninterrupted Current (I_u)	1200 A
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A/MS 800 3p W MP new

E2S-A/MS 800 3p W MP new



General Information

Extended Product Type	E2S-A/MS 800 3p W MP new
Product ID	1SDA061405R1
EAN	8015644639259
Catalog Description	E2S-A/MS 800 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2S-A/MS 800A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644639259
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Uninterrupted Current (I _u)	800 A
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2S-A/MS 800 3p F HR new

E2S-A/MS 800 3p F HR new



General Information

Extended Product Type	E2S-A/MS 800 3p F HR new
Product ID	1SDA061403R1
EAN	8015644639235
Catalog Description	E2S-A/MS 800 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E2S-A/MS 800A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639235
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Uninterrupted Current (I_u)	800 A
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1200 PR121/P-LI In=1200A 3p W MP

E2S-A 1200 PR121/P-LI In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR121/P-LI In=1200A 3p W MP
Product ID	1SDA060981R1
EAN	8015644635046
Catalog Description	E2S-A 1200 PR121/P-LI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635046
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W
Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR123/P-LSIG In=1600A 3p W MP

E2S-A 1600 PR123/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR123/P-LSIG In=1600A 3p W MP
Product ID	1SDA061073R1
EAN	8015644635961
Catalog Description	E2S-A 1600 PR123/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635961
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR122/P-LI In=1200A 3p F HR

E2S-A 1200 PR122/P-LI In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR122/P-LI In=1200A 3p F HR
Product ID	1SDA060991R1
EAN	8015644635145
Catalog Description	E2S-A 1200 PR122/P-LI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635145
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1200 PR122/P-LSI In=1200A 3p W MP

E2S-A 1200 PR122/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR122/P-LSI In=1200A 3p W MP
Product ID	1SDA060997R1
EAN	8015644635206
Catalog Description	E2S-A 1200 PR122/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN		8015644635206
Minimum Order Quantity		1 piece
Customs Tariff Number		85362090
Dimensions		
Product Net Width		324 mm
Product Net Height		461 mm
Product Net Depth / Length		396.5 mm
Product Net Weight		49 kg
Container Information		
Package Level 1 EAN		8015644609139
Additional Information		
Current Type		AC
Electrical Durability		Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability		20000 cycle 30 cycles per hour
Number of Poles		3
Power Loss		at Rated Operating Conditions per Pole 120 W
Product Main Type		SACE Emax
Product Name		Air Circuit Breaker
Product Type		CBMP
Rated Current (I _n)		1200 A
Rated Voltage (U _r)		600 V
Rated Operational Current (I _e)		1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})		(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)		1200 A
Release		PR122/P-LSI
Release Type		EL
Short-Circuit Performance Level		S
Standards		UL 1066
Sub-type		E2
Terminal Connection Type		Withdrawable Circuit-Breakers
Version		W
Technical UL/CSA		
		(240 V AC) 65 kA
to UL1066		(480 V AC) 65 kA
		(600 V AC) 65 kA
Certificates and Declarations		
Data Sheet, Technical Information		1SDC200008D0202
Declaration of Conformity - CE		1SDL000165R0014
Instructions and Manuals		1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR122/P-LSIG In=1200A 3p F HR

E2S-A 1200 PR122/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR122/P-LSIG In=1200A 3p F HR
Product ID	1SDA060999R1
EAN	8015644635220
Catalog Description	E2S-A 1200 PR122/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635220
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 65 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CB	
Rated Current (I _n)	1200 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	1200 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Rated Uninterrupted Current (I _u)	1200 A	
Release	PR122/P-LSIG	
Release Type	EL	
Short-Circuit Performance Level	S	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal	
Version	F	

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR122/P-LSI In=1200A 3p F HR

E2S-A 1200 PR122/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR122/P-LSI In=1200A 3p F HR
Product ID	1SDA060995R1
EAN	8015644635183
Catalog Description	E2S-A 1200 PR122/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635183
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1200 PR122/P-LI In=1200A 3p W MP

E2S-A 1200 PR122/P-LI In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR122/P-LI In=1200A 3p W MP
Product ID	1SDA060993R1
EAN	8015644635169
Catalog Description	E2S-A 1200 PR122/P-LI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635169
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR123/P-LSIG In=800A 3p F HR

E2S-A 800 PR123/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR123/P-LSIG In=800A 3p F HR
Product ID	1SDA061039R1
EAN	8015644635626
Catalog Description	E2S-A 800 PR123/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635626
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA
	(600 V AC) 65 kA

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR122/P-LSIG In=800A 3p F HR

E2S-A 800 PR122/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR122/P-LSIG In=800A 3p F HR
Product ID	1SDA061031R1
EAN	8015644635541
Catalog Description	E2S-A 800 PR122/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635541
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR121/P-LI In=1200A 3p F HR

E2S-A 1200 PR121/P-LI In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR121/P-LI In=1200A 3p F HR
Product ID	1SDA060979R1
EAN	8015644635022
Catalog Description	E2S-A 1200 PR121/P-LI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635022
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F
Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR121/P-LSI In=800A 3p W MP

E2S-A 800 PR121/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR121/P-LSI In=800A 3p W MP
Product ID	1SDA061017R1
EAN	8015644635404
Catalog Description	E2S-A 800 PR121/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635404
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR121/P-LI In=800A 3p F HR

E2S-A 800 PR121/P-LI In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR121/P-LI In=800A 3p F HR
Product ID	1SDA061011R1
EAN	8015644635343
Catalog Description	E2S-A 800 PR121/P-LI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN	8015644635343	
Minimum Order Quantity	1 piece	
Customs Tariff Number	85362090	
Dimensions		
Product Net Width	296 mm	
Product Net Height	418 mm	
Product Net Depth / Length	302 mm	
Product Net Weight	45 kg	
Container Information		
Package Level 1 EAN	8015644609139	
Additional Information		
Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 29 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CB	
Rated Current (I _N)	800 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	800 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Rated Uninterrupted Current (I _u)	800 A	
Release	PR121/P-LI	
Release Type	EL	
Short-Circuit Performance Level	S	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal	
Version	F	
Technical UL/CSA		
to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Certificates and Declarations		
Data Sheet, Technical Information	1SDC200008D0202	
Declaration of Conformity - CE	1SDL000165R0014	
Instructions and Manuals	1SDH000532R0002	

PRODUCT-DETAILS

E2S-A 800 PR121/P-LSIG In=800A 3p F HR

E2S-A 800 PR121/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR121/P-LSIG In=800A 3p F HR
Product ID	1SDA061019R1
EAN	8015644635428
Catalog Description	E2S-A 800 PR121/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635428
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _N)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F
Technical UL/CSA	
to UL1066	(240 V AC) 65 kA
	(480 V AC) 65 kA
	(600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR123/P-LSIG In=1200A 3p F HR

E2S-A 1200 PR123/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR123/P-LSIG In=1200A 3p F HR
Product ID	1SDA061007R1
EAN	8015644635305
Catalog Description	E2S-A 1200 PR123/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635305
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR123/P-LSIG In=1200A 3p W MP

E2S-A 1200 PR123/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR123/P-LSIG In=1200A 3p W MP
Product ID	1SDA061009R1
EAN	8015644635329
Catalog Description	E2S-A 1200 PR123/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635329
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR122/P-LSIG In=1200A 3p W MP

E2S-A 1200 PR122/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR122/P-LSIG In=1200A 3p W MP
Product ID	1SDA061001R1
EAN	8015644635244
Catalog Description	E2S-A 1200 PR122/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635244
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
-------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1600 PR123/P-LSIG In=1600A 3p F HR

E2S-A 1600 PR123/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR123/P-LSIG In=1600A 3p F HR
Product ID	1SDA061071R1
EAN	8015644635947
Catalog Description	E2S-A 1600 PR123/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635947
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 800 PR122/P-LI In=800A 3p W MP

E2S-A 800 PR122/P-LI In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR122/P-LI In=800A 3p W MP
Product ID	1SDA061025R1
EAN	8015644635480
Catalog Description	E2S-A 800 PR122/P-LI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN	8015644635480	
Minimum Order Quantity	1 piece	
Customs Tariff Number	85362090	
Dimensions		
Product Net Width	324 mm	
Product Net Height	461 mm	
Product Net Depth / Length	396.5 mm	
Product Net Weight	49 kg	
Container Information		
Package Level 1 EAN	8015644609139	
Additional Information		
Current Type	AC	
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour	
Mechanical Durability	20000 cycle 30 cycles per hour	
Number of Poles	3	
Power Loss	at Rated Operating Conditions per Pole 54 W	
Product Main Type	SACE Emax	
Product Name	Air Circuit Breaker	
Product Type	CBMP	
Rated Current (I _n)	800 A	
Rated Voltage (U _r)	600 V	
Rated Operational Current (I _e)	800 A	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA	
Rated Uninterrupted Current (I _u)	800 A	
Release	PR122/P-LI	
Release Type	EL	
Short-Circuit Performance Level	S	
Standards	UL 1066	
Sub-type	E2	
Terminal Connection Type	Withdrawable Circuit-Breakers	
Version	W	
Technical UL/CSA		
	(240 V AC) 65 kA	
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA	
Certificates and Declarations		
Data Sheet, Technical Information	1SDC200008D0202	
Declaration of Conformity - CE	1SDL000165R0014	
Instructions and Manuals	1SDH000532R0002	

PRODUCT-DETAILS

E2S-A 800 PR122/P-LSI In=800A 3p W MP

E2S-A 800 PR122/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR122/P-LSI In=800A 3p W MP
Product ID	1SDA061029R1
EAN	8015644635527
Catalog Description	E2S-A 800 PR122/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635527
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I_u)	800 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 800 PR122/P-LI In=800A 3p F HR

E2S-A 800 PR122/P-LI In=800A 3p F HR



General Information

Extended Product Type	E2S-A 800 PR122/P-LI In=800A 3p F HR
Product ID	1SDA061023R1
EAN	8015644635466
Catalog Description	E2S-A 800 PR122/P-LI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635466
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg
Container Information	
Package Level 1 EAN	8015644609139
Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 29 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F
Technical UL/CSA	
to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 800 PR122/P-LSIG In=800A 3p W MP

E2S-A 800 PR122/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E2S-A 800 PR122/P-LSIG In=800A 3p W MP
Product ID	1SDA061033R1
EAN	8015644635565
Catalog Description	E2S-A 800 PR122/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635565
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 54 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	800 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	800 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR122/P-LSI In=1600A 3p W MP

E2S-A 1600 PR122/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E2S-A 1600 PR122/P-LSI In=1600A 3p W MP
Product ID	1SDA061061R1
EAN	8015644635848
Catalog Description	E2S-A 1600 PR122/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635848
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA
	(480 V AC) 65 kA
	(600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

PRODUCT-DETAILS

E2S-A 1600 PR122/P-LSIG In=1600A 3p F HR

E2S-A 1600 PR122/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR122/P-LSIG In=1600A 3p F HR
Product ID	1SDA061063R1
EAN	8015644635862
Catalog Description	E2S-A 1600 PR122/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635862
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1600 PR122/P-LSI In=1600A 3p F HR

E2S-A 1600 PR122/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E2S-A 1600 PR122/P-LSI In=1600A 3p F HR
Product ID	1SDA061059R1
EAN	8015644635824
Catalog Description	E2S-A 1600 PR122/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635824
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 115 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1200 PR121/P-LSIG In=1200A 3p F HR

E2S-A 1200 PR121/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR121/P-LSIG In=1200A 3p F HR
Product ID	1SDA060987R1
EAN	8015644635107
Catalog Description	E2S-A 1200 PR121/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644635107
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
------------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

PRODUCT-DETAILS

E2S-A 1200 PR121/P-LSI In=1200A 3p W MP

E2S-A 1200 PR121/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR121/P-LSI In=1200A 3p W MP
Product ID	1SDA060985R1
EAN	8015644635084
Catalog Description	E2S-A 1200 PR121/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635084
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 65 kA
to UL1066	(480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR121/P-LSIG In=1200A 3p W MP

E2S-A 1200 PR121/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E2S-A 1200 PR121/P-LSIG In=1200A 3p W MP
Product ID	1SDA060989R1
EAN	8015644635121
Catalog Description	E2S-A 1200 PR121/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635121
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 120 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

PRODUCT-DETAILS

E2S-A 1200 PR121/P-LSI In=1200A 3p F HR

E2S-A 1200 PR121/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E2S-A 1200 PR121/P-LSI In=1200A 3p F HR
Product ID	1SDA060983R1
EAN	8015644635060
Catalog Description	E2S-A 1200 PR121/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644635060
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	296 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	45 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 65 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL 1066
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 65 kA (480 V AC) 65 kA (600 V AC) 65 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000532R0002

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>