

Автоматические выключатели ЕЗV-A/MS, ЕЗV-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E3V-A/MS 3200 3p F VR<HR new

E3V-A/MS 3200 3p F VR<HR new



General Information

Extended Product Type	E3V-A/MS 3200 3p F VR<HR new
Product ID	1SDA061455R1
EAN	8015644639754
Catalog Description	E3V-A/MS 3200 3p F VR<HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 3200A UL THREE-POLE FIXED WITH TERMINALES REAR VERTICAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639754
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Uninterrupted Current (I_u)	3200 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

PRODUCT-DETAILS

E3V-A/MS 1200 3p F HR new

E3V-A/MS 1200 3p F HR new



General Information

Extended Product Type	E3V-A/MS 1200 3p F HR new
Product ID	1SDA061439R1
EAN	8015644639594
Catalog Description	E3V-A/MS 1200 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 1200A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639594
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Uninterrupted Current (I_u)	1200 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

PRODUCT-DETAILS

E3V-A/MS 3200 3p W MP new

E3V-A/MS 3200 3p W MP new



General Information

Extended Product Type	E3V-A/MS 3200 3p W MP new
Product ID	1SDA061457R1
EAN	8015644639778
Catalog Description	E3V-A/MS 3200 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 3200A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639778
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Uninterrupted Current (I_u)	3200 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E3V-A/MS 2500 3p W MP new

E3V-A/MS 2500 3p W MP new



General Information

Extended Product Type	E3V-A/MS 2500 3p W MP new
Product ID	1SDA061453R1
EAN	8015644639730
Catalog Description	E3V-A/MS 2500 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 2500A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639730
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Uninterrupted Current (I_u)	2500 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E3V-A/MS 800 3p F HR new

E3V-A/MS 800 3p F HR new



General Information

Extended Product Type	E3V-A/MS 800 3p F HR new
Product ID	1SDA061459R1
EAN	8015644639792
Catalog Description	E3V-A/MS 800 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 800A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN		8015644639792
Minimum Order Quantity		1 piece
Customs Tariff Number		85362090

Dimensions		
Product Net Width		404 mm
Product Net Height		418 mm
Product Net Depth / Length		302 mm
Product Net Weight		60 kg

Container Information		
Package Level 1 EAN		8015644609139

Additional Information		
Current Type		AC
Number of Poles		3
Power Loss	at Rated Operating Conditions per Pole 25 W	
Product Main Type		SACE Emax
Product Name		Switch-disconnector
Product Type		SD
Rated Current (I_n)		800 A
Rated Voltage (U_r)		600 V
Rated Operational Current (I_e)		800 A
Rated Uninterrupted Current (I_u)		800 A
Short-Circuit Performance Level		V
Standards		UL 1066
Sub-type		E3
Terminal Connection Type		Fixed Circuit-Breakers Rear flat Horizontal
Version		F

PRODUCT-DETAILS

E3V-A/MS 2500 3p F HR new

E3V-A/MS 2500 3p F HR new



General Information

Extended Product Type	E3V-A/MS 2500 3p F HR new
Product ID	1SDA061451R1
EAN	8015644639716
Catalog Description	E3V-A/MS 2500 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 2500A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639716
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Uninterrupted Current (I_u)	2500 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

PRODUCT-DETAILS

E3V-A/MS 2000 3p F HR new

E3V-A/MS 2000 3p F HR new



General Information

Extended Product Type	E3V-A/MS 2000 3p F HR new
Product ID	1SDA061447R1
EAN	8015644639679
Catalog Description	E3V-A/MS 2000 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 2000A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639679
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Uninterrupted Current (I_u)	2000 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

PRODUCT-DETAILS

E3V-A/MS 1600 3p F HR new

E3V-A/MS 1600 3p F HR new



General Information

Extended Product Type	E3V-A/MS 1600 3p F HR new
Product ID	1SDA061443R1
EAN	8015644639631
Catalog Description	E3V-A/MS 1600 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 1600A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639631
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Uninterrupted Current (I_u)	1600 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

PRODUCT-DETAILS

E3V-A/MS 1200 3p W MP new

E3V-A/MS 1200 3p W MP new



General Information

Extended Product Type	E3V-A/MS 1200 3p W MP new
Product ID	1SDA061441R1
EAN	8015644639617
Catalog Description	E3V-A/MS 1200 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 1200A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639617
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Uninterrupted Current (I_u)	1200 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E3V-A/MS 1600 3p W MP new

E3V-A/MS 1600 3p W MP new



General Information

Extended Product Type	E3V-A/MS 1600 3p W MP new
Product ID	1SDA061445R1
EAN	8015644639655
Catalog Description	E3V-A/MS 1600 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 1600A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639655
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Uninterrupted Current (I_u)	1600 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E3V-A/MS 2000 3p W MP new

E3V-A/MS 2000 3p W MP new



General Information

Extended Product Type	E3V-A/MS 2000 3p W MP new
Product ID	1SDA061449R1
EAN	8015644639693
Catalog Description	E3V-A/MS 2000 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 2000A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639693
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Uninterrupted Current (I_u)	2000 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E3V-A/MS 800 3p W MP new

E3V-A/MS 800 3p W MP new



General Information

Extended Product Type	E3V-A/MS 800 3p W MP new
Product ID	1SDA061461R1
EAN	8015644639815
Catalog Description	E3V-A/MS 800 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3V-A/MS 800A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639815
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	800 A
Rated Uninterrupted Current (I_u)	800 A
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E3V-A 800 PR123/P-LSIG In=800A 3p W MP

E3V-A 800 PR123/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E3V-A 800 PR123/P-LSIG In=800A 3p W MP
Product ID	1SDA060881R1
EAN	8015644634049
Catalog Description	E3V-A 800 PR123/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634049
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 37 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR121/P-LSI In=800A 3p F HR

E3V-A 800 PR121/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR121/P-LSI In=800A 3p F HR
Product ID	1SDA060855R1
EAN	8015644633783
Catalog Description	E3V-A 800 PR121/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644633783
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR121/P-LI In=800A 3p W MP

E3V-A 800 PR121/P-LI In=800A 3p W MP



General Information

Extended Product Type	E3V-A 800 PR121/P-LI In=800A 3p W MP
Product ID	1SDA060853R1
EAN	8015644633769
Catalog Description	E3V-A 800 PR121/P-LI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644633769
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 37 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR121/P-LSIG In=800A 3p F HR

E3V-A 800 PR121/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR121/P-LSIG In=800A 3p F HR
Product ID	1SDA060859R1
EAN	8015644633820
Catalog Description	E3V-A 800 PR121/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644633820
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR123/P-LSIG In=800A 3p F HR

E3V-A 800 PR123/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR123/P-LSIG In=800A 3p F HR
Product ID	1SDA060879R1
EAN	8015644634025
Catalog Description	E3V-A 800 PR123/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634025
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR122/P-LSI In=800A 3p W MP

E3V-A 800 PR122/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E3V-A 800 PR122/P-LSI In=800A 3p W MP
Product ID	1SDA060869R1
EAN	8015644633929
Catalog Description	E3V-A 800 PR122/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644633929
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 37 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 800 PR122/P-LI In=800A 3p W MP

E3V-A 800 PR122/P-LI In=800A 3p W MP



General Information

Extended Product Type	E3V-A 800 PR122/P-LI In=800A 3p W MP
Product ID	1SDA060865R1
EAN	8015644633882
Catalog Description	E3V-A 800 PR122/P-LI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644633882
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 37 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR122/P-LI In=800A 3p F HR

E3V-A 800 PR122/P-LI In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR122/P-LI In=800A 3p F HR
Product ID	1SDA060863R1
EAN	8015644633868
Catalog Description	E3V-A 800 PR122/P-LI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644633868
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 800 PR122/P-LI In=800A 3p F HR

E3V-A 800 PR122/P-LI In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR122/P-LI In=800A 3p F HR
Product ID	1SDA060863R1
EAN	8015644633868
Catalog Description	E3V-A 800 PR122/P-LI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644633868
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 800 PR121/P-LSIG In=800A 3p W MP

E3V-A 800 PR121/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E3V-A 800 PR121/P-LSIG In=800A 3p W MP
Product ID	1SDA060861R1
EAN	8015644633844
Catalog Description	E3V-A 800 PR121/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644633844
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 37 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 800 PR122/P-LSI In=800A 3p F HR

E3V-A 800 PR122/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR122/P-LSI In=800A 3p F HR
Product ID	1SDA060867R1
EAN	8015644633905
Catalog Description	E3V-A 800 PR122/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644633905
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 800 PR122/P-LSIG In=800A 3p F HR

E3V-A 800 PR122/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E3V-A 800 PR122/P-LSIG In=800A 3p F HR
Product ID	1SDA060871R1
EAN	8015644633943
Catalog Description	E3V-A 800 PR122/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644633943
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 25 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 800 PR122/P-LSIG In=800A 3p W MP

E3V-A 800 PR122/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E3V-A 800 PR122/P-LSIG In=800A 3p W MP
Product ID	1SDA060873R1
EAN	8015644633967
Catalog Description	E3V-A 800 PR122/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644633967
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 37 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR121/P-LSI In=1200A 3p W MP

E3V-A 1200 PR121/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR121/P-LSI In=1200A 3p W MP
Product ID	1SDA057693R1
EAN	8015644599560
Catalog Description	E3V-A 1200 PR121/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644599560
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644599560
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 1200 PR121/P-LSIG In=1200A 3p F HR

E3V-A 1200 PR121/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR121/P-LSIG In=1200A 3p F HR
Product ID	1SDA057695R1
EAN	8015644599584
Catalog Description	E3V-A 1200 PR121/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599584
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599584

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR121/P-LSIG In=1200A 3p W MP

E3V-A 1200 PR121/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR121/P-LSIG In=1200A 3p W MP
Product ID	1SDA057697R1
EAN	8015644599607
Catalog Description	E3V-A 1200 PR121/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644599607
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644599607
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 1200 PR121/P-LSI In=1200A 3p F HR

E3V-A 1200 PR121/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR121/P-LSI In=1200A 3p F HR
Product ID	1SDA057691R1
EAN	8015644599546
Catalog Description	E3V-A 1200 PR121/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644599546
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644599546
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 1200 PR122/P-LI In=1200A 3p F HR

E3V-A 1200 PR122/P-LI In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR122/P-LI In=1200A 3p F HR
Product ID	1SDA057699R1
EAN	8015644599621
Catalog Description	E3V-A 1200 PR122/P-LI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599621
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599621

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR121/P-LI In=1200A 3p W MP

E3V-A 1200 PR121/P-LI In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR121/P-LI In=1200A 3p W MP
Product ID	1SDA057689R1
EAN	8015644599522
Catalog Description	E3V-A 1200 PR121/P-LI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644599522
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644599522
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 1200 PR121/P-LI In=1200A 3p F HR

E3V-A 1200 PR121/P-LI In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR121/P-LI In=1200A 3p F HR
Product ID	1SDA057687R1
EAN	8015644599508
Catalog Description	E3V-A 1200 PR121/P-LI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599508
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599508

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR122/P-LSI In=1200A 3p F HR

E3V-A 1200 PR122/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR122/P-LSI In=1200A 3p F HR
Product ID	1SDA057703R1
EAN	8015644599669
Catalog Description	E3V-A 1200 PR122/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599669
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599669

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR122/P-LSIG In=1200A 3p W MP

E3V-A 1200 PR122/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR122/P-LSIG In=1200A 3p W MP
Product ID	1SDA057709R1
EAN	8015644599720
Catalog Description	E3V-A 1200 PR122/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644599720
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644599720
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 1200 PR122/P-LI In=1200A 3p W MP

E3V-A 1200 PR122/P-LI In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR122/P-LI In=1200A 3p W MP
Product ID	1SDA057701R1
EAN	8015644599645
Catalog Description	E3V-A 1200 PR122/P-LI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644599645
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644599645
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue ≤ 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 1200 PR122/P-LSI In=1200A 3p W MP

E3V-A 1200 PR122/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR122/P-LSI In=1200A 3p W MP
Product ID	1SDA057705R1
EAN	8015644599683
Catalog Description	E3V-A 1200 PR122/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599683
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644599683

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR122/P-LSIG In=1200A 3p F HR

E3V-A 1200 PR122/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR122/P-LSIG In=1200A 3p F HR
Product ID	1SDA057707R1
EAN	8015644599706
Catalog Description	E3V-A 1200 PR122/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599706
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599706

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR123/P-LSIG In=1200A 3p W MP

E3V-A 1200 PR123/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E3V-A 1200 PR123/P-LSIG In=1200A 3p W MP
Product ID	1SDA057717R1
EAN	8015644599805
Catalog Description	E3V-A 1200 PR123/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599805
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644599805

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 83 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1200 PR123/P-LSIG In=1200A 3p F HR

E3V-A 1200 PR123/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E3V-A 1200 PR123/P-LSIG In=1200A 3p F HR
Product ID	1SDA057715R1
EAN	8015644599782
Catalog Description	E3V-A 1200 PR123/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599782
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599782

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 55 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR121/P-LSIG In=1600A 3p W MP

E3V-A 1600 PR121/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E3V-A 1600 PR121/P-LSIG In=1600A 3p W MP
Product ID	1SDA057729R1
EAN	8015644599928
Catalog Description	E3V-A 1600 PR121/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599928
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644599928

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR121/P-LSIG In=1600A 3p F HR

E3V-A 1600 PR121/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR121/P-LSIG In=1600A 3p F HR
Product ID	1SDA057727R1
EAN	8015644599904
Catalog Description	E3V-A 1600 PR121/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599904
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599904

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR121/P-LSI In=1600A 3p F HR

E3V-A 1600 PR121/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR121/P-LSI In=1600A 3p F HR
Product ID	1SDA057723R1
EAN	8015644599867
Catalog Description	E3V-A 1600 PR121/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599867
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599867

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR121/P-LSI In=1600A 3p W MP

E3V-A 1600 PR121/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E3V-A 1600 PR121/P-LSI In=1600A 3p W MP
Product ID	1SDA057725R1
EAN	8015644599881
Catalog Description	E3V-A 1600 PR121/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599881
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644599881

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

Ordering	
EAN	8015644600129
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600129

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR122/P-LSIG In=1600A 3p W MP

E3V-A 1600 PR122/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E3V-A 1600 PR122/P-LSIG In=1600A 3p W MP
Product ID	1SDA057741R1
EAN	8015644600044
Catalog Description	E3V-A 1600 PR122/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600044
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600044

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR121/P-LI In=1600A 3p W MP

E3V-A 1600 PR121/P-LI In=1600A 3p W MP



General Information

Extended Product Type	E3V-A 1600 PR121/P-LI In=1600A 3p W MP
Product ID	1SDA057721R1
EAN	8015644599843
Catalog Description	E3V-A 1600 PR121/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599843
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644599843

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR121/P-LI In=1600A 3p F HR

E3V-A 1600 PR121/P-LI In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR121/P-LI In=1600A 3p F HR
Product ID	1SDA057719R1
EAN	8015644599829
Catalog Description	E3V-A 1600 PR121/P-LI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599829
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599829

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR122/P-LSI In=1600A 3p F HR

E3V-A 1600 PR122/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR122/P-LSI In=1600A 3p F HR
Product ID	1SDA057735R1
EAN	8015644599980
Catalog Description	E3V-A 1600 PR122/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599980
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599980

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR122/P-LSIG In=1600A 3p F HR

E3V-A 1600 PR122/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR122/P-LSIG In=1600A 3p F HR
Product ID	1SDA057739R1
EAN	8015644600020
Catalog Description	E3V-A 1600 PR122/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600020
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600020

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR122/P-LI In=1600A 3p F HR

E3V-A 1600 PR122/P-LI In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR122/P-LI In=1600A 3p F HR
Product ID	1SDA057731R1
EAN	8015644599942
Catalog Description	E3V-A 1600 PR122/P-LI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599942
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644599942

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR122/P-LSI In=1600A 3p W MP

E3V-A 1600 PR122/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E3V-A 1600 PR122/P-LSI In=1600A 3p W MP
Product ID	1SDA057737R1
EAN	8015644600006
Catalog Description	E3V-A 1600 PR122/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600006
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600006

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR122/P-LI In=1600A 3p W MP

E3V-A 1600 PR122/P-LI In=1600A 3p W MP



General Information

Extended Product Type	E3V-A 1600 PR122/P-LI In=1600A 3p W MP
Product ID	1SDA057733R1
EAN	8015644599966
Catalog Description	E3V-A 1600 PR122/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644599966
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644599966

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 150 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 1600 PR123/P-LSIG In=1600A 3p F HR

E3V-A 1600 PR123/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E3V-A 1600 PR123/P-LSIG In=1600A 3p F HR
Product ID	1SDA057747R1
EAN	8015644600105
Catalog Description	E3V-A 1600 PR123/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600105
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600105

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 85 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2000 PR123/P-LSIG In=2000A 3p W MP

E3V-A 2000 PR123/P-LSIG In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR123/P-LSIG In=2000A 3p W MP
Product ID	1SDA057781R1
EAN	8015644600440
Catalog Description	E3V-A 2000 PR123/P-LSIG In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600440
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600440

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2000 PR123/P-LSIG In=2000A 3p F HR

E3V-A 2000 PR123/P-LSIG In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR123/P-LSIG In=2000A 3p F HR
Product ID	1SDA057779R1
EAN	8015644600426
Catalog Description	E3V-A 2000 PR123/P-LSIG In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600426
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600426

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2000 PR122/P-LSIG In=2000A 3p W MP

E3V-A 2000 PR122/P-LSIG In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR122/P-LSIG In=2000A 3p W MP
Product ID	1SDA057773R1
EAN	8015644600365
Catalog Description	E3V-A 2000 PR122/P-LSIG In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600365
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600365
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR122/P-LSIG In=2000A 3p F HR

E3V-A 2000 PR122/P-LSIG In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR122/P-LSIG In=2000A 3p F HR
Product ID	1SDA057771R1
EAN	8015644600341
Catalog Description	E3V-A 2000 PR122/P-LSIG In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600341
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600341
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR122/P-LSI In=2000A 3p F HR

E3V-A 2000 PR122/P-LSI In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR122/P-LSI In=2000A 3p F HR
Product ID	1SDA057767R1
EAN	8015644600303
Catalog Description	E3V-A 2000 PR122/P-LSI In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600303
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600303
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
-------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR122/P-LI In=2000A 3p W MP

E3V-A 2000 PR122/P-LI In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR122/P-LI In=2000A 3p W MP
Product ID	1SDA057765R1
EAN	8015644600280
Catalog Description	E3V-A 2000 PR122/P-LI In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600280
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600280
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR122/P-LSI In=2000A 3p W MP

E3V-A 2000 PR122/P-LSI In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR122/P-LSI In=2000A 3p W MP
Product ID	1SDA057769R1
EAN	8015644600327
Catalog Description	E3V-A 2000 PR122/P-LSI In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600327
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600327
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR122/P-LI In=2000A 3p F HR

E3V-A 2000 PR122/P-LI In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR122/P-LI In=2000A 3p F HR
Product ID	1SDA057763R1
EAN	8015644600266
Catalog Description	E3V-A 2000 PR122/P-LI In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600266
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600266
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR121/P-LSIG In=2000A 3p W MP

E3V-A 2000 PR121/P-LSIG In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR121/P-LSIG In=2000A 3p W MP
Product ID	1SDA057761R1
EAN	8015644600242
Catalog Description	E3V-A 2000 PR121/P-LSIG In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600242
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600242
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR121/P-LSI In=2000A 3p F HR

E3V-A 2000 PR121/P-LSI In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR121/P-LSI In=2000A 3p F HR
Product ID	1SDA057755R1
EAN	8015644600181
Catalog Description	E3V-A 2000 PR121/P-LSI In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600181
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600181
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR121/P-LI In=2000A 3p F HR

E3V-A 2000 PR121/P-LI In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR121/P-LI In=2000A 3p F HR
Product ID	1SDA057751R1
EAN	8015644600143
Catalog Description	E3V-A 2000 PR121/P-LI In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600143
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600143

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2000 PR121/P-LI In=2000A 3p W MP

E3V-A 2000 PR121/P-LI In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR121/P-LI In=2000A 3p W MP
Product ID	1SDA057753R1
EAN	8015644600167
Catalog Description	E3V-A 2000 PR121/P-LI In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600167
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600167

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2000 PR121/P-LSIG In=2000A 3p F HR

E3V-A 2000 PR121/P-LSIG In=2000A 3p F HR



General Information

Extended Product Type	E3V-A 2000 PR121/P-LSIG In=2000A 3p F HR
Product ID	1SDA057759R1
EAN	8015644600228
Catalog Description	E3V-A 2000 PR121/P-LSIG In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600228
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600228
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2000 PR121/P-LSI In=2000A 3p W MP

E3V-A 2000 PR121/P-LSI In=2000A 3p W MP



General Information

Extended Product Type	E3V-A 2000 PR121/P-LSI In=2000A 3p W MP
Product ID	1SDA057757R1
EAN	8015644600204
Catalog Description	E3V-A 2000 PR121/P-LSI In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600204
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600204

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 225 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR122/P-LI In=2500A 3p W MP

E3V-A 2500 PR122/P-LI In=2500A 3p W MP



General Information

Extended Product Type	E3V-A 2500 PR122/P-LI In=2500A 3p W MP
Product ID	1SDA057797R1
EAN	8015644600600
Catalog Description	E3V-A 2500 PR122/P-LI In=2500A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600600
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600600
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2500 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2500 PR122/P-LI In=2500A 3p F HR

E3V-A 2500 PR122/P-LI In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR122/P-LI In=2500A 3p F HR
Product ID	1SDA057795R1
EAN	8015644600587
Catalog Description	E3V-A 2500 PR122/P-LI In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600587
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600587

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR121/P-LSIG In=2500A 3p F HR

E3V-A 2500 PR121/P-LSIG In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR121/P-LSIG In=2500A 3p F HR
Product ID	1SDA057791R1
EAN	8015644600549
Catalog Description	E3V-A 2500 PR121/P-LSIG In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600549
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600549
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2500 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2500 PR122/P-LSI In=2500A 3p F HR

E3V-A 2500 PR122/P-LSI In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR122/P-LSI In=2500A 3p F HR
Product ID	1SDA057799R1
EAN	8015644600624
Catalog Description	E3V-A 2500 PR122/P-LSI In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600624
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600624

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR121/P-LSIG In=2500A 3p W MP

E3V-A 2500 PR121/P-LSIG In=2500A 3p W MP



General Information

Extended Product Type	E3V-A 2500 PR121/P-LSIG In=2500A 3p W MP
Product ID	1SDA057793R1
EAN	8015644600563
Catalog Description	E3V-A 2500 PR121/P-LSIG In=2500A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600563
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600563

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR122/P-LSIG In=2500A 3p F HR

E3V-A 2500 PR122/P-LSIG In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR122/P-LSIG In=2500A 3p F HR
Product ID	1SDA057803R1
EAN	8015644600662
Catalog Description	E3V-A 2500 PR122/P-LSIG In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600662
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600662

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR121/P-LI In=2500A 3p W MP

E3V-A 2500 PR121/P-LI In=2500A 3p W MP



General Information

Extended Product Type	E3V-A 2500 PR121/P-LI In=2500A 3p W MP
Product ID	1SDA057785R1
EAN	8015644600488
Catalog Description	E3V-A 2500 PR121/P-LI In=2500A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600488
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600488
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2500 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2500 PR122/P-LSI In=2500A 3p W MP

E3V-A 2500 PR122/P-LSI In=2500A 3p W MP



General Information

Extended Product Type	E3V-A 2500 PR122/P-LSI In=2500A 3p W MP
Product ID	1SDA057801R1
EAN	8015644600648
Catalog Description	E3V-A 2500 PR122/P-LSI In=2500A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600648
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644600648
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2500 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2500 PR121/P-LSI In=2500A 3p W MP

E3V-A 2500 PR121/P-LSI In=2500A 3p W MP



General Information

Extended Product Type	E3V-A 2500 PR121/P-LSI In=2500A 3p W MP
Product ID	1SDA057789R1
EAN	8015644600525
Catalog Description	E3V-A 2500 PR121/P-LSI In=2500A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600525
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600525

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR121/P-LSI In=2500A 3p F HR

E3V-A 2500 PR121/P-LSI In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR121/P-LSI In=2500A 3p F HR
Product ID	1SDA057787R1
EAN	8015644600501
Catalog Description	E3V-A 2500 PR121/P-LSI In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644600501
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644600501
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2500 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2500 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 2500 PR121/P-LI In=2500A 3p F HR

E3V-A 2500 PR121/P-LI In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR121/P-LI In=2500A 3p F HR
Product ID	1SDA057783R1
EAN	8015644600464
Catalog Description	E3V-A 2500 PR121/P-LI In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600464
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600464

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR123/P-LSIG In=2500A 3p W MP

E3V-A 2500 PR123/P-LSIG In=2500A 3p W MP



General Information

Extended Product Type	E3V-A 2500 PR123/P-LSIG In=2500A 3p W MP
Product ID	1SDA057813R1
EAN	8015644600761
Catalog Description	E3V-A 2500 PR123/P-LSIG In=2500A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600761
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644600761

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 2500 PR123/P-LSIG In=2500A 3p F HR

E3V-A 2500 PR123/P-LSIG In=2500A 3p F HR



General Information

Extended Product Type	E3V-A 2500 PR123/P-LSIG In=2500A 3p F HR
Product ID	1SDA057811R1
EAN	8015644600747
Catalog Description	E3V-A 2500 PR123/P-LSIG In=2500A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644600747
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644600747

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 205 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	2500 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR122/P-LSI In=3200A 3p W MP

E3V-A 3200 PR122/P-LSI In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR122/P-LSI In=3200A 3p W MP
Product ID	1SDA060901R1
EAN	8015644634247
Catalog Description	E3V-A 3200 PR122/P-LSI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634247
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR122/P-LSIG In=3200A 3p W MP

E3V-A 3200 PR122/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR122/P-LSIG In=3200A 3p W MP
Product ID	1SDA060905R1
EAN	8015644634285
Catalog Description	E3V-A 3200 PR122/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634285
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR121/P-LI In=3200A 3p W MP

E3V-A 3200 PR121/P-LI In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR121/P-LI In=3200A 3p W MP
Product ID	1SDA060885R1
EAN	8015644634087
Catalog Description	E3V-A 3200 PR121/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634087
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR121/P-LSI In3200 3p F VR<HR

E3V-A 3200 PR121/P-LSI In3200 3p F VR<HR



General Information

Extended Product Type	E3V-A 3200 PR121/P-LSI In3200 3p F VR<HR
Product ID	1SDA060887R1
EAN	8015644634100
Catalog Description	E3V-A 3200 PR121/P-LSI In3200 3p F VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR121/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634100
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR121/P-LSI In=3200A 3p W MP

E3V-A 3200 PR121/P-LSI In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR121/P-LSI In=3200A 3p W MP
Product ID	1SDA060889R1
EAN	8015644634124
Catalog Description	E3V-A 3200 PR121/P-LSI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644634124
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	3200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E3V-A 3200 PR121/P-LSIG In=3200A 3p W MP

E3V-A 3200 PR121/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR121/P-LSIG In=3200A 3p W MP
Product ID	1SDA060893R1
EAN	8015644634162
Catalog Description	E3V-A 3200 PR121/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634162
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR122/P-LI In=3200A 3p W MP

E3V-A 3200 PR122/P-LI In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR122/P-LI In=3200A 3p W MP
Product ID	1SDA060897R1
EAN	8015644634209
Catalog Description	E3V-A 3200 PR122/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634209
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR122/P-LSI In3200 3p F VR<HR

E3V-A 3200 PR122/P-LSI In3200 3p F VR<HR



General Information

Extended Product Type	E3V-A 3200 PR122/P-LSI In3200 3p F VR<HR
Product ID	1SDA060899R1
EAN	8015644634223
Catalog Description	E3V-A 3200 PR122/P-LSI In3200 3p F VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634223
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR123/P-LSIG In=3200A 3p W MP

E3V-A 3200 PR123/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E3V-A 3200 PR123/P-LSIG In=3200A 3p W MP
Product ID	1SDA060913R1
EAN	8015644634360
Catalog Description	E3V-A 3200 PR123/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634360
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 570 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR

E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR



General Information

Extended Product Type	E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR
Product ID	1SDA060883R1
EAN	8015644634063
Catalog Description	E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR121/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634063
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR122/P-LI In=3200 3p F VR<HR

E3V-A 3200 PR122/P-LI In=3200 3p F VR<HR



General Information

Extended Product Type	E3V-A 3200 PR122/P-LI In=3200 3p F VR<HR
Product ID	1SDA060895R1
EAN	8015644634186
Catalog Description	E3V-A 3200 PR122/P-LI In=3200 3p F VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634186
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR122/P-LSIG In3200 3pF VR<HR

E3V-A 3200 PR122/P-LSIG In3200 3pF VR<HR



General Information

Extended Product Type	E3V-A 3200 PR122/P-LSIG In3200 3pF VR<HR
Product ID	1SDA060903R1
EAN	8015644634261
Catalog Description	E3V-A 3200 PR122/P-LSIG In3200 3pF VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR122/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634261
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR121/P-LSIG In3200 3pF VR<HR

E3V-A 3200 PR121/P-LSIG In3200 3pF VR<HR



General Information

Extended Product Type	E3V-A 3200 PR121/P-LSIG In3200 3pF VR<HR
Product ID	1SDA060891R1
EAN	8015644634148
Catalog Description	E3V-A 3200 PR121/P-LSIG In3200 3pF VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR121/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634148
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E3V-A 3200 PR123/P-LSIG In3200 3pF VR<HR

E3V-A 3200 PR123/P-LSIG In3200 3pF VR<HR



General Information

Extended Product Type	E3V-A 3200 PR123/P-LSIG In3200 3pF VR<HR
Product ID	1SDA060911R1
EAN	8015644634346
Catalog Description	E3V-A 3200 PR123/P-LSIG In3200 3pF VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR123/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644634346
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated
Version	F

Technical UL/CSA	
	(240 V AC) 125 kA
to UL1066	(480 V AC) 125 kA (600 V AC) 100 kA



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>