

Автоматические выключатели ЕЗХ-А

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E3X-A 800 PR123/P-LSIG In=800A 3p W MP

E3X-A 800 PR123/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E3X-A 800 PR123/P-LSIG In=800A 3p W MP
Product ID	1SDA063940R1
EAN	8015644667863
Catalog Description	E3X-A 800 PR123/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667863
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information

Current Type	AC
Electrical Durability	U _e ≤ 508 V 1500 cycle U _e = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 800 PR121/P-LSIG In=800A 3p F HR

E3X-A 800 PR121/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E3X-A 800 PR121/P-LSIG In=800A 3p F HR
Product ID	1SDA063919R1
EAN	8015644667658
Catalog Description	E3X-A 800 PR121/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667658
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 34 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 800 PR121/P-LSI In=800A 3p W MP

E3X-A 800 PR121/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E3X-A 800 PR121/P-LSI In=800A 3p W MP
Product ID	1SDA063916R1
EAN	8015644667627
Catalog Description	E3X-A 800 PR121/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644667627
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 800 PR121/P-LSI In=800A 3p F HR

E3X-A 800 PR121/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E3X-A 800 PR121/P-LSI In=800A 3p F HR
Product ID	1SDA063915R1
EAN	8015644667610
Catalog Description	E3X-A 800 PR121/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667610
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 34 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 800 PR122/P-LSIG In=800A 3p F HR

E3X-A 800 PR122/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E3X-A 800 PR122/P-LSIG In=800A 3p F HR
Product ID	1SDA063931R1
EAN	8015644667771
Catalog Description	E3X-A 800 PR122/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644667771
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 34 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 800 PR122/P-LSIG In=800A 3p W MP

E3X-A 800 PR122/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E3X-A 800 PR122/P-LSIG In=800A 3p W MP
Product ID	1SDA063932R1
EAN	8015644667788
Catalog Description	E3X-A 800 PR122/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667788
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 800 PR123/P-LSIG In=800A 3p F HR

E3X-A 800 PR123/P-LSIG In=800A 3p F HR



General Information

Extended Product Type	E3X-A 800 PR123/P-LSIG In=800A 3p F HR
Product ID	1SDA063939R1
EAN	8015644667856
Catalog Description	E3X-A 800 PR123/P-LSIG In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644667856
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 34 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 800 PR122/P-LSI In=800A 3p F HR

E3X-A 800 PR122/P-LSI In=800A 3p F HR



General Information

Extended Product Type	E3X-A 800 PR122/P-LSI In=800A 3p F HR
Product ID	1SDA063927R1
EAN	8015644667733
Catalog Description	E3X-A 800 PR122/P-LSI In=800A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667733
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 34 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	800 A
Rated Voltage (U_r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 800 PR122/P-LSI In=800A 3p W MP

E3X-A 800 PR122/P-LSI In=800A 3p W MP



General Information

Extended Product Type	E3X-A 800 PR122/P-LSI In=800A 3p W MP
Product ID	1SDA063928R1
EAN	8015644667740
Catalog Description	E3X-A 800 PR122/P-LSI In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667740
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 800 PR121/P-LSIG In=800A 3p W MP

E3X-A 800 PR121/P-LSIG In=800A 3p W MP



General Information

Extended Product Type	E3X-A 800 PR121/P-LSIG In=800A 3p W MP
Product ID	1SDA063920R1
EAN	8015644667665
Catalog Description	E3X-A 800 PR121/P-LSIG In=800A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 800A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644667665
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 53 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1200 PR121/P-LSI In=1200A 3p F HR

E3X-A 1200 PR121/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E3X-A 1200 PR121/P-LSI In=1200A 3p F HR
Product ID	1SDA063947R1
EAN	8015644667931
Catalog Description	E3X-A 1200 PR121/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667931
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 77 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
-------------------------------------	--

PRODUCT-DETAILS

E3X-A 1200 PR121/P-LSIG In=1200A 3p F HR

E3X-A 1200 PR121/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E3X-A 1200 PR121/P-LSIG In=1200A 3p F HR
Product ID	1SDA063951R1
EAN	8015644667979
Catalog Description	E3X-A 1200 PR121/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644667979
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 77 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1200 PR121/P-LSIG In=1200A 3p W MP

E3X-A 1200 PR121/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E3X-A 1200 PR121/P-LSIG In=1200A 3p W MP
Product ID	1SDA063952R1
EAN	8015644667986
Catalog Description	E3X-A 1200 PR121/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644667986
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 119 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1200 PR122/P-LSI In=1200A 3p F HR

E3X-A 1200 PR122/P-LSI In=1200A 3p F HR



General Information

Extended Product Type	E3X-A 1200 PR122/P-LSI In=1200A 3p F HR
Product ID	1SDA063959R1
EAN	8015644668051
Catalog Description	E3X-A 1200 PR122/P-LSI In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668051
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 77 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
-------------------------------------	--

PRODUCT-DETAILS

E3X-A 1200 PR121/P-LSI In=1200A 3p W MP

E3X-A 1200 PR121/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E3X-A 1200 PR121/P-LSI In=1200A 3p W MP
Product ID	1SDA063948R1
EAN	8015644667948
Catalog Description	E3X-A 1200 PR121/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644667948
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 119 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 1200 PR123/P-LSIG In=1200A 3p W MP

E3X-A 1200 PR123/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E3X-A 1200 PR123/P-LSIG In=1200A 3p W MP
Product ID	1SDA063972R1
EAN	8015644668181
Catalog Description	E3X-A 1200 PR123/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668181
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 119 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1200 PR123/P-LSIG In=1200A 3p F HR

E3X-A 1200 PR123/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E3X-A 1200 PR123/P-LSIG In=1200A 3p F HR
Product ID	1SDA063971R1
EAN	8015644668174
Catalog Description	E3X-A 1200 PR123/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668174
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 77 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
-------------------------------------	--

PRODUCT-DETAILS

E3X-A 1200 PR122/P-LSIG In=1200A 3p F HR

E3X-A 1200 PR122/P-LSIG In=1200A 3p F HR



General Information

Extended Product Type	E3X-A 1200 PR122/P-LSIG In=1200A 3p F HR
Product ID	1SDA063963R1
EAN	8015644668099
Catalog Description	E3X-A 1200 PR122/P-LSIG In=1200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668099
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 77 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1200 PR122/P-LSIG In=1200A 3p W MP

E3X-A 1200 PR122/P-LSIG In=1200A 3p W MP



General Information

Extended Product Type	E3X-A 1200 PR122/P-LSIG In=1200A 3p W MP
Product ID	1SDA063964R1
EAN	8015644668105
Catalog Description	E3X-A 1200 PR122/P-LSIG In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668105
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 119 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 1200 PR122/P-LSI In=1200A 3p W MP

E3X-A 1200 PR122/P-LSI In=1200A 3p W MP



General Information

Extended Product Type	E3X-A 1200 PR122/P-LSI In=1200A 3p W MP
Product ID	1SDA063960R1
EAN	8015644668068
Catalog Description	E3X-A 1200 PR122/P-LSI In=1200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668068
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 119 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1600 PR121/P-LSI In=1600A 3p F HR

E3X-A 1600 PR121/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E3X-A 1600 PR121/P-LSI In=1600A 3p F HR
Product ID	1SDA063979R1
EAN	8015644668259
Catalog Description	E3X-A 1600 PR121/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668259
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 138 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1600 PR122/P-LSIG In=1600A 3p F HR

E3X-A 1600 PR122/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E3X-A 1600 PR122/P-LSIG In=1600A 3p F HR
Product ID	1SDA063995R1
EAN	8015644668419
Catalog Description	E3X-A 1600 PR122/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668419
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 138 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1600 PR122/P-LSIG In=1600A 3p W MP

E3X-A 1600 PR122/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E3X-A 1600 PR122/P-LSIG In=1600A 3p W MP
Product ID	1SDA063996R1
EAN	8015644668426
Catalog Description	E3X-A 1600 PR122/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668426
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 211 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 1600 PR122/P-LSI In=1600A 3p F HR

E3X-A 1600 PR122/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E3X-A 1600 PR122/P-LSI In=1600A 3p F HR
Product ID	1SDA063991R1
EAN	8015644668372
Catalog Description	E3X-A 1600 PR122/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668372
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 138 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1600 PR122/P-LSI In=1600A 3p F HR

E3X-A 1600 PR122/P-LSI In=1600A 3p F HR



General Information

Extended Product Type	E3X-A 1600 PR122/P-LSI In=1600A 3p F HR
Product ID	1SDA063991R1
EAN	8015644668372
Catalog Description	E3X-A 1600 PR122/P-LSI In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668372
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 138 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1600 PR121/P-LSIG In=1600A 3p W MP

E3X-A 1600 PR121/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E3X-A 1600 PR121/P-LSIG In=1600A 3p W MP
Product ID	1SDA063984R1
EAN	8015644668303
Catalog Description	E3X-A 1600 PR121/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668303
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 211 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 1600 PR121/P-LSIG In=1600A 3p F HR

E3X-A 1600 PR121/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E3X-A 1600 PR121/P-LSIG In=1600A 3p F HR
Product ID	1SDA063983R1
EAN	8015644668297
Catalog Description	E3X-A 1600 PR121/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668297
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 138 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
-------------------------------------	--

PRODUCT-DETAILS

E3X-A 1600 PR121/P-LSI In=1600A 3p W MP

E3X-A 1600 PR121/P-LSI In=1600A 3p W MP



General Information

Extended Product Type	E3X-A 1600 PR121/P-LSI In=1600A 3p W MP
Product ID	1SDA063980R1
EAN	8015644668266
Catalog Description	E3X-A 1600 PR121/P-LSI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668266
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 211 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	1600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	1600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 1600 PR123/P-LSIG In=1600A 3p F HR

E3X-A 1600 PR123/P-LSIG In=1600A 3p F HR



General Information

Extended Product Type	E3X-A 1600 PR123/P-LSIG In=1600A 3p F HR
Product ID	1SDA064003R1
EAN	8015644668495
Catalog Description	E3X-A 1600 PR123/P-LSIG In=1600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668495
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 138 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 1600 PR123/P-LSIG In=1600A 3p W MP

E3X-A 1600 PR123/P-LSIG In=1600A 3p W MP



General Information

Extended Product Type	E3X-A 1600 PR123/P-LSIG In=1600A 3p W MP
Product ID	1SDA064004R1
EAN	8015644668501
Catalog Description	E3X-A 1600 PR123/P-LSIG In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 1600A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668501
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 211 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	1600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	1600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	1600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR123/P-LSIG In=2000A 3p W MP

E3X-A 2000 PR123/P-LSIG In=2000A 3p W MP



General Information

Extended Product Type	E3X-A 2000 PR123/P-LSIG In=2000A 3p W MP
Product ID	1SDA064036R1
EAN	8015644668822
Catalog Description	E3X-A 2000 PR123/P-LSIG In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668822
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA
	(600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR122/P-LSIG In=2000A 3p F HR

E3X-A 2000 PR122/P-LSIG In=2000A 3p F HR



General Information

Extended Product Type	E3X-A 2000 PR122/P-LSIG In=2000A 3p F HR
Product ID	1SDA064027R1
EAN	8015644668730
Catalog Description	E3X-A 2000 PR122/P-LSIG In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668730
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
-------------------------------------	--

PRODUCT-DETAILS

E3X-A 2000 PR122/P-LSI In=2000A 3p F HR

E3X-A 2000 PR122/P-LSI In=2000A 3p F HR



General Information

Extended Product Type	E3X-A 2000 PR122/P-LSI In=2000A 3p F HR
Product ID	1SDA064023R1
EAN	8015644668693
Catalog Description	E3X-A 2000 PR122/P-LSI In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668693
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR122/P-LSIG In=2000A 3p W MP

E3X-A 2000 PR122/P-LSIG In=2000A 3p W MP



General Information

Extended Product Type	E3X-A 2000 PR122/P-LSIG In=2000A 3p W MP
Product ID	1SDA064028R1
EAN	8015644668747
Catalog Description	E3X-A 2000 PR122/P-LSIG In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644668747
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
------------------------------------	--

PRODUCT-DETAILS

E3X-A 2000 PR122/P-LSI In=2000A 3p W MP

E3X-A 2000 PR122/P-LSI In=2000A 3p W MP



General Information

Extended Product Type	E3X-A 2000 PR122/P-LSI In=2000A 3p W MP
Product ID	1SDA064024R1
EAN	8015644668709
Catalog Description	E3X-A 2000 PR122/P-LSI In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668709
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA
	(600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR121/P-LSI In=2000A 3p W MP

E3X-A 2000 PR121/P-LSI In=2000A 3p W MP



General Information

Extended Product Type	E3X-A 2000 PR121/P-LSI In=2000A 3p W MP
Product ID	1SDA064012R1
EAN	8015644668587
Catalog Description	E3X-A 2000 PR121/P-LSI In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668587
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR121/P-LSIG In=2000A 3p F HR

E3X-A 2000 PR121/P-LSIG In=2000A 3p F HR



General Information

Extended Product Type	E3X-A 2000 PR121/P-LSIG In=2000A 3p F HR
Product ID	1SDA064015R1
EAN	8015644668617
Catalog Description	E3X-A 2000 PR121/P-LSIG In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668617
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR121/P-LSI In=2000A 3p F HR

E3X-A 2000 PR121/P-LSI In=2000A 3p F HR



General Information

Extended Product Type	E3X-A 2000 PR121/P-LSI In=2000A 3p F HR
Product ID	1SDA064011R1
EAN	8015644668570
Catalog Description	E3X-A 2000 PR121/P-LSI In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668570
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR121/P-LSIG In=2000A 3p W MP

E3X-A 2000 PR121/P-LSIG In=2000A 3p W MP



General Information

Extended Product Type	E3X-A 2000 PR121/P-LSIG In=2000A 3p W MP
Product ID	1SDA064016R1
EAN	8015644668624
Catalog Description	E3X-A 2000 PR121/P-LSIG In=2000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668624
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA

PRODUCT-DETAILS

E3X-A 2000 PR123/P-LSIG In=2000A 3p F HR

E3X-A 2000 PR123/P-LSIG In=2000A 3p F HR



General Information

Extended Product Type	E3X-A 2000 PR123/P-LSIG In=2000A 3p F HR
Product ID	1SDA064035R1
EAN	8015644668815
Catalog Description	E3X-A 2000 PR123/P-LSIG In=2000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3X-A 2000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644668815
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 1500 cycle Ue = 508 ... 635 V 1500 cycle 30 cycles per hour
Mechanical Durability	10000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 215 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	2000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 200 kA (480 V AC) 200 kA (600 V AC) 14 kA
Rated Uninterrupted Current (I _u)	2000 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	X
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 200 kA
to UL1066	(480 V AC) 200 kA (600 V AC) 14 kA



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>