

Автоматические выключатели Emax2

E4.2H-A/E, E4.2H-A/MS

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



E4.2H-A/E
3200 Ekip Dip
LSI 4p FVR



E4.2H-A/E
3200 Ekip Dip
LSI 3p FVR



E4.2H-A/E
3200 Ekip Dip
LSI 4p WMP



E4.2H-A/E
3200 Ekip Dip
LSI 3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	116 kg	91 kg	171 kg	136 kg
Product Net Width:	510 mm	384 mm	551 mm	425 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 Gross Weight:	122 kg	101 kg	177 kg	142 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	445 W	445 W	410 W	410 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	730 V	730 V	730 V	730 V
Rated Operational Voltage:	730 V	730 V	730 V	730 V
Rated Voltage (U _r):	730 V	730 V	730 V	730 V
Release:	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL	EL	EL
Remarks:	UL1066 760V	UL1066 760V	UL1066 760V	UL1066 760V
Short-Circuit Performance Level:	N	N	N	N

Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA
-------------------------------------	------------------	------------------	------------------	------------------



E4.2H-A/E
3200 Ekip Dip
LSIG 3p FVR



E4.2H-A/E
3200 Ekip Dip
LSIG 4p WMP



E4.2H-A/E
3200 Ekip Dip
LSIG 3p WMP



E4.2H-A/E
3200 Ekip Dip
LSIG 4p FVR

Dimensions

Product Net Depth / Length:	270 mm	393 mm	393 mm	270 mm
Product Net Height:	371 mm	425 mm	425 mm	371 mm
Product Net Weight:	91 kg	171 kg	136 kg	116 kg
Product Net Width:	384 mm	551 mm	425 mm	510 mm

Container Information

Package Level 1 Depth / Length:	615 mm	785 mm	615 mm	785 mm
Package Level 1 Gross Weight:	101 kg	177 kg	142 kg	122 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	W	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	N/A	100 %	N/A	100 %

Number of Poles:	3	4	3	4
Power Loss:	445 W	410 W	410 W	445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	730 V	730 V	730 V	730 V
Rated Operational Voltage:	730 V	730 V	730 V	730 V
Rated Voltage (U _r):	730 V	730 V	730 V	730 V
Release:	Ekip Dip LSIg	Ekip Dip LSIg	Ekip Dip LSIg	Ekip Dip LSIg
Release Type:	EL	EL	EL	EL
Remarks:	UL1066 760V	UL1066 760V	UL1066 760V	UL1066 760V
Short-Circuit Performance Level:	N	N	N	N
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA
-------------------------------------	------------------	------------------	------------------	------------------



E4.2H-A/E
3200 Ekip
Touch LSI
4p WMP



E4.2H-A/E
3200 Ekip
Touch LSI
4p FVR



E4.2H-A/E
3200 Ekip
Touch LSI 3p
WMP



E4.2H-A/E
3200 Ekip
Touch LSI 3p
FVR

Dimensions

Product Net Depth / Length:	393 mm	270 mm	393 mm	270 mm
Product Net Height:	425 mm	371 mm	425 mm	371 mm
Product Net Weight:	171 kg	116 kg	136 kg	91 kg
Product Net Width:	551 mm	510 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 Gross Weight:	177 kg	122 kg	142 kg	101 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece

Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm
------------------------	--------	--------	--------	--------

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	W	F

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	410 W	445 W	410 W	445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	730 V	730 V	730 V	730 V
Rated Operational Voltage:	730 V	730 V	730 V	730 V
Rated Voltage (U _r):	730 V	730 V	730 V	730 V
Release:	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL	EL	EL
Remarks:	UL1066 760V	UL1066 760V	UL1066 760V	UL1066 760V
Short-Circuit Performance Level:	N	N	N	N
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA
-------------------------------------	------------------	------------------	------------------	------------------



E4.2H-A/E
3200 Ekip
Touch LSI
4p WMP



E4.2H-A/E
3200 Ekip
Touch LSI
4p FVR



E4.2H-A/E
3200 Ekip
Touch LSI
3p WMP



E4.2H-A/E
3200 Ekip
Touch LSI
3p FVR

Dimensions

Product Net Depth / Length:	393 mm	270 mm	393 mm	270 mm
Product Net Height:	425 mm	371 mm	425 mm	371 mm
Product Net Weight:	171 kg	116 kg	136 kg	91 kg
Product Net Width:	551 mm	510 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 Gross Weight:	177 kg	122 kg	142 kg	101 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current (I _N):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	410 W	445 W	410 W	445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	730 V	730 V	730 V	730 V
Rated Operational Voltage:	730 V	730 V	730 V	730 V
Rated Voltage (U _r):	730 V	730 V	730 V	730 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL	EL	EL
Remarks:	UL1066 760V	UL1066 760V	UL1066 760V	UL1066 760V
Short-Circuit Performance Level:	N	N	N	N
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA	(730 V AC) 85 kA
-------------------------------------	------------------	------------------	------------------	------------------



E4.2H-A/E 3600
Ekip Dip LSI 3p
FVR

E4.2H-A/E 3600
Ekip Dip LSI 3p
FVR

E4.2H-A/E 3600
Ekip Dip LSI 3p F
no Term

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	95 kg	95 kg	56 kg
Product Net Width:	384 mm	384 mm	384 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm	615 mm
Package Level 1 EAN:	N/A	N/A	
Package Level 1 Gross Weight:	101 kg	101 kg	79 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour	10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	3	3
Power Loss:	445 W	445 W	578 W
Rated Current (I _n):	3600 A	3600 A	3600 A

Rated Insulation Voltage (U _i):	730 V	730 V	AC 1000 V
Rated Operational Voltage:	730 V	730 V	730 V 635 V
Rated Uninterrupted Current (I _u):	N/A	N/A	3600 A
Rated Voltage (U _r):	730 V	730 V	730 V 635 V
Release:	Ekip Dip LSIG	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL	EL
Remarks:	UL1066 760V	UL1066 760V	N/A
Short-Circuit Performance Level:	N	N	H
Standards:	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(730 V AC) 85 kA	(730 V AC) 85 kA	N/A
-------------------------------------	------------------	------------------	-----



E4.2H-A/E 3600 Ekip
Touch LSIG43p FVR



E4.2H-A/E 3600 Ekip
Touch LSI 3p4FVR

Dimensions

Product Net Depth / Length:	270 mm	270 mm
Product Net Height:	371 mm	371 mm
Product Net Weight:	95 kg	95 kg
Product Net Width:	384 mm	384 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 Gross Weight:	101 kg	101 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F

Technical

Current Type:	AC	AC
Electrical Durability:	Ue = 730 V 400 cycle 30 cycles per hour	Ue = 730 V 400 cycle 30 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	445 W	445 W
Rated Current (I _n):	3600 A	3600 A
Rated Insulation Voltage (U _i):	730 V	730 V
Rated Operational Voltage:	730 V	730 V
Rated Voltage (U _r):	730 V	730 V
Release:	Ekip Touch LSIG	Ekip Touch LSI
Release Type:	EL	EL
Remarks:	UL1066 760V	UL1066 760V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(730 V AC) 85 kA	(730 V AC) 85 kA
-------------------------------------	------------------	------------------



E4.2H-A/MS
2500 3p
WMP

E4.2H-A/MS
2500 4p FHR

E4.2H-A/MS
2500 3p FHR

E4.2H-A/MS
2500 4p
WMP

Dimensions

Product Net Depth / Length:	393 mm	270 mm	270 mm	393 mm
Product Net Height:	425 mm	371 mm	371 mm	425 mm
Product Net Weight:	59 kg	74 kg	59 kg	74 kg
Product Net Width:	425 mm	510 mm	384 mm	551 mm

Container Information

Package Level 1 Depth / Length:	615 mm	785 mm	615 mm	785 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	75 kg	75 kg	75 kg	75 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Version:	W	F	F	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Je = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	3	4	3	4
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2



E4.2H-A/
MS 3200

E4.2H-A/
MS 3200

E4.2H-A/
MS 3200

E4.2H-A/MS
3200 4p WMP

Dimensions

Product Net Depth / Length:	270 mm	393 mm	270 mm	393 mm
Product Net Height:	371 mm	425 mm	371 mm	425 mm
Product Net Weight:	74 kg	59 kg	59 kg	74 kg
Product Net Width:	510 mm	425 mm	384 mm	551 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	615 mm	785 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	75 kg	75 kg	75 kg	75 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnector	Switch Disconnector	Switch Disconnector	Switch Disconnector
Product Type:	Switch Disconnector	Switch Disconnector	Switch Disconnector	Switch Disconnector
Version:	F	W	F	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Je = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Number of Poles:	4	3	3	4
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>