

Автоматические выключатели Emax2

E4.2H-A, E4.2H MS/DC

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



E4.2H-A 2500
Ekip Dip LI 4p
WMP



E4.2H-A 2500
Ekip Dip LI 3p
WMP



E4.2H-A 2500
Ekip Dip LI 3p
F HR



E4.2H-A 2500
Ekip Dip LI 4p
F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	384 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	615 mm	785 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	100 kg	95 kg	81 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle e = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	N/A	100 %
Number of Poles:	4	3	3	4
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V

Release:	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 2500
Ekip Dip LSI
4p WMP



E4.2H-A 2500
Ekip Dip LSI
3p WMP



E4.2H-A 2500
Ekip Dip LSI
3p F HR



E4.2H-A 2500
Ekip Dip LSI 4p
F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	384 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	615 mm	785 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	100 kg	95 kg	81 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Je = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	N/A	100 %
Number of Poles:	4	3	3	4
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



E4.2H-A 2500
Ekip Dip LSI
4p WMP



E4.2H-A 2500
Ekip Dip LSI
3p WMP



E4.2H-A 2500
Ekip Dip LSI
4p F HR



E4.2H-A 2500
Ekip Dip LSI
3p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	510 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:	8015644850234	8015644847937	8015644845636	8015644843335
Package Level 1 Gross Weight:	91 kg	100 kg	81 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current (I _n):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A
2500 Ekip
Hi-Touch LSI
4p WMP



E4.2H-A
2500 Ekip
Hi-Touch LSI
3p WMP



E4.2H-A
2500 Ekip
Hi-Touch LSI
4p F HR



E4.2H-A
2500 Ekip
Hi-Touch LSI
3p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	510 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:	8015644850289	8015644847982	8015644845681	8015644843380
Package Level 1 Gross Weight:	91 kg	100 kg	81 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_n]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I_n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V	600 V	600 V

Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A
2500 Ekip
Hi-Touch
LSIG 4p
WMP



E4.2H-A
2500 Ekip
Hi-Touch
LSIG 3p WMP



E4.2H-A
2500 Ekip
Hi-Touch
LSIG 4p F HR



E4.2H-A
2500 Ekip
Hi-Touch
LSIG 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	510 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	100 kg	81 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle e = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 2500
Ekip Touch LI
4p WMP



E4.2H-A 2500
Ekip Touch LI
3p WMP



E4.2H-A 2500
Ekip Touch LI
4p F HR



E4.2H-A 2500
Ekip Touch LI
3p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	510 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:	8015644850241	8015644847944	8015644845643	8015644843342
Package Level 1 Gross Weight:	91 kg	100 kg	81 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 2500 Ekip Touch LSI 4p WMP

E4.2H-A 2500 Ekip Touch LSI 3p WMP

E4.2H-A 2500 Ekip Touch LSI 4p F HR

E4.2H-A 2500 Ekip Touch LSI 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	510 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	100 kg	81 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V

Release:	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 2500
Ekip Touch
LSIG 4p WMP

E4.2H-A 2500
Ekip Touch
LSIG 3p WMP

E4.2H-A 2500
Ekip Touch
LSIG 4p F HR

E4.2H-A 2500
Ekip Touch
LSIG 3p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	85 kg	85 kg	81 kg	81 kg
Product Net Width:	551 mm	425 mm	510 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:	8015644850265	8015644847968	8015644845667	8015644843366
Package Level 1 Gross Weight:	91 kg	100 kg	81 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 8000 cycle Je = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 410 W	at Rated Operating Conditions per Pole 310 W	at Rated Operating Conditions per Pole 310 W
Rated Current (I _n):	2500 A	2500 A	2500 A	2500 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 3200
Ekip Dip LI 4p
FVR



E4.2H-A 3200
Ekip Dip LI 4p
WMP



E4.2H-A 3200
Ekip Dip LI 3p
WMP



E4.2H-A 3200
Ekip Dip LI 3p
FVR

Dimensions

Product Net Depth / Length:	270 mm	393 mm	393 mm	270 mm
Product Net Height:	371 mm	425 mm	425 mm	371 mm
Product Net Weight:	81 kg	85 kg	85 kg	81 kg
Product Net Width:	510 mm	551 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 EAN:	8015644845711	8015644850319	8015644848019	8015644843410
Package Level 1 Gross Weight:	81 kg	91 kg	100 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	W	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current (I _n):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 3200
Ekip Dip LSI
4p FVR

E4.2H-A 3200
Ekip Dip LSI
4p WMP

E4.2H-A 3200
Ekip Dip LSI
3p WMP

E4.2H-A 3200
Ekip Dip LSI
3p FVR

Dimensions

Product Net Depth / Length:	270 mm	393 mm	393 mm	270 mm
Product Net Height:	371 mm	425 mm	425 mm	371 mm
Product Net Weight:	81 kg	85 kg	85 kg	81 kg
Product Net Width:	510 mm	551 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	81 kg	91 kg	100 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	W	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Je = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL	EL	EL

Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 3200
Ekip Dip4
LSIG 4p WMP



E4.2H-A 3200
Ekip Dip4
LSIG 4p FVR



E4.2H-A 3200
Ekip Dip4
LSIG 3p WMP



E4.2H-A 3200
Ekip Dip4
LSIG 3p FVR

Dimensions

Product Net Depth / Length:	393 mm	270 mm	393 mm	270 mm
Product Net Height:	425 mm	371 mm	425 mm	371 mm
Product Net Weight:	85 kg	81 kg	85 kg	81 kg
Product Net Width:	551 mm	510 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	81 kg	100 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ie = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour

Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I_n]):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W
Rated Current (I_n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U_r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



**E4.2H-A
3200 Ekip
Hi-Touch
LSIG 4p
WMP**



**E4.2H-A
3200 Ekip
Hi-Touch
LSIG 4p FVR**



**E4.2H-A
3200 Ekip
Hi-Touch
LSIG 3p WMP**



**E4.2H-A
3200 Ekip
Hi-Touch
LSIG 3p FVR**

Dimensions

Product Net Depth / Length:	393 mm	270 mm	393 mm	270 mm
Product Net Height:	425 mm	371 mm	425 mm	371 mm
Product Net Weight:	81 kg	81 kg	81 kg	81 kg
Product Net Width:	551 mm	510 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	81 kg	95 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 3200
Ekip Touch LI
4p WMP



E4.2H-A 3200
Ekip Touch LI
4p FVR



E4.2H-A 3200
Ekip Touch LI
3p WMP



E4.2H-A 3200
Ekip Touch LI
3p FVR

Dimensions

Product Net Depth / Length:	393 mm	270 mm	393 mm	270 mm
Product Net Height:	425 mm	371 mm	425 mm	371 mm
Product Net Weight:	85 kg	81 kg	85 kg	81 kg
Product Net Width:	551 mm	510 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 EAN:	8015644850340	8015644845742	8015644848040	8015644843441
Package Level 1 Gross Weight:	91 kg	81 kg	100 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ie = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ie = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ie = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ie = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 3200
Ekip Touch LSI
4p WMP



E4.2H-A 3200
Ekip Touch LSI
3p FVR



E4.2H-A 3200
Ekip Touch LSI
4p FVR



E4.2H-A 3200
Ekip Touch LSI
3p WMP

Dimensions

Product Net Depth / Length:	393 mm	270 mm	270 mm	393 mm
Product Net Height:	425 mm	371 mm	371 mm	425 mm
Product Net Weight:	85 kg	81 kg	81 kg	85 kg
Product Net Width:	551 mm	384 mm	510 mm	425 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm	785 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	91 kg	95 kg	81 kg	100 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	F	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ie = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	N/A	100 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	Rear flat Vertical	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E4.2H-A 3200
Ekip Touch
LSIG 4p WMP



E4.2H-A 3200
Ekip Touch
LSIG 4p FVR



E4.2H-A 3200
Ekip Touch
LSIG 3p WMP



E4.2H-A 3200
Ekip Touch
LSIG 3p FVR

Dimensions

Product Net Depth / Length:	393 mm	270 mm	393 mm	270 mm
Product Net Height:	425 mm	371 mm	425 mm	371 mm
Product Net Weight:	85 kg	81 kg	85 kg	81 kg
Product Net Width:	551 mm	510 mm	425 mm	384 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	615 mm	615 mm
Package Level 1 EAN:	8015644850364	8015644845766	8015644848064	8015644843465
Package Level 1 Gross Weight:	91 kg	81 kg	100 kg	95 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	F	W	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Je = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour	20000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	N/A	N/A
Number of Poles:	4	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W	at Rated Operating Conditions per Pole 610 W	at Rated Operating Conditions per Pole 445 W
Rated Current (I _n):	3200 A	3200 A	3200 A	3200 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	N/A	Rear flat Vertical	N/A	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



E4.2H-A 3600
Ekip Dip LSIG 3p
FVR



E4.2H-A 3600
Ekip Dip LSI 3p
FVR



E4.2H-A 3600 Ekip
Dip LI 3p FVR

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	95 kg	95 kg	95 kg
Product Net Width:	384 mm	384 mm	384 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm	615 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	108 kg	108 kg	108 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Number of Poles:	3	3	3
Power Loss:	578 W	578 W	578 W
Rated Current (I _n):	3600 A	3600 A	3600 A
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V	AC 1000 V
Rated Operational Voltage:	635 V AC	635 V AC	635 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Dip LSiG	Ekip Dip LSI	Ekip Dip LI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA	(254 V) 85 kA	(254 V) 85 kA
	(508 V) 85 kA	(508 V) 85 kA	(508 V) 85 kA
	(635 V) 85 kA	(635 V) 85 kA	(635 V) 85 kA



E4.2H-A 3600 Ekip Hi-Touch LSIG43p FVR



E4.2H-A 3600 Ekip Hi-Touch LSI 3p4FVR

Dimensions

Product Net Depth / Length:	270 mm	270 mm
Product Net Height:	371 mm	371 mm
Product Net Weight:	95 kg	95 kg
Product Net Width:	384 mm	384 mm

Container Information

Package Level 1 Depth / Length:	615 mm	615 mm
Package Level 1 EAN:	8015644843595	8015644843588
Package Level 1 Gross Weight:	108 kg	108 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F

Technical

Current Type:	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Number of Poles:	3	3
Power Loss:	578 W	578 W
Rated Current (I _n):	3600 A	3600 A
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V
Rated Operational Voltage:	635 V AC	635 V AC
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	H	H
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---



E4.2H-A 3600 Ekip
Touch LSI 3p FVR



E4.2H-A 3600 Ekip
Touch LSI 3p FVR



E4.2H-A 3600 Ekip
Touch LI 3p FVR

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	95 kg	95 kg	95 kg
Product Net Width:	384 mm	384 mm	384 mm



Container Information

Package Level 1 Depth / Length:	615 mm	615 mm	615 mm
Package Level 1 EAN:	8015644843557	8015644843564	8015644843540
Package Level 1 Gross Weight:	108 kg	108 kg	108 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm



Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F



Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour	Ue =< 508 V 7000 cycle Ue = 635 V 7000 cycle 20 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Number of Poles:	3	3	3
Power Loss:	578 W	578 W	578 W
Rated Current (I _n):	3600 A	3600 A	3600 A
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V	AC 1000 V
Rated Operational Voltage:	635 V AC	635 V AC	635 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSIG	Ekip Touch LI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL

Sub-type:	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical	Rear flat Vertical

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E4.2H-A MS/DC-E 1600A
1500V 4p F



E4.2H-A MS/DC-E 1600A
1500V 4p W MP

Dimensions

Product Net Depth / Length:	270 mm	270 mm
Product Net Height:	371 mm	371 mm
Product Net Weight:	67 kg	81 kg
Product Net Width:	510 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm
Package Level 1 EAN:	8056221075244	8056221075299
Package Level 1 Gross Weight:	79 kg	95 kg
Package Level 1 Height:	600 mm	600 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnectors	Switch Disconnectors
Product Type:	Switch Disconnectors	Switch Disconnectors
Version:	F	W

Technical

Current Type:	DC	DC
Number of Poles:	4	4
Power Loss:	130 W	230 W
Rated Current (I_n):	1600 A	1600 A
Rated Impulse Withstand Voltage (U_{imp}):	12000 V	12000 V
Rated Insulation Voltage (U_i):	1500 V	1500 V
Rated Operational Voltage:	1500 V DC	1500 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw}):	85 kA	85 kA
Rated Uninterrupted Current (I_u):	1600 A	1600 A
Rated Voltage (U_r):	1500 V	1500 V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A



E4.2H-A MS/DC-E 2000A
1500V 4p F



E4.2H-A MS/DC-E 2000A
1500V 4p W MP

Dimensions

Product Net Depth / Length:	270 mm	270 mm
Product Net Height:	371 mm	371 mm
Product Net Weight:	67 kg	81 kg
Product Net Width:	510 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm
---------------------------------	--------	--------

Package Level 1 Gross Weight:	79 kg	95 kg
Package Level 1 Height:	600 mm	600 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter
Version:	F	W

Technical

Current Type:	DC	DC
Number of Poles:	4	4
Power Loss:	200 W	360 W
Rated Current (I_n):	2000 A	2000 A
Rated Impulse Withstand Voltage (U_{imp}):	12000 V	12000 V
Rated Insulation Voltage (U_i):	1500 V	1500 V
Rated Operational Voltage:	1500 V DC	1500 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw}):	85 kA	85 kA
Rated Uninterrupted Current (I_u):	2000 A	2000 A
Rated Voltage (U_r):	1500 V	1500 V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A



**E4.2H-A MS/DC-E 2500A
1500V 4p F**

**E4.2H-A MS/DC-E 2500A
1500V 4p W MP**

Dimensions

Product Net Depth / Length:	270 mm	270 mm
Product Net Height:	371 mm	371 mm
Product Net Weight:	67 kg	81 kg
Product Net Width:	510 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	79 kg	95 kg
Package Level 1 Height:	600 mm	600 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter
Version:	F	W

Technical

Current Type:	DC	DC
Number of Poles:	4	4
Power Loss:	320 W	560 W
Rated Current (I_n):	2500 A	2500 A

Rated Impulse Withstand Voltage (U _{imp}):	12000 V	12000 V
Rated Insulation Voltage (U _i):	1500 V	1500 V
Rated Operational Voltage:	1500 V DC	1500 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA
Rated Uninterrupted Current (I _u):	2500 A	2500 A
Rated Voltage (U _r):	1500 V	1500 V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A



E4.2H-A MS/DC-E 3200A
1500V 4p F



E4.2H-A MS/DC-E 3200A
1500V 4p W MP

Dimensions

Product Net Depth / Length:	270 mm	270 mm
Product Net Height:	371 mm	371 mm
Product Net Weight:	81 kg	85 kg
Product Net Width:	510 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm
Package Level 1 Gross Weight:	95 kg	100 kg
Package Level 1 Height:	600 mm	600 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter
Version:	F	W

Technical

Current Type:	DC	DC
Number of Poles:	4	4
Power Loss:	500 W	800 W
Rated Current (I _n):	3200 A	3200 A
Rated Impulse Withstand Voltage (U _{imp}):	12000 V	12000 V
Rated Insulation Voltage (U _i):	1500 V	1500 V
Rated Operational Voltage:	1500 V DC	1500 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA
Rated Uninterrupted Current (I _u):	3200 A	3200 A
Rated Voltage (U _r):	1500 V	1500 V
Short-Circuit Performance Level:	N	N
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A



E4.2H MS/
DC-E 2000A
1500V 4p F



E4.2H MS/
DC-E 4000A
1500V 4p F



E4.2H MS/
DC-E 3200A
1500V 4p F



E4.2H MS/
DC-E 2500A
1500V 4p F

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm	371 mm
Product Net Weight:	81 kg	81 kg	81 kg	81 kg
Product Net Width:	510 mm	510 mm	510 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	785 mm	785 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	95 kg	95 kg	95 kg	95 kg
Package Level 1 Height:	600 mm	600 mm	600 mm	600 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Version:	F	F	F	F

Technical

Current Type:	DC	DC	DC	DC
Number of Poles:	4	4	4	4
Power Loss:	200 W	620 W	500 W	320 W
Rated Current (I _n):	2000 A	4000 A	3200 A	2500 A
Rated Impulse Withstand Voltage (U _{imp}):	12000 V	12000 V	12000 V	12000 V
Rated Insulation Voltage (U _i):	1500 V	1500 V	1500 V	1500 V
Rated Operational Voltage:	1500 V DC	1500 V DC	1500 V DC	1500 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA	85 kA	85 kA
Rated Uninterrupted Current (I _u):	2000 A	4000 A	3200 A	2500 A
Rated Voltage (U _r):	1500 V	1500 V	1500 V	1500 V
Short-Circuit Performance Level:	N	N	N	N
Standards:	IEC	IEC	IEC	IEC
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical	Rear flat Vertical	Rear flat Vertical



E4.2H MS/
DC-E 1600A
1500V 4p F



E4.2H MS/
DC-E 3200A
1500V 4p W
MP



E4.2H MS/
DC-E 2500A
1500V 4p W
MP



E4.2H MS/
DC-E 2000A
1500V 4p W
MP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm	371 mm
Product Net Weight:	81 kg	85 kg	85 kg	85 kg
Product Net Width:	510 mm	510 mm	510 mm	510 mm

Container Information

Package Level 1 Depth / Length:	785 mm	785 mm	785 mm	785 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	95 kg	100 kg	100 kg	100 kg
Package Level 1 Height:	600 mm	600 mm	600 mm	600 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Product Type:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Version:	F	W	W	W

Technical

Current Type:	DC	DC	DC	DC
Number of Poles:	4	4	4	4
Power Loss:	130 W	800 W	560 W	360 W
Rated Current (I _n):	1600 A	3200 A	2500 A	2000 A
Rated Impulse Withstand Voltage (U _{imp}):	12000 V	12000 V	12000 V	12000 V
Rated Insulation Voltage (U _i):	1500 V	1500 V	1500 V	1500 V
Rated Operational Voltage:	1500 V DC	1500 V DC	1500 V DC	1500 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA	85 kA	85 kA
Rated Uninterrupted Current (I _u):	1600 A	3200 A	2500 A	2000 A
Rated Voltage (U _r):	1500 V	1500 V	1500 V	1500 V
Short-Circuit Performance Level:	N	N	N	N
Standards:	IEC	IEC	IEC	IEC
Sub-type:	E4.2	E4.2	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	N/A	N/A	N/A



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>