

Автоматические выключатели E4H-A/MS, E4H-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E4H-A/MS 3600 3p W MP new

E4H-A/MS 3600 3p W MP new



General Information

Extended Product Type	E4H-A/MS 3600 3p W MP new
Product ID	1SDA061469R1
EAN	8015644639891
Catalog Description	E4H-A/MS 3600 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E4H-A/MS 3600A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639891
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	SD
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Uninterrupted Current (I_u)	3600 A
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E4H-A/MS 3200 3p F HR new

E4H-A/MS 3200 3p F HR new



General Information

Extended Product Type	E4H-A/MS 3200 3p F HR new
Product ID	1SDA061463R1
EAN	8015644639839
Catalog Description	E4H-A/MS 3200 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E4H-A/MS 3200A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639839
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Switch Disconnecter
Product Type	Switch-disconnector
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Uninterrupted Current (I_u)	3200 A
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

PRODUCT-DETAILS

E4H-A/MS 3200 3p W MP new

E4H-A/MS 3200 3p W MP new



General Information

Extended Product Type	E4H-A/MS 3200 3p W MP new
Product ID	1SDA061465R1
EAN	8015644639853
Catalog Description	E4H-A/MS 3200 3p W MP new
Long Description	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E4H-A/MS 3200A UL THREE-POLE NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644639853
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Switch Disconnecter
Product Type	Air Circuit Breaker
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Uninterrupted Current (I_u)	3200 A
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E4H-A/MS 3600 3p F HR new

E4H-A/MS 3600 3p F HR new



General Information

Extended Product Type	E4H-A/MS 3600 3p F HR new
Product ID	1SDA061467R1
EAN	8015644639877
Catalog Description	E4H-A/MS 3600 3p F HR new
Long Description	SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E4H-A/MS 3600A UL THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644639877
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Switch-disconnector
Product Type	SD
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Uninterrupted Current (I _u)	3600 A
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

PRODUCT-DETAILS

E4H-A 3200 PR121/P-LSI In=3200A 3p W MP

E4H-A 3200 PR121/P-LSI In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR121/P-LSI In=3200A 3p W MP
Product ID	1SDA057885R1
EAN	8015644601485
Catalog Description	E4H-A 3200 PR121/P-LSI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601485
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601485

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR121/P-LSIG In=3200A 3p W MP

E4H-A 3200 PR121/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR121/P-LSIG In=3200A 3p W MP
Product ID	1SDA057889R1
EAN	8015644601522
Catalog Description	E4H-A 3200 PR121/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601522
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644601522
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3600 PR123/P-LSIG In=3600A 3p W MP

E4H-A 3600 PR123/P-LSIG In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR123/P-LSIG In=3600A 3p W MP
Product ID	1SDA057941R1
EAN	8015644602048
Catalog Description	E4H-A 3600 PR123/P-LSIG In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644602048
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644602048
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3200 PR123/P-LSIG In=3200A 3p W MP

E4H-A 3200 PR123/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR123/P-LSIG In=3200A 3p W MP
Product ID	1SDA057909R1
EAN	8015644601720
Catalog Description	E4H-A 3200 PR123/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601720
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601720

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LSIG In=3200A 3p W MP

E4H-A 3200 PR122/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR122/P-LSIG In=3200A 3p W MP
Product ID	1SDA057901R1
EAN	8015644601645
Catalog Description	E4H-A 3200 PR122/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601645
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644601645
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3200 PR123/P-LSIG In=3200A 3p F HR

E4H-A 3200 PR123/P-LSIG In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR123/P-LSIG In=3200A 3p F HR
Product ID	1SDA057907R1
EAN	8015644601706
Catalog Description	E4H-A 3200 PR123/P-LSIG In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601706
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601706

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR121/P-LI In=3200A 3p F HR

E4H-A 3200 PR121/P-LI In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR121/P-LI In=3200A 3p F HR
Product ID	1SDA057879R1
EAN	8015644601423
Catalog Description	E4H-A 3200 PR121/P-LI In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601423
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601423

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR122/P-LI In=3600A 3p W MP

E4H-A 3600 PR122/P-LI In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR122/P-LI In=3600A 3p W MP
Product ID	1SDA057925R1
EAN	8015644601881
Catalog Description	E4H-A 3600 PR122/P-LI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601881
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644601881
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3600 PR122/P-LSI In=3600A 3p W MP

E4H-A 3600 PR122/P-LSI In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR122/P-LSI In=3600A 3p W MP
Product ID	1SDA057929R1
EAN	8015644601928
Catalog Description	E4H-A 3600 PR122/P-LSI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601928
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601928

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR121/P-LSIG In=3600A 3p W MP

E4H-A 3600 PR121/P-LSIG In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR121/P-LSIG In=3600A 3p W MP
Product ID	1SDA057921R1
EAN	8015644601843
Catalog Description	E4H-A 3600 PR121/P-LSIG In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601843
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644601843
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LI In=3200A 3p W MP

E4H-A 3200 PR122/P-LI In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR122/P-LI In=3200A 3p W MP
Product ID	1SDA057893R1
EAN	8015644601560
Catalog Description	E4H-A 3200 PR122/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601560
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644601560
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LI In=3200A 3p W MP

E4H-A 3200 PR122/P-LI In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR122/P-LI In=3200A 3p W MP
Product ID	1SDA057893R1
EAN	8015644601560
Catalog Description	E4H-A 3200 PR122/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601560
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information

Package Level 1 EAN	8015644601560
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LSIG In=3200A 3p F HR
E4H-A 3200 PR122/P-LSIG In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR122/P-LSIG In=3200A 3p F HR
Product ID	1SDA057899R1
EAN	8015644601621
Catalog Description	E4H-A 3200 PR122/P-LSIG In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601621
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601621

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LSI In=3200A 3p W MP

E4H-A 3200 PR122/P-LSI In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR122/P-LSI In=3200A 3p W MP
Product ID	1SDA057897R1
EAN	8015644601607
Catalog Description	E4H-A 3200 PR122/P-LSI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601607
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601607

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LI In=3200A 3p F HR

E4H-A 3200 PR122/P-LI In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR122/P-LI In=3200A 3p F HR
Product ID	1SDA057891R1
EAN	8015644601546
Catalog Description	E4H-A 3200 PR122/P-LI In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601546
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601546

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR122/P-LSI In=3200A 3p F HR

E4H-A 3200 PR122/P-LSI In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR122/P-LSI In=3200A 3p F HR
Product ID	1SDA057895R1
EAN	8015644601584
Catalog Description	E4H-A 3200 PR122/P-LSI In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601584
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601584

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR121/P-LSI In=3200A 3p F HR

E4H-A 3200 PR121/P-LSI In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR121/P-LSI In=3200A 3p F HR
Product ID	1SDA057883R1
EAN	8015644601461
Catalog Description	E4H-A 3200 PR121/P-LSI In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601461
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information

Package Level 1 EAN	8015644601461
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	3200 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3200 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3200 PR121/P-LSIG In=3200A 3p F HR

E4H-A 3200 PR121/P-LSIG In=3200A 3p F HR



General Information

Extended Product Type	E4H-A 3200 PR121/P-LSIG In=3200A 3p F HR
Product ID	1SDA057887R1
EAN	8015644601508
Catalog Description	E4H-A 3200 PR121/P-LSIG In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601508
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601508

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 230 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3200 PR121/P-LI In=3200A 3p W MP

E4H-A 3200 PR121/P-LI In=3200A 3p W MP



General Information

Extended Product Type	E4H-A 3200 PR121/P-LI In=3200A 3p W MP
Product ID	1SDA057881R1
EAN	8015644601447
Catalog Description	E4H-A 3200 PR121/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601447
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601447

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 422 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3200 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3200 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR121/P-LSI In=3600A 3p W MP

E4H-A 3600 PR121/P-LSI In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR121/P-LSI In=3600A 3p W MP
Product ID	1SDA057917R1
EAN	8015644601805
Catalog Description	E4H-A 3600 PR121/P-LSI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601805
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601805

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR121/P-LI In=3600A 3p F HR

E4H-A 3600 PR121/P-LI In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR121/P-LI In=3600A 3p F HR
Product ID	1SDA057911R1
EAN	8015644601744
Catalog Description	E4H-A 3600 PR121/P-LI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601744
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information

Package Level 1 EAN	8015644601744
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3600 PR121/P-LI In=3600A 3p W MP

E4H-A 3600 PR121/P-LI In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR121/P-LI In=3600A 3p W MP
Product ID	1SDA057913R1
EAN	8015644601768
Catalog Description	E4H-A 3600 PR121/P-LI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601768
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601768

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA
	(600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR121/P-LSIG In=3600A 3p F HR

E4H-A 3600 PR121/P-LSIG In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR121/P-LSIG In=3600A 3p F HR
Product ID	1SDA057919R1
EAN	8015644601829
Catalog Description	E4H-A 3600 PR121/P-LSIG In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601829
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601829

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR121/P-LSI In=3600A 3p F HR

E4H-A 3600 PR121/P-LSI In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR121/P-LSI In=3600A 3p F HR
Product ID	1SDA057915R1
EAN	8015644601782
Catalog Description	E4H-A 3600 PR121/P-LSI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601782
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information

Package Level 1 EAN	8015644601782
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3600 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL 1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
-------------------------------------	---

PRODUCT-DETAILS

E4H-A 3600 PR122/P-LSIG In=3600A 3p W MP

E4H-A 3600 PR122/P-LSIG In=3600A 3p W MP



General Information

Extended Product Type	E4H-A 3600 PR122/P-LSIG In=3600A 3p W MP
Product ID	1SDA057933R1
EAN	8015644601966
Catalog Description	E4H-A 3600 PR122/P-LSIG In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-A-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601966
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Container Information	
Package Level 1 EAN	8015644601966

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 535 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR123/P-LSIG In=3600A 3p F HR

E4H-A 3600 PR123/P-LSIG In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR123/P-LSIG In=3600A 3p F HR
Product ID	1SDA057939R1
EAN	8015644602024
Catalog Description	E4H-A 3600 PR123/P-LSIG In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644602024
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644602024

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR122/P-LSIG In=3600A 3p F HR

E4H-A 3600 PR122/P-LSIG In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR122/P-LSIG In=3600A 3p F HR
Product ID	1SDA057931R1
EAN	8015644601942
Catalog Description	E4H-A 3600 PR122/P-LSIG In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644601942
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information

Package Level 1 EAN	8015644601942
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I_u)	3600 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
------------------------------------	---

PRODUCT-DETAILS

E4H-A 3600 PR122/P-LSI In=3600A 3p F HR

E4H-A 3600 PR122/P-LSI In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR122/P-LSI In=3600A 3p F HR
Product ID	1SDA057927R1
EAN	8015644601904
Catalog Description	E4H-A 3600 PR122/P-LSI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601904
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601904

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA

PRODUCT-DETAILS

E4H-A 3600 PR122/P-LI In=3600A 3p F HR

E4H-A 3600 PR122/P-LI In=3600A 3p F HR



General Information

Extended Product Type	E4H-A 3600 PR122/P-LI In=3600A 3p F HR
Product ID	1SDA057923R1
EAN	8015644601867
Catalog Description	E4H-A 3600 PR122/P-LI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644601867
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Container Information	
Package Level 1 EAN	8015644601867

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 292 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	3600 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
Rated Uninterrupted Current (I _u)	3600 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E4
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 100 kA
to UL1066	(480 V AC) 85 kA (600 V AC) 85 kA



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>