

Автоматические выключатели E4L-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E4L-A 3600 PR121/P-LSIG In=3600A 3p W MP

E4L-A 3600 PR121/P-LSIG In=3600A 3p W MP



General Information

Extended Product Type	E4L-A 3600 PR121/P-LSIG In=3600A 3p W MP
Product ID	1SDA061213R1
EAN	8015644637361
Catalog Description	E4L-A 3600 PR121/P-LSIG In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637361
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3200 PR123/P-LSIG In=3200A 3p F HR

E4L-A 3200 PR123/P-LSIG In=3200A 3p F HR



General Information

Extended Product Type	E4L-A 3200 PR123/P-LSIG In=3200A 3p F HR
Product ID	1SDA061199R1
EAN	8015644637224
Catalog Description	E4L-A 3200 PR123/P-LSIG In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637224
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 340 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3200 PR122/P-LSIG In=3200A 3p F HR

E4L-A 3200 PR122/P-LSIG In=3200A 3p F HR



General Information

Extended Product Type	E4L-A 3200 PR122/P-LSIG In=3200A 3p F HR
Product ID	1SDA061191R1
EAN	8015644637149
Catalog Description	E4L-A 3200 PR122/P-LSIG In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637149
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 340 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LI In=3600A 3p W MP

E4L-A 3600 PR122/P-LI In=3600A 3p W MP



General Information

Extended Product Type	E4L-A 3600 PR122/P-LI In=3600A 3p W MP
Product ID	1SDA061217R1
EAN	8015644637408
Catalog Description	E4L-A 3600 PR122/P-LI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637408
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3600 PR121/P-LSI In=3600A 3p W MP

E4L-A 3600 PR121/P-LSI In=3600A 3p W MP



General Information

Extended Product Type	E4L-A 3600 PR121/P-LSI In=3600A 3p W MP
Product ID	1SDA061209R1
EAN	8015644637323
Catalog Description	E4L-A 3600 PR121/P-LSI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637323
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3200 PR123/P-LSIG In=3200A 3p W MP

E4L-A 3200 PR123/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E4L-A 3200 PR123/P-LSIG In=3200A 3p W MP
Product ID	1SDA061201R1
EAN	8015644637248
Catalog Description	E4L-A 3200 PR123/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637248
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 541 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3600 PR121/P-LI In=3600A 3p W MP

E4L-A 3600 PR121/P-LI In=3600A 3p W MP



General Information

Extended Product Type	E4L-A 3600 PR121/P-LI In=3600A 3p W MP
Product ID	1SDA061205R1
EAN	8015644637286
Catalog Description	E4L-A 3600 PR121/P-LI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637286
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3600 PR121/P-LI In=3600A 3p F HR

E4L-A 3600 PR121/P-LI In=3600A 3p F HR



General Information

Extended Product Type	E4L-A 3600 PR121/P-LI In=3600A 3p F HR
Product ID	1SDA061203R1
EAN	8015644637262
Catalog Description	E4L-A 3600 PR121/P-LI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637262
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 430 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LSIG In=3600A 3p W MP

E4L-A 3600 PR122/P-LSIG In=3600A 3p W MP



General Information

Extended Product Type	E4L-A 3600 PR122/P-LSIG In=3600A 3p W MP
Product ID	1SDA061225R1
EAN	8015644637484
Catalog Description	E4L-A 3600 PR122/P-LSIG In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637484
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LSI In=3600A 3p W MP

E4L-A 3600 PR122/P-LSI In=3600A 3p W MP



General Information

Extended Product Type	E4L-A 3600 PR122/P-LSI In=3600A 3p W MP
Product ID	1SDA061221R1
EAN	8015644637446
Catalog Description	E4L-A 3600 PR122/P-LSI In=3600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637446
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LSI In=3600A 4p W MP

E4L-A 3600 PR122/P-LSI In=3600A 4p W MP



General Information

Extended Product Type	E4L-A 3600 PR122/P-LSI In=3600A 4p W MP
Product ID	1SDA061222R1
EAN	8015644637453
Catalog Description	E4L-A 3600 PR122/P-LSI In=3600A 4p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3600A UL FOUR-POLE OVERCURRENT RELEASE PR122/P-A-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637453
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	684 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	96 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Neutral Pole Current ([% I _n])	50 %
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 684 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LSIG In=3600A 3p F HR

E4L-A 3600 PR122/P-LSIG In=3600A 3p F HR



General Information

Extended Product Type	E4L-A 3600 PR122/P-LSIG In=3600A 3p F HR
Product ID	1SDA061223R1
EAN	8015644637460
Catalog Description	E4L-A 3600 PR122/P-LSIG In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637460
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 430 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	3600 A
Rated Voltage (U_r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3200 PR122/P-LI In=3200A 3p W MP

E4L-A 3200 PR122/P-LI In=3200A 3p W MP



General Information

Extended Product Type	E4L-A 3200 PR122/P-LI In=3200A 3p W MP
Product ID	1SDA061185R1
EAN	8015644637088
Catalog Description	E4L-A 3200 PR122/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637088
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 541 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3200 PR122/P-LSI In=3200A 3p W MP

E4L-A 3200 PR122/P-LSI In=3200A 3p W MP



General Information

Extended Product Type	E4L-A 3200 PR122/P-LSI In=3200A 3p W MP
Product ID	1SDA061189R1
EAN	8015644637125
Catalog Description	E4L-A 3200 PR122/P-LSI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637125
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 541 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3200 PR122/P-LSI In=3200A 3p F HR

E4L-A 3200 PR122/P-LSI In=3200A 3p F HR



General Information

Extended Product Type	E4L-A 3200 PR122/P-LSI In=3200A 3p F HR
Product ID	1SDA061187R1
EAN	8015644637101
Catalog Description	E4L-A 3200 PR122/P-LSI In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637101
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 340 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3200 PR122/P-LI In=3200A 3p F HR

E4L-A 3200 PR122/P-LI In=3200A 3p F HR



General Information

Extended Product Type	E4L-A 3200 PR122/P-LI In=3200A 3p F HR
Product ID	1SDA061183R1
EAN	8015644637064
Catalog Description	E4L-A 3200 PR122/P-LI In=3200A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637064
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 340 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LSI In=3600A 3p F HR

E4L-A 3600 PR122/P-LSI In=3600A 3p F HR



General Information

Extended Product Type	E4L-A 3600 PR122/P-LSI In=3600A 3p F HR
Product ID	1SDA061219R1
EAN	8015644637422
Catalog Description	E4L-A 3600 PR122/P-LSI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637422
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 430 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3600 PR121/P-LSIG In=3600A 3p F HR

E4L-A 3600 PR121/P-LSIG In=3600A 3p F HR



General Information

Extended Product Type	E4L-A 3600 PR121/P-LSIG In=3600A 3p F HR
Product ID	1SDA061211R1
EAN	8015644637347
Catalog Description	E4L-A 3600 PR121/P-LSIG In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644637347
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 430 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E4L-A 3600 PR122/P-LI In=3600A 3p F HR

E4L-A 3600 PR122/P-LI In=3600A 3p F HR



General Information

Extended Product Type	E4L-A 3600 PR122/P-LI In=3600A 3p F HR
Product ID	1SDA061215R1
EAN	8015644637385
Catalog Description	E4L-A 3600 PR122/P-LI In=3600A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E4L-A 3600A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637385
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	566 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	81 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 430 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	3600 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	F

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E4L-A 3200 PR122/P-LSIG In=3200A 3p W MP

E4L-A 3200 PR122/P-LSIG In=3200A 3p W MP



General Information

Extended Product Type	E4L-A 3200 PR122/P-LSIG In=3200A 3p W MP
Product ID	1SDA061193R1
EAN	8015644637163
Catalog Description	E4L-A 3200 PR122/P-LSIG In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4L-A 3200A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644637163
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	594 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	85 kg

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 5000 cycle Ue = 508 ... 635 V 5000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 541 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	3200 A
Rated Voltage (U _r)	600 V
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	L
Standards	UL 1066
Sub-type	E4
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>