

Автоматические выключатели Emax2

E6.2H-A/f, E6.2H-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



**E6.2H-A/f 4000
Ekip Dip LI 4p
WMP**

**E6.2H-A/f 4000
Ekip Dip LSI 4p
WMP**

**E6.2H-A/f 4000
Ekip Dip LSI 4p
WMP**

Dimensions

Product Net Depth / Length:	393 mm	393 mm	393 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1055 mm	1055 mm	1055 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	180 kg	180 kg	180 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	W

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour

Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LSI	Ekip Dip LSIG
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A/f 4000
Ekip Dip LSI 4p
F HR



E6.2H-A/f 4000
Ekip Dip LI 4p F
HR



E6.2H-A/f 4000
Ekip Dip LSIG 4p
F HR

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1014 mm	1014 mm	1014 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	159 kg	159 kg	159 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W
Rated Current (I _n):	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LI	Ekip Dip LSIg
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A/f
4000 Ekip Hi-Touch LSI 4p
F HR



E6.2H-A/f
4000 Ekip Hi-Touch LSI 4p
F HR



E6.2H-A/f
4000 Ekip Hi-Touch LSI 4p
WMP



E6.2H-A/f
4000 Ekip Hi-Touch LSI 4p
WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	135 kg	135 kg	135 kg	135 kg
Product Net Width:	1014 mm	1014 mm	1055 mm	1055 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	159 kg	159 kg	180 kg	180 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Je = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A/f 4000
Ekip Touch LI
4p WMP



E6.2H-A/f 4000
Ekip Touch LSI
4p WMP



E6.2H-A/f 4000
Ekip Touch LSIG
4p WMP

Dimensions

Product Net Depth / Length:	393 mm	393 mm	393 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1055 mm	1055 mm	1055 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	180 kg	180 kg	180 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	W

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LSI	Ekip Touch LSIG
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A/f
4000 Ekip
Touch LSI 4p
F HR



E6.2H-A/f
4000 Ekip
Touch LSIG
4p F HR



E6.2H-A/f
4000 Ekip
Touch LI 4p F
HR

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1014 mm	1014 mm	1014 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	159 kg	159 kg	159 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W
Rated Current (I _n):	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSIG	Ekip Touch LI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A/f 5000
Ekip Dip LI 4p
WMP



E6.2H-A/f 5000
Ekip Dip LSI 4p
WMP



E6.2H-A/f 5000
Ekip Dip LSIG 4p
WMP



Dimensions

Product Net Depth / Length:	393 mm	393 mm	393 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1055 mm	1055 mm	1055 mm



Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	180 kg	180 kg	180 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm



Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	W



Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A

Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LSI	Ekip Dip LSIg
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A/f 5000
Ekip Dip LSIg
4p F HR



E6.2H-A/f 5000
Ekip Dip LI 4p F
HR



E6.2H-A/f 5000
Ekip Dip LSI 4p
F HR

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1014 mm	1014 mm	1014 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	159 kg	159 kg	159 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour

Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W
Rated Current (I _n):	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LI	Ekip Dip LSI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A/f
5000 Ekip Hi-
Touch LSI 4p
F HR

E6.2H-A/f
5000 Ekip Hi-
Touch LSI 4p F HR

E6.2H-A/f
5000 Ekip Hi-
Touch LSI 4p WMP

E6.2H-A/f
5000 Ekip Hi-
Touch LSI 4p
WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	135 kg	135 kg	135 kg	135 kg
Product Net Width:	1014 mm	1014 mm	1055 mm	1055 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	159 kg	159 kg	180 kg	180 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A/f
5000 Ekip
Touch LSI 4p
WMP



E6.2H-A/f
5000 Ekip
Touch LI 4p
WMP



E6.2H-A/f
5000 Ekip
Touch LSiG
4p WMP

Dimensions

Product Net Depth / Length:	393 mm	393 mm	393 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1055 mm	1055 mm	1055 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	180 kg	180 kg	180 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	W

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle	Ue =< 508 V 3000 cycle	Ue =< 508 V 3000 cycle

Mechanical Durability:	Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue = 508 ... 635 V 2000 cycl 10 cycles per hour
	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LI	Ekip Touch LSIG
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



**E6.2H-A/f
5000 Ekip
Touch LSI 4p
F HR**



**E6.2H-A/f
5000 Ekip
Touch LSI 4p F HR**



**E6.2H-A/f
5000 Ekip
Touch LI 4p F
HR**

Dimensions

Product Net Depth / Length:	270 mm	270 mm	270 mm
Product Net Height:	371 mm	371 mm	371 mm
Product Net Weight:	135 kg	135 kg	135 kg
Product Net Width:	1014 mm	1014 mm	1014 mm

Container Information

Package Level 1 Depth / Length:	1257 mm	1257 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	159 kg	159 kg	159 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	F

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycl 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour

Neutral Pole Current ([%I _n]):	100 %	100 %	100 %
Number of Poles:	4 / f	4 / f	4 / f
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W
Rated Current (I _n):	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSIg	Ekip Touch LI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---



E6.2H-A 4000
Ekip Dip LI 3p
F HR



E6.2H-A 4000
Ekip Dip LI 4p
F HR



E6.2H-A 4000
Ekip Dip LI 3p
WMP



E6.2H-A 4000
Ekip Dip LI 4p
WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	762 mm	888 mm	803 mm	929 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1000 mm	1127 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	126 kg	143 kg	147 kg	163 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Ie = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	N/A	50 %	N/A	50 %
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 4000
Ekip Dip LSI
3p F HR



E6.2H-A 4000
Ekip Dip LSI
4p F HR



E6.2H-A 4000
Ekip Dip LSI
3p WMP



E6.2H-A 4000
Ekip Dip LSI
4p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	762 mm	888 mm	803 mm	929 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1000 mm	1127 mm
Package Level 1 EAN:	8015644852528	8015644853723	8015644854928	8015644856120
Package Level 1 Gross Weight:	126 kg	143 kg	147 kg	163 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Je = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	N/A	50 %	N/A	50 %
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H

Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 4000
Ekip Dip LSIG
4p F HR



E6.2H-A 4000
Ekip Dip LSIG
3p F HR



E6.2H-A 4000
Ekip Dip LSIG
4p WMP



E6.2H-A 4000
Ekip Dip LSIG
3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle e = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour

Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _N]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _N):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSIg	Ekip Dip LSIg	Ekip Dip LSIg	Ekip Dip LSIg
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



E6.2H-A
4000 Ekip
Hi-Touch LSI
3p WMP



E6.2H-A
4000 Ekip
Hi-Touch LSI
4p WMP



E6.2H-A
4000 Ekip
Hi-Touch LSI
3p F HR



E6.2H-A
4000 Ekip
Hi-Touch LSI
4p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	116 kg	116 kg	112 kg	112 kg
Product Net Width:	803 mm	929 mm	762 mm	888 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1000 mm	1127 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	147 kg	163 kg	126 kg	143 kg

Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle e = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	N/A	50 %	N/A	50 %
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



E6.2H-A
4000 Ekip
Hi-Touch
LSIG 3p F HR



E6.2H-A
4000 Ekip
Hi-Touch
LSIG 4p F HR



E6.2H-A
4000 Ekip
Hi-Touch
LSIG 4p WMP



E6.2H-A
4000 Ekip
Hi-Touch
LSIG 3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	762 mm	888 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1127 mm	1000 mm
Package Level 1 EAN:	8015644852597	8015644853792	8015644856199	8015644854997
Package Level 1 Gross Weight:	126 kg	143 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle e = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	N/A	50 %	50 %	N/A
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 4000
Ekip Touch LI
4p F HR



E6.2H-A 4000
Ekip Touch LI
3p F HR



E6.2H-A 4000
Ekip Touch LI
4p WMP



E6.2H-A 4000
Ekip Touch LI
3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Je = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour

Neutral Pole Current ([%I _n]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 4000
Ekip Touch LSI
4p F HR



E6.2H-A 4000
Ekip Touch LSI
3p F HR



E6.2H-A 4000
Ekip Touch LSI
4p WMP



E6.2H-A 4000
Ekip Touch LSI
3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle Je = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 4000
Ekip Touch
LSIG 4p F HR



E6.2H-A 4000
Ekip Touch
LSIG 3p F HR



E6.2H-A 4000
Ekip Touch
LSIG 4p WMP



E6.2H-A 4000
Ekip Touch
LSIG 3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information				
Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information				
Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical				
Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 4000 cycle e = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour	Ue =< 508 V 4000 cycle Ue = 508 ... 635 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 476 W	at Rated Operating Conditions per Pole 646 W	at Rated Operating Conditions per Pole 646 W
Rated Current (I _n):	4000 A	4000 A	4000 A	4000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA				
Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA



E6.2H-A 5000
Ekip Dip LI 4p
F HR



E6.2H-A 5000
Ekip Dip LI 3p
F HR



E6.2H-A 5000
Ekip Dip LI 4p
WMP



E6.2H-A 5000
Ekip Dip LI 3p
WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Je = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI	Ekip Dip LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H

Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 5000
Ekip Dip LSI
3p WMP



E6.2H-A 5000
Ekip Dip LSI
4p WMP



E6.2H-A 5000
Ekip Dip LSI
3p F HR



E6.2H-A 5000
Ekip Dip LSI 4p
F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	116 kg	116 kg	112 kg	112 kg
Product Net Width:	803 mm	929 mm	762 mm	888 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1000 mm	1127 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	147 kg	163 kg	126 kg	143 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Je = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour

Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	N/A	50 %	N/A	50 %
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI	Ekip Dip LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



E6.2H-A 5000
Ekip Dip LSI
4p F HR



E6.2H-A 5000
Ekip Dip LSI
3p F HR



E6.2H-A 5000
Ekip Dip LSI
4p WMP



E6.2H-A 5000
Ekip Dip LSI
3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Dip LSIG	Ekip Dip LSIG	Ekip Dip LSIG	Ekip Dip LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
--	---	---	---	---



E6.2H-A
5000 Ekip
Hi-Touch LSI
3p WMP



E6.2H-A
5000 Ekip
Hi-Touch LSI
4p WMP



E6.2H-A
5000 Ekip
Hi-Touch LSI
3p F HR



E6.2H-A
5000 Ekip
Hi-Touch LSI
4p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	116 kg	116 kg	112 kg	112 kg
Product Net Width:	803 mm	929 mm	762 mm	888 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1000 mm	1127 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	147 kg	163 kg	126 kg	143 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current (I _n):	N/A	50 %	N/A	50 %
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI	Ekip Hi-Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA	(254 V) 85 kA	(254 V) 85 kA	(254 V) 85 kA
	(508 V) 85 kA	(508 V) 85 kA	(508 V) 85 kA	(508 V) 85 kA
	(635 V) 85 kA	(635 V) 85 kA	(635 V) 85 kA	(635 V) 85 kA



E6.2H-A
5000 Ekip
Hi-Touch
LSIG 4p F HR



E6.2H-A
5000 Ekip
Hi-Touch
LSIG 3p F HR



E6.2H-A
5000 Ekip
Hi-Touch
LSIG 4p WMP



E6.2H-A
5000 Ekip
Hi-Touch
LSIG 3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour

Neutral Pole Current ([%I _n):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 5000
Ekip Touch LI
3p WMP



E6.2H-A 5000
Ekip Touch LI
4p WMP



E6.2H-A 5000
Ekip Touch LI
3p F HR



E6.2H-A 5000
Ekip Touch LI
4p F HR

Dimensions

Product Net Depth / Length:	393 mm	393 mm	270 mm	270 mm
Product Net Height:	425 mm	425 mm	371 mm	371 mm
Product Net Weight:	116 kg	116 kg	112 kg	112 kg
Product Net Width:	803 mm	929 mm	762 mm	888 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1127 mm	1000 mm	1127 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	147 kg	163 kg	126 kg	143 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	F	F

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Je = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	N/A	50 %	N/A	50 %
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI	Ekip Touch LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	N/A	N/A	Rear flat Horizontal	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 5000
Ekip Touch LSI
4p F HR



E6.2H-A 5000
Ekip Touch LSI
3p F HR



E6.2H-A 5000
Ekip Touch LSI
4p WMP



E6.2H-A 5000
Ekip Touch LSI
3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Ise = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ise = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ise = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ise = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current (I%lu):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI	Ekip Touch LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 5000
Ekip Touch
LSIG 4p F HR

E6.2H-A 5000
Ekip Touch
LSIG 3p F HR

E6.2H-A 5000
Ekip Touch
LSIG 4p WMP

E6.2H-A 5000
Ekip Touch
LSIG 3p WMP

Dimensions

Product Net Depth / Length:	270 mm	270 mm	393 mm	393 mm
Product Net Height:	371 mm	371 mm	425 mm	425 mm
Product Net Weight:	112 kg	112 kg	116 kg	116 kg
Product Net Width:	888 mm	762 mm	929 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1127 mm	1000 mm
Package Level 1 Gross Weight:	143 kg	126 kg	163 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	F	F	W	W

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	Ue =< 508 V 3000 cycle Je = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 2000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour	12000 cycle 60 cycles per hour
Neutral Pole Current ([%I _n]):	50 %	N/A	50 %	N/A
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 700 W	at Rated Operating Conditions per Pole 950 W	at Rated Operating Conditions per Pole 950 W
Rated Current (I _n):	5000 A	5000 A	5000 A	5000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Voltage (U _r):	600 V	600 V	600 V	600 V
Release:	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG	Ekip Touch LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL

Standards:	UL	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	N/A	N/A

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
-------------------------------------	---	---	---	---



E6.2H-A 6000
Ekip Dip LSI
3p WMP



E6.2H-A 6000
Ekip Dip LI 3p
WMP



E6.2H-A 6000
Ekip Dip LSI
3p WMP

Dimensions

Product Net Depth / Length:	393 mm	393 mm	393 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	116 kg	116 kg	116 kg
Product Net Width:	803 mm	803 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1000 mm	1000 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	147 kg	147 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	W

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue = 500 ... 690 V 2000 cycle	Ue = 500 ... 690 V 2000 cycle	Ue = 500 ... 690 V 2000 cycl
Mechanical Durability:	12000 cycle	12000 cycle	12000 cycle
Number of Poles:	3	3	3
Rated Current (I _n):	6000 A	6000 A	6000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs}):	100 %	100 %	100 %
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA	85 kA
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Dip LSI	Ekip Dip LI	Ekip Dip LSIG
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2



E6.2H-A 6000 Ekip Hi-Touch LSIG 3p WMP



E6.2H-A 6000 Ekip Hi-Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	393 mm	393 mm
Product Net Height:	425 mm	425 mm
Product Net Weight:	116 kg	116 kg
Product Net Width:	803 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1000 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	147 kg	147 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W

Technical

Current Type:	AC	AC
Electrical Durability:	Ue = 500 ... 690 V 2000 cycle	Ue = 500 ... 690 V 2000 cycle
Mechanical Durability:	12000 cycle	12000 cycle
Number of Poles:	3	3
Rated Current (I _n):	6000 A	6000 A
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs}):	100 %	100 %
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA
Rated Voltage (U _r):	600 V	600 V
Release:	Ekip Hi-Touch LSIG	Ekip Hi-Touch LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	H	H
Standards:	UL	UL
Sub-type:	E6.2	E6.2



E6.2H-A 6000 Ekip
Touch LI 3p WMP

E6.2H-A 6000 Ekip
Touch LSIG 3p
WMP

E6.2H-A 6000 Ekip
Touch LSI 3p WMP

Dimensions

Product Net Depth / Length:	393 mm	393 mm	393 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	116 kg	116 kg	116 kg
Product Net Width:	803 mm	803 mm	803 mm

Container Information

Package Level 1 Depth / Length:	1000 mm	1000 mm	1000 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	147 kg	147 kg	147 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	515 mm	515 mm	515 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Product Type:	Air Circuit Breaker	Air Circuit Breaker	Air Circuit Breaker
Version:	W	W	W

Technical

Current Type:	AC	AC	AC
Electrical Durability:	Ue = 500 ... 690 V 2000 cycle	Ue = 500 ... 690 V 2000 cycle	Ue = 500 ... 690 V 2000 cycl
Mechanical Durability:	12000 cycle	12000 cycle	12000 cycle
Number of Poles:	3	3	3
Rated Current (I_n):	6000 A	6000 A	6000 A
Rated Insulation Voltage (U_i):	AC 635 V	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC

Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs}):	100 %	100 %	100 %
Rated Short-time Withstand Current Low Voltage (I _{cw}):	85 kA	85 kA	85 kA
Rated Voltage (U _r):	600 V	600 V	600 V
Release:	Ekip Touch LI	Ekip Touch LSIG	Ekip Touch LSI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	H	H	H
Standards:	UL	UL	UL
Sub-type:	E6.2	E6.2	E6.2



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>