

Автоматические выключатели E6L-A

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E6L-A 5000 PR122/P-LI In=5000A 3p W MP

E6L-A 5000 PR122/P-LI In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR122/P-LI In=5000A 3p W MP
Product ID	1SDA061313R1
EAN	8015644638368
Catalog Description	E6L-A 5000 PR122/P-LI In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644638368
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	5000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	5000 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E6L-A 5000 PR123/P-LSIG In=5000A 3p F HR

E6L-A 5000 PR123/P-LSIG In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR123/P-LSIG In=5000A 3p F HR
Product ID	1SDA061327R1
EAN	8015644638504
Catalog Description	E6L-A 5000 PR123/P-LSIG In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR123/P-LSIG R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638504
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR121/P-LI In=5000A 3p F HR

E6L-A 5000 PR121/P-LI In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR121/P-LI In=5000A 3p F HR
Product ID	1SDA061299R1
EAN	8015644638221
Catalog Description	E6L-A 5000 PR121/P-LI In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644638221
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	5000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	5000 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E6L-A 5000 PR122/P-LSIG In=5000A 3p F HR

E6L-A 5000 PR122/P-LSIG In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR122/P-LSIG In=5000A 3p F HR
Product ID	1SDA061319R1
EAN	8015644638429
Catalog Description	E6L-A 5000 PR122/P-LSIG In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIG R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644638429
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I_n)	5000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	5000 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E6L-A 5000 PR121/P-LSI In=5000A 3p F HR

E6L-A 5000 PR121/P-LSI In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR121/P-LSI In=5000A 3p F HR
Product ID	1SDA061303R1
EAN	8015644638269
Catalog Description	E6L-A 5000 PR121/P-LSI In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638269
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR121/P-LSIG In=5000A 3p W MP

E6L-A 5000 PR121/P-LSIG In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR121/P-LSIG In=5000A 3p W MP
Product ID	1SDA061309R1
EAN	8015644638320
Catalog Description	E6L-A 5000 PR121/P-LSIG In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSIG R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644638320
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	5000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	5000 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E6L-A 5000 PR121/P-LI In=5000A 3p W MP

E6L-A 5000 PR121/P-LI In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR121/P-LI In=5000A 3p W MP
Product ID	1SDA061301R1
EAN	8015644638245
Catalog Description	E6L-A 5000 PR121/P-LI In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644638245
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 EAN	8015644609139
---------------------	---------------

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I_n)	5000 A
Rated Voltage (U_r)	600 V
Rated Operational Current (I_e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	5000 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
------------------------------------	---

PRODUCT-DETAILS

E6L-A 5000 PR121/P-LSIG In=5000A 3p F HR

E6L-A 5000 PR121/P-LSIG In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR121/P-LSIG In=5000A 3p F HR
Product ID	1SDA061307R1
EAN	8015644638306
Catalog Description	E6L-A 5000 PR121/P-LSIG In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638306
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR121/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR121/P-LSI In=5000A 3p W MP

E6L-A 5000 PR121/P-LSI In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR121/P-LSI In=5000A 3p W MP
Product ID	1SDA061305R1
EAN	8015644638283
Catalog Description	E6L-A 5000 PR121/P-LSI In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638283
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR123/P-LSIG In=5000A 3p W MP

E6L-A 5000 PR123/P-LSIG In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR123/P-LSIG In=5000A 3p W MP
Product ID	1SDA061329R1
EAN	8015644638528
Catalog Description	E6L-A 5000 PR123/P-LSIG In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR123/P-LSIG R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638528
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR123/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA
	(600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR122/P-LSIG In=5000A 3p W MP

E6L-A 5000 PR122/P-LSIG In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR122/P-LSIG In=5000A 3p W MP
Product ID	1SDA061321R1
EAN	8015644638443
Catalog Description	E6L-A 5000 PR122/P-LSIG In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638443
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR122/P-LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR122/P-LSI In=5000A 3p F HR

E6L-A 5000 PR122/P-LSI In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR122/P-LSI In=5000A 3p F HR
Product ID	1SDA061315R1
EAN	8015644638382
Catalog Description	E6L-A 5000 PR122/P-LSI In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638382
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR122/P-LI In=5000A 3p F HR

E6L-A 5000 PR122/P-LI In=5000A 3p F HR



General Information

Extended Product Type	E6L-A 5000 PR122/P-LI In=5000A 3p F HR
Product ID	1SDA061311R1
EAN	8015644638344
Catalog Description	E6L-A 5000 PR122/P-LI In=5000A 3p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638344
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	782 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	112 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 675 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA (600 V AC) 100 kA

PRODUCT-DETAILS

E6L-A 5000 PR122/P-LSI In=5000A 3p W MP

E6L-A 5000 PR122/P-LSI In=5000A 3p W MP



General Information

Extended Product Type	E6L-A 5000 PR122/P-LSI In=5000A 3p W MP
Product ID	1SDA061317R1
EAN	8015644638405
Catalog Description	E6L-A 5000 PR122/P-LSI In=5000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E6L-A 5000A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
EAN	8015644638405
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information	
Package Level 1 EAN	8015644609139

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 3000 cycle Ue = 508 ... 635 V 3000 cycle 30 cycles per hour
Mechanical Durability	8000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 1025 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CBMP
Rated Current (I _n)	5000 A
Rated Voltage (U _r)	600 V
Rated Operational Current (I _e)	5000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(240 V AC) 150 kA (480 V AC) 150 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I _u)	5000 A
Release	PR122/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL 1066
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

Technical UL/CSA	
	(240 V AC) 150 kA
to UL1066	(480 V AC) 150 kA
	(600 V AC) 100 kA



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>