

Автоматические выключатели Е6МТ, Е6МТР

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>

PRODUCT-DETAILS

E6MTPEarth.Sw.-LowTerm.63004pWMPnew

E6MTP Earth.Sw.-LowTerm.6300 4p W MP new



Product image
not available

General Information

Extended Product Type	E6MTPEarth.Sw.-LowTerm.63004pWMPnew
Product ID	1SDA059114R1
EAN	8015644614737
Catalog Description	E6MTP Earth.Sw.-LowTerm.6300 4p W MP new
Long Description	SACE EMAX MOVING PART FOR E6/MTP 6300A FOUR-POLE WITH LOWER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614737
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	936 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	134 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	157 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	4
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing switch with making capacity MTP
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTPEarth.Sw.-Up.Term.63004pWMPnew

E6MTP Earth.Sw.-Up.Term.6300 4p W MP new



Product image
not available

General Information

Extended Product Type	E6MTPEarth.Sw.-Up.Term.63004pWMPnew
Product ID	1SDA059113R1
EAN	8015644614720
Catalog Description	E6MTP Earth.Sw.-Up.Term.6300 4p W MP new
Long Description	SACE EMAX MOVING PART FOR E6/MTP 6300A FOUR-POLE WITH UPPER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614720
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	936 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	134 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	157 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	4
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing switch with making capacity MTP
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTPEarth.Sw.-Up.Term.63003pWMPnew

E6MTP Earth.Sw.-Up.Term.6300 3p W MP new



Product image
not available

General Information

Extended Product Type	E6MTPEarth.Sw.-Up.Term.63003pWMPnew
Product ID	1SDA059111R1
EAN	8015644614706
Catalog Description	E6MTP Earth.Sw.-Up.Term.6300 3p W MP new
Long Description	SACE EMAX MOVING PART FOR E6/MTP 6300A THREE-POLE WITH UPPER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614706
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	138 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	3
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing switch with making capacity MTP
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTPEarth.Sw.-LowTerm.63003pWMPnew

E6MTP Earth.Sw.-LowTerm.6300 3p W MP new



Product image
not available

General Information

Extended Product Type	E6MTPEarth.Sw.-LowTerm.63003pWMPnew
Product ID	1SDA059112R1
EAN	8015644614713
Catalog Description	E6MTP Earth.Sw.-LowTerm.6300 3p W MP new
Long Description	SACE EMAX MOVING PART FOR E6/MTP 6300A THREE-POLE WITH LOWER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614713
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	138 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	3
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing switch with making capacity MTP
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTEarth.truckUp.Term.63004pWMPnew

E6MT Earth.truckUp.Term.6300 4p W MP new



Product image
not available

General Information

Extended Product Type	E6MTEarth.truckUp.Term.63004pWMPnew
Product ID	1SDA059133R1
EAN	8015644614928
Catalog Description	E6MT Earth.truckUp.Term.6300 4p W MP new
Long Description	SACE EMAX MOVING PART FOR E6V/MT 6300A FOUR-POLE WITH UPPER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614928
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	936 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	134 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	157 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	4
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing truck MT
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTEarth.truckLowTerm.63004pWMPnew

E6MT Earth.truckLowTerm.6300 4p W MP new



Product image
not available

General Information

Extended Product Type	E6MTEarth.truckLowTerm.63004pWMPnew
Product ID	1SDA059134R1
EAN	8015644614935
Catalog Description	E6MT Earth.truckLowTerm.6300 4p W MP new
Long Description	SACE EMAX MOVING PART FOR E6V/MT 6300A FOUR-POLE WITH LOWER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614935
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	936 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	134 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	157 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	4
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing truck MT
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTEarth.truckUp.Term.63003pWMPnew

E6MT Earth.truckUp.Term.6300 3p W MP new



Product image
not available

General Information

Extended Product Type	E6MTEarth.truckUp.Term.63003pWMPnew
Product ID	1SDA059131R1
EAN	8015644614904
Catalog Description	E6MT Earth.truckUp.Term.6300 3p W MP new
Long Description	SACE EMAX MOVING PART FOR E6V/MT 6300A THREE-POLE WITH UPPER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614904
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	138 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	3
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing truck MT
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W

PRODUCT-DETAILS

E6MTEarth.truckLowTerm.63003pWMPnew

E6MT Earth.truckLowTerm.6300 3p W MP new



Product image
not available

General Information

Extended Product Type	E6MTEarth.truckLowTerm.63003pWMPnew
Product ID	1SDA059132R1
EAN	8015644614911
Catalog Description	E6MT Earth.truckLowTerm.6300 3p W MP new
Long Description	SACE EMAX MOVING PART FOR E6V/MT 6300A THREE-POLE WITH LOWER JAW-TYPE CONTACTS NEW

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
---	---------------------------------

Environmental

Environmental Information	1SDL000142R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644614911
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	810 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	116 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	138 kg
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	3
Product Main Type	SACE Emax
Product Name	Derived version
Product Type	Derived version - Earthing truck MT
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	6300 A
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I_u)	6300 A
Standards	IEC
Sub-type	E6
Terminal Connection Type	Withdrawable Circuit-Breakers
Version	W



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>