

Автоматические выключатели Tmax T T6D, T6H, T6L

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



T6D 630 3p F F



T6D 630 4p F F



T6D 800 3p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	10.731 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Switch Disconnector	Switch Disconnector	Switch Disconnector
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 32 W
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV	8 kV

Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 A	for 1 s 15 A	for 1 s 15 A
Rated Uninterrupted Current (I _u):	630 A	630 A	800 A
Short-Circuit Performance Level:	D	D	D
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V



T6D 1000 3p F F



T6D 1000 4p F F



T6D 800 4p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	10.845 kg
Product Net Width:	210 mm	280 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	11 kg	14 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm



Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Switch Disconnecter	Switch Disconnecter	Switch Disconnecter
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F



Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	4
Power Loss:	at Rated Operating Conditions per Pole 48 W	at Rated Operating Conditions per Pole 48 W	at Rated Operating Conditions per Pole 32 W
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 A
Rated Uninterrupted Current (I _u):	1000 A	1000 A	800 A
Short-Circuit Performance Level:	D	D	D
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V



T6H 630
PR221DS-LS/I
In=630 4p F F



T6H 630
PR221DS-LS/I
In=630 3p F F



T6H 630
PR221DS-I
In=630 3p F
F



T6H 630
PR221DS-I
In=630 4p
F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12 kg	9.5 kg	9.5 kg	12 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	370 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	14 kg	11 kg	11 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	3	3	4
Power Loss:	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I _n):	630 A	630 A	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 100 kA	(220 V AC) 100 kA	(220 V AC) 100 kA	(220 V AC) 100 kA
	(230 V AC) 100 kA	(230 V AC) 100 kA	(230 V AC) 100 kA	(230 V AC) 100 kA
	(380 V AC) 70 kA	(380 V AC) 70 kA	(380 V AC) 70 kA	(380 V AC) 70 kA
	(400 V AC) 70 kA	(400 V AC) 70 kA	(400 V AC) 70 kA	(400 V AC) 70 kA
	(415 V AC) 70 kA	(415 V AC) 70 kA	(415 V AC) 70 kA	(415 V AC) 70 kA
	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA
	(500 V AC) 50 kA	(500 V AC) 50 kA	(500 V AC) 50 kA	(500 V AC) 50 kA
	(690 V AC) 19 kA	(690 V AC) 19 kA	(690 V AC) 19 kA	(690 V AC) 19 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 7.6 kA	for 1 s 7.6 kA	for 1 s 7.6 kA	for 1 s 7.6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 100 kA	(220 V AC) 100 kA	(220 V AC) 100 kA	(220 V AC) 100 kA
	(230 V AC) 100 kA	(230 V AC) 100 kA	(230 V AC) 100 kA	(230 V AC) 100 kA
	(380 V AC) 70 kA	(380 V AC) 70 kA	(380 V AC) 70 kA	(380 V AC) 70 kA
	(400 V AC) 70 kA	(400 V AC) 70 kA	(400 V AC) 70 kA	(400 V AC) 70 kA
	(415 V AC) 70 kA	(415 V AC) 70 kA	(415 V AC) 70 kA	(415 V AC) 70 kA
	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA
	(500 V AC) 50 kA	(500 V AC) 50 kA	(500 V AC) 50 kA	(500 V AC) 50 kA
	(690 V AC) 25 kA	(690 V AC) 25 kA	(690 V AC) 25 kA	(690 V AC) 25 kA
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A	630 A
Release:	PR221DS-LS/I	PR221DS-LS/I	PR221DS-I	PR221DS-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V



T6H 630 PR222DS/P-
LSIG In=630 3p F F



T6H 630 PR222DS/P-
LSIG In=630 4p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg

Product Net Width:	210 mm	280 mm
--------------------	--------	--------

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm
Package Level 1 EAN:	8015644627119	8015644627164
Package Level 1 Gross Weight:	11 kg	14 kg
Package Level 1 Height:	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4
Power Loss:	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I _n):	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 7.6 kA	for 1 s 7.6 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA
Rated Uninterrupted Current (I_u):	630 A	630 A
Release:	PR222DS/P-LSIG	PR222DS/P-LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	H	H
Standards:	IEC	IEC
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V



T6H 630 TMA
630-6300 3p F F



T6H 630 TMA
630-6300 4p F F



T6H 630 TMA
630-6300 4p F F
InN=100%In

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	12 kg
Product Net Width:	210 mm	280 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
---------------------------------	--------	--------	--------

Package Level 1 Gross Weight:	11 kg	14 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	4
Power Loss:	at Rated Operating Conditions per Pole 30.6 W	at Rated Operating Conditions per Pole 30.6 W	at Rated Operating Conditions per Pole 30.6 W
Rated Current (I _n):	630 A	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 7.6 kA	for 1 s 7.6 kA	for 1 s 7.6 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 100 kA	(220 V AC) 100 kA	(220 V AC) 100 kA
	(230 V AC) 100 kA	(230 V AC) 100 kA	(230 V AC) 100 kA
	(380 V AC) 70 kA	(380 V AC) 70 kA	(380 V AC) 70 kA
	(400 V AC) 70 kA	(400 V AC) 70 kA	(400 V AC) 70 kA
	(415 V AC) 70 kA	(415 V AC) 70 kA	(415 V AC) 70 kA
	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA
	(500 V AC) 50 kA	(500 V AC) 50 kA	(500 V AC) 50 kA
	(690 V AC) 25 kA	(690 V AC) 25 kA	(690 V AC) 25 kA
	(250 V DC) 2 Poles in Series 70 kA	(250 V DC) 2 Poles in Series 70 kA	(250 V DC) 2 Poles in Series 70 kA
	(500 V DC) 2 Poles in Series 50 kA	(500 V DC) 2 Poles in Series 50 kA	(500 V DC) 2 Poles in Series 50 kA
	(750 V DC) 3 Poles in Series 36 kA	(750 V DC) 3 Poles in Series 36 kA	(750 V DC) 3 Poles in Series 36 kA
Rated Uninterrupted Current (I_u):	630 A	630 A	630 A
Release:	TMA	TMA	TMA
Release Type:	TM	TM	TM
Short-Circuit Performance Level:	H	H	H
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V



T6H800 MCP-UL/CSA
PR221DS-I4In=600 3p FF



T6H800 MCP-UL/CSA
PR221DS-I4In=800 3p FF

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg
Product Net Width:	210 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 21 W
Rated Current (I _n):	600 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	800 A	800 A
Release:	PR221DS-I	PR221DS-I
Release Type:	EL	EL
Short-Circuit Performance Level:	H	H
Standards:	UL	UL
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA
------------------------------------	---	---



**T6H 800
PR221DS-LS/I
In=800 3p F F**



**T6H 800
PR221DS-LS/I
In=800 4p F F**



**T6H 800
PR221DS-I
In=800 3p
F F**



**T6H 800
PR221DS-I
In=800 4p
F F**

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.652 kg	12 kg	9.5 kg	12 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	370 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I_n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 10 kA	for 1 s 10 kA	for 1 s 10 kA	for 1 s 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A	800 A
Release:	PR221DS-LS/I	PR221DS-LS/I	PR221DS-I	PR221DS-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V	3500 V



T6H 800 TMA
800-8000 4p F F



T6H 800 TMA
800-8000 3p F F



T6H 800 TMA
800-8000 4p F F
InN=100%In

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	12 kg	9.5 kg	12 kg
Product Net Width:	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	14 kg	9.6 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 31 W	at Rated Operating Conditions per Pole 31 W	at Rated Operating Conditions per Pole 31 W
Rated Current (I _n):	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA

	(500 V AC) 50 kA (690 V AC) 19 kA	(500 V AC) 50 kA (690 V AC) 19 kA	(500 V AC) 50 kA (690 V AC) 19 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 10 kA	for 1 s 10 kA	for 1 s 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA (250 V DC) 2 Poles in Series 70 kA (500 V DC) 2 Poles in Series 50 kA (750 V DC) 3 Poles in Series 36 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA (250 V DC) 2 Poles in Series 70 kA (500 V DC) 2 Poles in Series 50 kA (750 V DC) 3 Poles in Series 36 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA (250 V DC) 2 Poles in Series 70 kA (500 V DC) 2 Poles in Series 50 kA (750 V DC) 3 Poles in Series 36 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A
Release:	TMA	TMA	TMA
Release Type:	TM	TM	TM
Short-Circuit Performance Level:	H	H	H
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V



T6H 800 UL/
CSA PR221DS-
LS/I 800 3p F
F



T6H 800 UL/
CSA PR221DS-
LS/I 800 4p F
F



T6H 800 UL/
CSA PR221DS-
LS/I 600 3p F
F



T6H 800 UL/
CSA PR221DS-
LS/I 600 4p F
F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm

Product Net Weight:	9.5 kg	9.5 kg	9.5 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	321 mm	N/A	321 mm	N/A
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11 kg	N/A	11 kg	N/A
Package Level 1 Height:	288 mm	N/A	288 mm	N/A
Package Level 1 Units:	box 1 piece	N/A	box 1 piece	N/A
Package Level 1 Width:	321 mm	N/A	321 mm	N/A

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 18 W
Rated Current (I _n):	800 A	800 A	600 A	600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR221DS-LS/I	PR221DS-LS/I	PR221DS-LS/I	PR221DS-LS/I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA
------------------------------------	---	---	---	---



T6H 800 UL/
CSA PR222DS/
P-LSI 600 3p F
F



T6H 800 UL/
CSA PR222DS/
P-LSI 600 4p F
F



T6H 800 UL/
CSA PR222DS/
P-LSI 800 4p F
F



T6H 800 UL/
CSA PR222DS/P-
LSI 800 3p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg	9.5 kg	9.5 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I_n):	600 A	600 A	800 A	800 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A	800 A
Release:	PR222DS/P-LSI	PR222DS/P-LSI	PR222DS/P-LSI	PR222DS/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA
------------------------------------	---	---	---	---



T6H 800 UL/
CSA PR222DS/
P-LSIG 600 4p
F F



T6H 800 UL/
CSA PR222DS/
P-LSIG 600 3p
F F



T6H 800 UL/
CSA PR222DS/
P-LSIG 800 4p
F F



T6H 800 UL/
CSA PR222DS/
P-LSIG 800 3p
F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg	9.5 kg	9.5 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	600 A	600 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR222DS/P-LSIG	PR222DS/P-LSIG	PR222DS/P-LSIG	PR222DS/P-LSIG

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	UL	UL	UL	UL
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA
------------------------------------	---	---	---	---



T6H 800 UL/CSA TMA
600-6000 3p F F



T6H 800 UL/CSA TMA
800-8000 3p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg
Product Net Width:	210 mm	210 mm

Container Information

Package Level 1 Depth / Length:	321 mm	321 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	11 kg	11 kg
Package Level 1 Height:	288 mm	288 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	321 mm	321 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
--------------------	-------------	-------------

Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 31 W
Rated Current (I _n):	600 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	600 V AC 600 V DC	600 V AC 600 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA
Rated Uninterrupted Current (I _u):	800 A	800 A
Release:	TMA	TMA
Release Type:	TM	TM
Short-Circuit Performance Level:	H	H
Standards:	UL	UL
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA
------------------------------------	---	---



T6H800 UL TMA
600-3000..6000 4p FF
N100%



T6H800 UL TMA
800-4000..8000 4p FF
N100%

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	12 kg	12 kg
Product Net Width:	280 mm	280 mm

Container Information

Package Level 1 EAN:

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	4
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 31 W
Rated Current (I_n):	600 A	800 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V

Rated Operational Voltage:	600 V AC 600 V DC	600 V AC 600 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA
Rated Uninterrupted Current (I_u):	800 A	800 A
Release:	TMA	TMA
Release Type:	TM	TM
Short-Circuit Performance Level:	H	H
Standards:	UL	UL
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA
------------------------------------	---	---



T6H 1000
PR221DS-LS/I
In=1000 3p F F



T6H 1000
PR221DS-LS/I
In=1000 4p F F



T6H 1000
PR221DS-I
In=1000 4p F F



T6H 1000
PR221DS-I
In=1000 3p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	12 kg	9.5 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	370 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11 kg	14 kg	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 19 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 50 kA (500 V AC) 50 kA (690 V AC) 25 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR221DS-LS/I	PR221DS-LS/I	PR221DS-I	PR221DS-I

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	H	H	H	H
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V	3500 V



T6L 630
PR221DS-I
In=630 3p F F



T6L 630
PR221DS-I
In=630 4p F F



T6L630 PR221DS-I
In=630 3p F F
1000VAC

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6

Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I _n):	630 A	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA	(1000 V AC) 6 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	(690 V AC) 22.5 kA for 1 s 7.6 kA	(690 V AC) 22.5 kA for 1 s 7.6 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(1000 V AC) 12 kA
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A
Release:	PR221DS-I	PR221DS-I	PR221DS-I
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	L	L	L

Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V



T6L 630
PR221DS-I
In=630 4p F F



T6L 630
PR221DS-I
In=630 3p F F



T6L630 PR221DS-I
In=630 3p F F
1000VAC

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	12 kg	9.5 kg	9.5 kg
Product Net Width:	280 mm	210 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 Gross Weight:	14 kg	11 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker

Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F



Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I _n):	630 A	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA	(1000 V AC) 6 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	(690 V AC) 22.5 kA	(690 V AC) 22.5 kA	
	for 1 s 7.6 kA	for 1 s 7.6 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(1000 V AC) 12 kA
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A
Release:	PR221DS-I	PR221DS-I	PR221DS-I
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	L	L	L



**T6L 630 PR222DS/P-
LSIG In=630 3p F F**



**T6L 630 PR222DS/P-
LSIG In=630 4p F F**

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg
Product Net Width:	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	11 kg	14 kg
Package Level 1 Height:	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4
Power Loss:	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I_n):	630 A	630 A

Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 7.6 kA	for 1 s 7.6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	630 A	630 A
Release:	PR222DS/P-LSIG	PR222DS/P-LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	L	L
Standards:	IEC	IEC
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
------------------------------------	----------	----------



T6L 630 PR222DS/P-LSI
In=630 4p4F F



T6L 630 PR222DS/P-LSI
In=630 3p4F F

Product Net Height:	268 mm	268 mm
Product Net Weight:	12 kg	9.5 kg
Product Net Width:	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	3
Power Loss:	at Rated Operating Conditions per Pole 20 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I _n):	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA

Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 7.6 kA	for 1 s 7.6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	630 A	630 A
Release:	PR222DS/P-LSI	PR222DS/P-LSI
Release Type:	EL	EL
Short-Circuit Performance Level:	L	L
Standards:	IEC	IEC
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V



**T6L 630 TMA
630-6300 4p
F F**



**T6L 630 TMA
630-6300 3p
F F**



**T6L 630 TMA
630-6300 4p
F F InN=100%
In**



**T6L630
TMA630-6300
4pFF N100%
1000VAC/DC**

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12 kg	9.5 kg	12 kg	12 kg
Product Net Width:	280 mm	210 mm	280 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	370 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	14 kg	11 kg	14 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	285 mm

Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	4	3	4	4
Power Loss:	at Rated Operating Conditions per Pole 30.6 W	at Rated Operating Conditions per Pole 30.6 W	at Rated Operating Conditions per Pole 30.6 W	at Rated Operating Conditions per Pole 30.6 W
Rated Current (I _n):	630 A	630 A	630 A	630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	1000 V AC 1000 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(1000 V AC) 6 kA (1150 V AC) 12.5 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 7.6 kA	for 1 s 7.6 kA	for 1 s 7.6 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA	(1000 V AC) 12 kA (1000 V DC) 50 kA
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A	630 A
Release:	TMA	TMA	TMA	TMA
Release Type:	TM	TM	TM	TM
Short-Circuit Performance Level:	L	L	L	L

Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V



T6L800 MCP-UL/CSA
PR221DS-I In=800 3p FF



T6L800 MCP-UL/CSA
PR221DS-I In=600 3p FF

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg
Product Net Width:	210 mm	210 mm

Container Information

Package Level 1 EAN:

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	3

Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 18 W
Rated Current (I_n):	800 A	600 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Uninterrupted Current (I_u):	800 A	800 A
Release:	PR221DS-I	PR221DS-I
Release Type:	EL	EL
Short-Circuit Performance Level:	L	L
Standards:	UL	UL
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA
------------------------------------	--	--



T6L 800
PR221DS-I
In=800 3p F F



T6L 800
PR221DS-I
In=800 4p F F



T6L800 PR221DS-I
In=800 3p F F
1000VAC

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm

Product Net Weight:	9.5 kg	12 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA	(1000 V AC) 6 kA

	(690 V AC) 22.5 kA	(690 V AC) 22.5 kA	
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 10 kA	for 1 s 10 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(1000 V AC) 12 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A
Release:	PR221DS-I	PR221DS-I	PR221DS-I
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	L	L	L
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V



T6L 800 PR221DS-LS/I
In=800 3p F F



T6L 800 PR221DS-LS/I
In=800 4p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg
Product Net Width:	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm
---------------------------------	--------	--------

Package Level 1 Gross Weight:	11 kg	14 kg
Package Level 1 Height:	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm



Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F



Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 10 kA	for 1 s 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA

	(690 V AC) 30 kA	(690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	800 A	800 A
Release:	PR221DS-LS/I	PR221DS-LS/I
Release Type:	EL	EL
Short-Circuit Performance Level:	L	L
Standards:	IEC	IEC
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V



T6L 800
PR222DS/P-
LSIG In=800 3p
F F



T6L 800
PR222DS/P-
LSIG In=800 4p
F F



T6L800 PR222DS/
P-LSIG In=800
3pFF1000VAC

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA	(1000 V AC) 6 kA
	(440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 10 kA	for 1 s 10 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(1000 V AC) 12 kA

Rated Uninterrupted Current (I _u):	800 A	800 A	800 A
Release:	PR222DS/P-LSIG	PR222DS/P-LSIG	PR222DS/P-LSIG
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	L	L	L
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V



T6L 800
PR222DS/P-LSI
In=800 3p F F



T6L 800
PR222DS/P-LSI
In=800 4p F F



T6L800 PR222DS/
P-LSI In=800 3pFF
1000VAC

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA	(1000 V AC) 6 kA
	(440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 10 kA	for 1 s 10 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(1000 V AC) 12 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A
Release:	PR222DS/P-LSI	PR222DS/P-LSI	PR222DS/P-LSI

Release Type:	EL	EL	EL
Short-Circuit Performance Level:	L	L	L
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V



T6L 800 TMA
800-8000 3p
F F



T6L 800 TMA
800-8000 4p
F F



T6L 800 TMA
800-8000 4p
F F InN=100%
In



T6L800
TMA800-8000
4p F F 1000VDC
JUMPER

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	12 kg	12 kg
Product Net Width:	210 mm	280 mm	280 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	286 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11 kg	14 kg	14 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	228 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	box 1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	228 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	4	4
Power Loss:	at Rated Operating Conditions per Pole 31 W	at Rated Operating Conditions per Pole 31 W	at Rated Operating Conditions per Pole 31 W	N/A
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	1000 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(1000 V AC) 6 kA (1150 V AC) 12.5 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 10 kA	for 1 s 10 kA	for 1 s 10 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA	(1000 V AC) 12 kA (1000 V DC) 50 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	TMA	TMA	TMA	TMA
Release Type:	TM	TM	TM	TM
Short-Circuit Performance Level:	L	L	L	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	N/A
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	N/A



T6L 800 UL/CSA
PR221DS-LS/I 600 3p F
F



T6L 800 UL/CSA
PR221DS-LS/I 800 3p F
F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg
Product Net Width:	210 mm	210 mm

Container Information

Package Level 1 EAN:

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I_n):	600 A	800 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC

Rated Uninterrupted Current (I _u):	800 A	800 A
Release:	PR221DS-LS/I	PR221DS-LS/I
Release Type:	EL	EL
Short-Circuit Performance Level:	L	L
Standards:	UL	UL
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA
------------------------------------	--	--



T6L 800 UL/
CSA PR222DS/
P-LSI 600 3p F
F



T6L 800 UL/
CSA PR222DS/
P-LSIG 600 3p
F F



T6L 800 UL/
CSA PR222DS/
P-LSIG 800 3p
F F



T6L 800 UL/CSA
PR222DS/P-LSI
800 3p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg	9.5 kg	9.5 kg
Product Net Width:	210 mm	210 mm	210 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	3	3	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	600 A	600 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR222DS/P-LSI	PR222DS/P-LSIG	PR222DS/P-LSIG	PR222DS/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	L	L	L	L
Standards:	UL	UL	UL	UL
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA
---------------------------------------	--	--	--	--



T6L 800 UL/CSA TMA
600-6000 3p F F



T6L 800 UL/CSA TMA
800-8000 3p F F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	9.5 kg	9.5 kg

Product Net Width:	210 mm	210 mm
--------------------	--------	--------

Container Information

Package Level 1 EAN:

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	3
Power Loss:	at Rated Operating Conditions per Pole 18 W	at Rated Operating Conditions per Pole 31 W
Rated Current (I _n):	600 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	600 V AC 600 V DC	600 V AC 600 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA (500 V DC) 2 Poles in Series 65 kA (600 V DC) 3 Poles in Series 50 kA	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 42 kA (500 V DC) 2 Poles in Series 65 kA (600 V DC) 3 Poles in Series 50 kA
Rated Uninterrupted Current (I _u):	800 A	800 A
Release:	TMA	TMA
Release Type:	TM	TM
Short-Circuit Performance Level:	L	L
Standards:	UL	UL
Sub-type:	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 200 kA	(240 V AC) 200 kA
	(480 V AC) 100 kA	(480 V AC) 100 kA
	(600 V AC) 42 kA	(600 V AC) 42 kA
	(500 V DC) 2 Poles in Series 65 kA	(500 V DC) 2 Poles in Series 65 kA
	(600 V DC) 3 Poles in Series 50 kA	(600 V DC) 3 Poles in Series 50 kA



T6L 1000 PR221DS-I	T6L 1000 PR221DS-I	T6L 1000 PR221DS-LS/I	T6L 1000 PR221DS-LS/I
In=1000 3p	In=1000 4p	In=1000 3p F	In=1000 4p F
F F	F F	F	F

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	9.5 kg	12 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	370 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg	14 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR221DS-I	PR221DS-I	PR221DS-LS/I	PR221DS-LS/I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	L	L	L	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V



T6L 1000
PR222DS/P-
LSIG
In=1000 3p F

T6L 1000
PR222DS/P-
LSIG
In=1000 4p F

T6L800
PR222DS/P-
LSIG In=800
3pFF1000VAC

T6L630
PR222DS/P-
LSIG In=630
3pFF1000VAC

Dimensions

Product Net Depth / Length:	103.5 mm	103.5 mm	103.5 mm	103.5 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.5 kg	12 kg	9.5 kg	9.5 kg
Product Net Width:	210 mm	280 mm	210 mm	210 mm

Container Information

Package Level 1 Depth / Length:	370 mm	370 mm	370 mm	370 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11 kg	14 kg	11 kg	11 kg
Package Level 1 Height:	285 mm	285 mm	285 mm	285 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	305 mm	305 mm	305 mm	305 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T6	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	4000 cycle 60 cycles per hour	4000 cycle 60 cycles per hour	5000 cycle 60 cycles per hour	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour	20000 cycle 120 cycles per hour
Number of Poles:	3	4	3	3
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 20 W
Rated Current (I_n):	1000 A	1000 A	800 A	630 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	1000 V AC	1000 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 60 kA (500 V AC) 49 kA (690 V AC) 22.5 kA	(1000 V AC) 6 kA	(1000 V AC) 6 kA
	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 80 kA (500 V AC) 65 kA (690 V AC) 30 kA	(1000 V AC) 12 kA	(1000 V AC) 12 kA
Rated Uninterrupted Current (I_u):	1000 A	1000 A	800 A	630 A
Release:	PR222DS/P-LSIG	PR222DS/P-LSIG	PR222DS/P-LSIG	PR222DS/P-LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	L	L	L	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T6	T6	T6	T6
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V	3500 V

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>