

Автоматические выключатели Tmax T7S, T7N-D/PV, T7S, T7V, T7X

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



T7S 800
PR231/P I
In=800A
4p F F



T7S 800
PR231/P I
In=800A
3p F F



T7S 800
PR231/P I
In=800A
4p F F M



T7S 800
PR231/P I
In=800A
3p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth /	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A	800 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR231/P LS/I
In=800A 4p F
F



T7S 800
PR231/P LS/I
In=800A 3p F
F



T7S 800
PR231/P LS/I
In=800A 4p F
F M



T7S 800
PR231/P LS/I
In=800A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR232/P LSI
In=800A 4p
F F



T7S 800
PR232/P LSI
In=800A 3p
F F



T7S 800
PR232/P LSI
In=800A 4p
F F M



T7S 800
PR232/P LSI
In=800A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3

Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR331/P LSIG
In=800A 4p F
F



T7S 800
PR331/P LSIG
In=800A 3p F
F



T7S 800
PR331/P LSIG
In=800A 4p F
F M



T7S 800
PR331/P LSIG
In=800A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm

Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cw}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA

Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR332/P LI4
In=800A 4p
F F



T7S 800
PR332/P LI4
In=800A 3p
F F



T7S 800
PR332/P LI4
In=800A 4p
F F M



T7S 800
PR332/P LI4
In=800A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR332/P LSIG
In=800A 4p F
F



T7S 800
PR332/P LSIG
In=800A 3p F
F



T7S 800
PR332/P LSIG
In=800A 4p F
F M



T7S 800
PR332/P LSIG
In=800A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA

Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR332/P LSI4
In=800A 4p
F F



T7S 800
PR332/P LSI4
In=800A 3p F
F



T7S 800
PR332/P LSI4
In=800A 4p
F F M



T7S 800
PR332/P LSI4
In=800A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
--------------------	-------------	-------------	-------------	-------------

Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 800
PR332/P LSIRc4
In=800A 4p F
F



T7S 800
PR332/P LSIRc4
In=800A 3p F
F



T7S 800
PR332/P LSIRc4
In=800A 4p F
F M



T7S 800
PR332/P LSIRc4
In=800A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W	at Rated Operating Conditions per Pole 19.3 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A	800 A
Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000
PR231/P I
In=1000A
3p F F



T7S 1000
PR231/P I
In=1000A
4p F F



T7S 1000
PR231/P I
In=1000A
4p F F M



T7S 1000
PR231/P I
In=1000A
3p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7

Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
---------------------------	---------------------------------	---------------------------------	---------------------------------	---------------------------------



T7S 1000 PR231/
P LS/I In=1000A
3p F F



T7S 1000 PR231/
P LS/I In=1000A
4p F F



T7S 1000 PR231/
P LS/I In=1000A
3p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	13.634 kg	17.642 kg	11 kg
Product Net Width:	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	290 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	14.352 kg	18.57 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	370 mm
Package Level 1 Units:	1 piece	1 piece	N/A
Package Level 1 Width:	280 mm	360 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	N/A
Suitable For:	T7	T7	N/A
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	N/A
Version:	F	F	N/A

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	N/A
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	N/A
Number of Poles:	3	4	N/A
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	N/A
Rated Current (I _n):	1000 A	1000 A	N/A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	N/A
Rated Insulation Voltage (U _i):	1000 V	1000 V	N/A
Rated Operational Voltage:	690 V AC	690 V AC	N/A
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	N/A
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	N/A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	N/A
Rated Uninterrupted Current (I _u):	1000 A	1000 A	N/A
Release:	PR231/P-LS/I	PR231/P-LS/I	N/A
Release Type:	EL	EL	N/A
Short-Circuit Performance Level:	S	S	N/A
Standards:	IEC	IEC	N/A
Sub-type:	T7	T7	N/A
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	N/A



**T7S 1000 PR231/
P LS/I In=1000A
4p F F M**

**T7S 1000 PR231/
P LS/I In=1000A
4p F F M**

**T7S 1000 PR231/
P LS/I In=1000A
3p F F M**

Dimensions

Product Net Depth / Length:	178 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	14 kg	14 kg	14.725 kg
Product Net Width:	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm
Package Level 1 EAN:	N/A		
Package Level 1 Gross Weight:	15.5 kg	15.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm
Package Level 1 Units:	N/A	1 piece	1 piece
Package Level 1 Width:	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	N/A	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	N/A	T7M	T7M
Suitable for Product Class:	N/A	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	N/A	F	F

Technical

Electrical Durability:	N/A	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	N/A	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	N/A	4	3
Power Loss:	N/A	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	N/A	1000 A	1000 A

Rated Impulse Withstand Voltage (U _{imp}):	N/A	8 kV	8 kV
Rated Insulation Voltage (U _i):	N/A	1000 V	1000 V
Rated Operational Voltage:	N/A	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	N/A	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	N/A	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	N/A	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	N/A	1000 A	1000 A
Release:	N/A	PR231/P-LS/I	PR231/P-LS/I
Release Type:	N/A	EL	EL
Short-Circuit Performance Level:	N/A	S	S
Standards:	N/A	IEC	IEC
Sub-type:	N/A	T7	T7
Terminal Connection Type:	N/A	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000
PR331/P LSIG
In=1000A 3p
F F



T7S 1000
PR331/P LSIG
In=1000A 4p
F F



T7S 1000
PR331/P LSIG
In=1000A 3p
F F M



T7S 1000
PR331/P LSIG
In=1000A 4p
F F M

Dimensions				
Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR331/P L SIG	PR331/P L SIG	PR331/P L SIG	PR331/P L SIG

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000
PR332/P LI4
In=1000A 4p
F F



T7S 1000
PR332/P LI4
In=1000A 3p
F F



T7S 1000
PR332/P LI4
In=1000A 4p
F F M



T7S 1000
PR332/P LI4
In=1000A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000
PR332/P LSIG
In=1000A 4p

F F



T7S 1000
PR332/P LSIG
In=1000A 3p F

F



T7S 1000
PR332/P LSIG
In=1000A 4p

F F M



T7S 1000
PR332/P LSIG
In=1000A 3p F

F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm

Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000
PR332/P LSI
In=1000A 4p
F F



T7S 1000
PR332/P LSI
In=1000A 3p
F F



T7S 1000
PR332/P LSI
In=1000A 4p
F F M



T7S 1000
PR332/P LSI
In=1000A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour

Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I_n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cw}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000
PR332/P LSIRc
In=1000A 3p F
F M



T7S 1000
PR332/P LSIRc
In=1000A 4p F
F M



T7S 1000
PR332/P LSIRc
In=1000A 3p F
F



T7S 1000
PR332/P LSIRc
In=1000A 4p F
F

Dimensions

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	11 kg	14 kg	9.7 kg	12.5 kg

Product Net Width:	210 mm	280 mm	210 mm	280 mm
--------------------	--------	--------	--------	--------

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	12.5 kg	15.5 kg	11.2 kg	14 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A

Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1000 UL
PR232/P LSI
In1000A 3p FF



T7S 1000 UL
PR232/P LSI
In1000A 4p FF



T7S 1000 UL
PR232/P LSI
In1000A 4p FF
M

T7S 1000 UL
PR232/P LSI
In1000A 3p FF
M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	N/A	N/A	N/A	299 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	N/A	N/A	N/A	12.5 kg
Package Level 1 Height:	N/A	N/A	N/A	388 mm
Package Level 1 Units:	N/A	N/A	N/A	box 1 piece
Package Level 1 Width:	N/A	N/A	N/A	399 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
------------------------	-----------------------------------	-----------------------------------	-----------------------------------	-----------------------------------

Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1000 UL
PR331/P4
LSIG In1000A
3p FF



T7S 1000 UL
PR331/P4
LSIG In1000A
4p FF



T7S 1000 UL
PR331/P4
LSIG In1000A
4p FF M



T7S 1000 UL
PR331/P4
LSIG In1000A
3p FF M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker

Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1000 UL
PR332/P
LSIG
In1000A 3p
FF



T7S 1000 UL
PR332/P
LSIG
In1000A 4p
FF



T7S 1000 UL
PR332/P
LSIG
In1000A 3p
FF M



T7S 1000 UL
PR332/P LSIG
In1000A 4p FF
M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm

Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1000 UL
PR332/P LSI
In1000A 3p FF



T7S 1000 UL
PR332/P LSI
In1000A 4p FF



T7S 1000 UL
PR332/P LSI
In1000A 4p FF
M



T7S 1000 UL
PR332/P LSI
In1000A 3p FF
M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W	at Rated Operating Conditions per Pole 30 W
Rated Current (I_n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U_i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	600 V AC	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I_u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1200 UL
PR232/P LSI
In1200A 3p FF



T7S 1200 UL
PR232/P LSI
In1200A 4p FF



T7S 1200 UL
PR232/P LSI
In1200A 4p FF

M



T7S 1200 UL
PR232/P LSI
In1200A 3p FF

M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	299 mm	N/A	N/A	299 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	N/A	N/A	12.5 kg
Package Level 1 Height:	388 mm	N/A	N/A	388 mm
Package Level 1 Units:	box 1 piece	N/A	N/A	box 1 piece
Package Level 1 Width:	399 mm	N/A	N/A	399 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3

Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1200 A	1200 A	1200 A	1200 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	630 V AC	630 V AC	630 V AC	630 V AC
Rated Uninterrupted Current (I _u):	1200 A	1200 A	1200 A	1200 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1200 UL
PR331/P
LSIG
In1200A 3p
FF



T7S 1200 UL
PR331/P
LSIG
In1200A 4p
FF



T7S 1200 UL
PR331/P
LSIG In1200A
4p FF M



T7S 1200 UL
PR331/P
LSIG In1200A
3p FF M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Additional Information				
Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1200 A	1200 A	1200 A	1200 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	630 V AC	630 V AC	630 V AC	630 V AC
Rated Uninterrupted Current (I _u):	1200 A	1200 A	1200 A	1200 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
---------------------------------------	--	--	--	--



T7S 1200 UL
PR332/P
LSIG In1200A
3p FF



T7S 1200 UL
PR332/P
LSIG In1200A
4p FF



T7S 1200 UL
PR332/P
LSIG In1200A
4p FF M



T7S 1200 UL
PR332/P
LSIG In1200A
3p FF M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1200 A	1200 A	1200 A	1200 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	630 V AC	630 V AC	630 V AC	630 V AC
Rated Uninterrupted Current (I _u):	1200 A	1200 A	1200 A	1200 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1200 UL
PR332/P LSI
In1200A 4p FF



T7S 1200 UL
PR332/P LSI
In1200A 3p FF



T7S 1200 UL
PR332/P LSI
In1200A 4p FF
M



T7S 1200 UL
PR332/P LSI
In1200A 3p FF
M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4	3	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1200 A	1200 A	1200 A	1200 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	630 V AC	630 V AC	630 V AC	630 V AC
Rated Uninterrupted Current (I _u):	1200 A	1200 A	1200 A	1200 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI

Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	UL	UL	UL	UL
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test}):	3500 V	3500 V	3500 V	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA	(240 V AC) 65 kA (480 V AC) 50 kA (600 V AC) 25 kA
------------------------------------	--	--	--	--



T7S 1250
PR231/P I
In=1250A
3p F F



T7S 1250
PR231/P I
In=1250A
4p F F



T7S 1250
PR231/P I
In=1250A
3p F F M



T7S 1250
PR231/P I
In=1250A
4p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker

Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	3	4
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cw}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR231/P LS/I
In=1250A 3p
F F



T7S 1250
PR231/P LS/I
In=1250A 4p
F F



T7S 1250
PR231/P LS/I
In=1250A 4p
F F M



T7S 1250
PR231/P LS/I
In=1250A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	14.369 kg	17.67 kg	14 kg	14.758 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	15.5 kg	18.6 kg	15.5 kg	15.535 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V

Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR232/P LSI
In=1250A 3p
F F



T7S 1250
PR232/P LSI
In=1250A 4p
F F



T7S 1250
PR232/P LSI
In=1250A 4p
F F M

T7S 1250
PR232/P LSI
In=1250A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	14.371 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information				
Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	14.372 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information				
Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical				
Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	1250 A	1250 A	1250 A	1250 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR331/P LSI
In=1250A 3p F
F



T7S 1250
PR331/P LSI
In=1250A 4p F
F



T7S 1250
PR331/P LSI
In=1250A 4p F
F M



T7S 1250
PR331/P LSI
In=1250A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker

Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cw}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR332/P LI
In=1250A 3p
F F M



T7S 1250
PR332/P LI
In=1250A 4p
F F M



T7S 1250
PR332/P LI
In=1250A 4p
F F



T7S 1250
PR332/P LI
In=1250A 3p
F F

Dimensions

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	11 kg	14 kg	12.5 kg	9.7 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	12.5 kg	15.5 kg	14 kg	11.2 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA	(220 V AC) 85 kA	(220 V AC) 85 kA	(220 V AC) 85 kA
	(230 V AC) 85 kA	(230 V AC) 85 kA	(230 V AC) 85 kA	(230 V AC) 85 kA
	(380 V AC) 50 kA	(380 V AC) 50 kA	(380 V AC) 50 kA	(380 V AC) 50 kA
	(400 V AC) 50 kA	(400 V AC) 50 kA	(400 V AC) 50 kA	(400 V AC) 50 kA
	(415 V AC) 50 kA	(415 V AC) 50 kA	(415 V AC) 50 kA	(415 V AC) 50 kA
	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA
	(500 V AC) 40 kA	(500 V AC) 40 kA	(500 V AC) 40 kA	(500 V AC) 40 kA
	(690 V AC) 30 kA	(690 V AC) 30 kA	(690 V AC) 30 kA	(690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA	(220 V AC) 85 kA	(220 V AC) 85 kA	(220 V AC) 85 kA
	(230 V AC) 85 kA	(230 V AC) 85 kA	(230 V AC) 85 kA	(230 V AC) 85 kA
	(380 V AC) 50 kA	(380 V AC) 50 kA	(380 V AC) 50 kA	(380 V AC) 50 kA
	(400 V AC) 50 kA	(400 V AC) 50 kA	(400 V AC) 50 kA	(400 V AC) 50 kA
	(415 V AC) 50 kA	(415 V AC) 50 kA	(415 V AC) 50 kA	(415 V AC) 50 kA
	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA	(440 V AC) 50 kA
	(500 V AC) 40 kA	(500 V AC) 40 kA	(500 V AC) 40 kA	(500 V AC) 40 kA
	(690 V AC) 30 kA	(690 V AC) 30 kA	(690 V AC) 30 kA	(690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR332/P LSIG
In=1250A 3p F
F



T7S 1250
PR332/P LSIG
In=1250A 4p F
F



T7S 1250
PR332/P LSIG
In=1250A 4p F
F M



T7S 1250
PR332/P LSIG
In=1250A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR332/P LSI
In=1250A 3p
F F



T7S 1250
PR332/P LSI
In=1250A 4p
F F



T7S 1250
PR332/P LSI
In=1250A 4p
F F M



T7S 1250
PR332/P LSI
In=1250A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1250
PR332/P LSIRc
In=1250A 3p F
F



T7S 1250
PR332/P LSIRc
In=1250A 4p F
F



T7S 1250
PR332/P LSIRc
In=1250A 4p F
F M



T7S 1250
PR332/P LSIRc
In=1250A 3p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W	at Rated Operating Conditions per Pole 47 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7

Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
---------------------------	---------------------------------	---------------------------------	---------------------------------	---------------------------------



T7S 1600
PR231/P I
In=1600A
3p F F



T7S 1600
PR231/P I
In=1600A
4p F F



T7S 1600
PR231/P I
In=1600A
4p F F M



T7S 1600
PR231/P I
In=1600A
3p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3	4	4	3
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W

Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1600
PR232/P LSI4
In=1600A 3p
F F



T7S 1600
PR232/P LSI4
In=1600A 4p
F F



T7S 1600
PR232/P LSI4
In=1600A 3p
F F M

T7S 1600
PR232/P LSI4
In=1600A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W
Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA

Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1600
PR331/P LSI
In=1600A 3p
F F



T7S 1600
PR331/P LSI
In=1600A 4p
F F



T7S 1600
PR331/P LSI
In=1600A 3p
F F M



T7S 1600
PR331/P LSI
In=1600A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	17.737 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W
Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1600
PR332/P LI
In=1600A 3p
F F



T7S 1600
PR332/P LI
In=1600A 4p
F F



T7S 1600
PR332/P LI
In=1600A 3p
F F M



T7S 1600
PR332/P LI
In=1600A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W
Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cw}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC

Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1600
PR332/P LSI
In=1600A 3p F



T7S 1600
PR332/P LSI
In=1600A 4p F F



T7S 1600
PR332/P LSI
In=1600A 3p F F M



T7S 1600
PR332/P LSI
In=1600A 4p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W
Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV

Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cw}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _n):	1600 A	1600 A	1600 A	1600 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1600
PR332/P LSI
In=1600A 3p
F F



T7S 1600
PR332/P LSI
In=1600A 4p
F F



T7S 1600
PR332/P LSI
In=1600A 3p
F F M



T7S 1600
PR332/P LSI
In=1600A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm

Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm
Additional Information				
Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F
Technical				
Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W
Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7S 1600
PR332/P LSIRc
In=1600A 3p F
F



T7S 1600
PR332/P LSIRc
In=1600A 4p F
F



T7S 1600
PR332/P LSIRc
In=1600A 3p F
F M



T7S 1600
PR332/P LSIRc
In=1600A 4p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W	at Rated Operating Conditions per Pole 77 W
Rated Current (I _n):	1600 A	1600 A	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA

Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	S	S	S	S
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR231/P I
In=800A
4p F F



T7V 800
PR231/P I
In=800A
3p F F



T7V 800
PR231/P I
In=800A
3p F F M



T7V 800
PR231/P I
In=800A
4p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR231/P LS/I
In=800A 4p F



T7V 800
PR231/P LS/I
In=800A 3p F



T7V 800
PR231/P LS/I
In=800A 3p F
M



T7V 800
PR231/P LS/I
In=800A 4p F
M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA

Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A	800 A
Release:	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR232/P LSI
In=800A 4p
F F



T7V 800
PR232/P LSI
In=800A 3p
F F



T7V 800
PR232/P LSI
In=800A 3p
F F M



T7V 800
PR232/P LSI
In=800A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker

Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{c_s}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{c_u}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR331/P LSIG4
In=800A 4p F
F M



T7V 800
PR331/P LSIG4
In=800A 3p F
F M



T7V 800
PR331/P LSIG4
In=800A 3p F
F



T7V 800
PR331/P LSIG4
In=800A 4p F
F

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	14 kg	11 kg	9.7 kg	12.5 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	15.5 kg	12.5 kg	11.2 kg	14 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A	800 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR332/P LI
In=800A 4p
F F M



T7V 800
PR332/P LI
In=800A 3p
F F M



T7V 800
PR332/P LI
In=800A 4p
F F



T7V 800
PR332/P LI
In=800A 3p
F F

Dimensions

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	14 kg	11 kg	12.5 kg	9.7 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	15.5 kg	12.5 kg	14 kg	11.2 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC

Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR332/P LSIG4
In=800A 4p F
F M



T7V 800
PR332/P LSIG4
In=800A 3p F
F M



T7V 800
PR332/P LSIG4
In=800A 3p F
F



T7V 800
PR332/P LSIG4
In=800A 4p F
F

Dimensions

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	14 kg	11 kg	9.7 kg	12.5 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	15.5 kg	12.5 kg	11.2 kg	14 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W

Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 800
PR332/P LSI
In=800A 3p
F F



T7V 800
PR332/P LSI
In=800A 4p
F F



T7V 800
PR332/P LSI
In=800A 3p
F F M



T7V 800
PR332/P LSI
In=800A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A

Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



**T7V 800
PR332/P
LSIRc
In=800A 3p F
F**



**T7V 800
PR332/P
LSIRc
In=800A 4p F
F**



**T7V 800
PR332/P
LSIRc
In=800A 3p F
F M**



**T7V 800
PR332/P
LSIRc
In=800A 4p F
F M**

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR231/P I
In=1000A
3p F F



T7V 1000
PR231/P I
In=1000A
4p F F



T7V 1000
PR231/P I
In=1000A
4p F F M



T7V 1000
PR231/P I
In=1000A
3p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I_u):	1000 A	1000 A	1000 A	1000 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR231/P LS/I
In=1000A 3p
F F



T7V 1000
PR231/P LS/I
In=1000A 4p
F F



T7V 1000
PR231/P LS/I
In=1000A 4p
F F M



T7V 1000
PR231/P LS/I
In=1000A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7

Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front
---------------------------	---------------------------------	---------------------------------	---------------------------------	---------------------------------



T7V 1000
PR232/P LSI
In=1000A 3p
F F



T7V 1000
PR232/P LSI
In=1000A 4p
F F



T7V 1000
PR232/P LSI
In=1000A 4p
F F M



T7V 1000
PR232/P LSI
In=1000A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	14 kg	11 kg
Product Net Width:	210 mm	280 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I_u):	1000 A	1000 A	1000 A	1000 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR331/P LSI G4
In=1000A 3p F
F



T7V 1000
PR331/P LSI G4
In=1000A 4p F
F



T7V 1000
PR331/P LSI G4
In=1000A 3p F
F M



T7V 1000
PR331/P LSI G4
In=1000A 4p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg

Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR332/P LI
In=1000A 3p
F F



T7V 1000
PR332/P LI
In=1000A 4p
F F



T7V 1000
PR332/P LI
In=1000A 3p
F F M



T7V 1000
PR332/P LI
In=1000A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I_u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR332/P LSIG
In=1000A 3p F
F



T7V 1000
PR332/P LSIG
In=1000A 4p
F F



T7V 1000
PR332/P LSIG
In=1000A 3p F
F M



T7V 1000
PR332/P LSIG
In=1000A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG	PR332/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC

Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR332/P LSI
In=1000A 3p
F F



T7V 1000
PR332/P LSI
In=1000A 4p
F F



T7V 1000
PR332/P LSI
In=1000A 3p
F F M



T7V 1000
PR332/P LSI
In=1000A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W

Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1000
PR332/P LSIRc4
In=1000A 3p F
F



T7V 1000
PR332/P LSIRc4
In=1000A 4p F
F



T7V 1000
PR332/P LSIRc4
In=1000A 3p F
F M



T7V 1000
PR332/P LSIRc4
In=1000A 4p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	9.7 kg	12.5 kg	11 kg	14 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	11.2 kg	14 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W	at Rated Operating Conditions per Pole 50 W
Rated Current (I _n):	1000 A	1000 A	1000 A	1000 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1000 A	1000 A	1000 A	1000 A
Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL

Short-Circuit Performance Level:	V	V	V	V
	IEC	IEC	IEC	IEC
	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR231/P I
In=1250A
4p F F



T7V 1250
PR231/P I
In=1250A
3p F F



T7V 1250
PR231/P I
In=1250A
3p F F M



T7V 1250
PR231/P I
In=1250A
4p F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour

Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR231/P-I	PR231/P-I	PR231/P-I	PR231/P-I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR231/P LS/I
In=1250A 3p
F F M



T7V 1250
PR231/P LS/I
In=1250A 4p
F F M



T7V 1250
PR231/P LS/I
In=1250A 3p
F F



T7V 1250
PR231/P LS/I
In=1250A 4p
F F

Dimensions

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm

Product Net Weight:	11 kg	14 kg	9.7 kg	12.5 kg
Product Net Width:	210 mm	280 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	12.5 kg	15.5 kg	11.2 kg	14 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	360 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	4P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA

Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I	PR231/P-LS/I
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR232/P LSI
In=1250A 4p
F F



T7V 1250
PR232/P LSI
In=1250A 3p
F F



T7V 1250
PR232/P LSI
In=1250A 3p
F F M



T7V 1250
PR232/P LSI
In=1250A 4p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker

Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI	PR232/P-LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR331/P LSIG4
In=1250A 4p F
F M



T7V 1250
PR331/P LSIG4
In=1250A 3p F
F M



T7V 1250
PR331/P LSIG4
In=1250A 3p F
F



T7V 1250
PR331/P LSIG4
In=1250A 4p F
F

Dimensions

Product Net Depth / Length:	178 mm	178 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	14 kg	11 kg	9.7 kg	12.5 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	15.5 kg	12.5 kg	11.2 kg	14 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7M	T7M	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC

Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR332/P LI
In=1250A 4p
F F



T7V 1250
PR332/P LI
In=1250A 3p
F F



T7V 1250
PR332/P LI
In=1250A 4p
F F M



T7V 1250
PR332/P LI
In=1250A 3p
F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P LI	PR332/P LI	PR332/P LI	PR332/P LI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC

Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR332/P LSIG
In=1250A 4p F
F



T7V 1250
PR332/P LSIG
In=1250A 3p F
F



T7V 1250
PR332/P LSIG
In=1250A 3p F
F M



T7V 1250
PR332/P LSIG
In=1250A 4p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W

Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P LSIg	PR332/P LSIg	PR332/P LSIg	PR332/P LSIg
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC



T7V 1250

PR332/P LSI

In=1250A 4p

F F



T7V 1250

PR332/P LSI

In=1250A 3p

F F



T7V 1250

PR332/P LSI

In=1250A 4p

F F M



T7V 1250

PR332/P LSI

In=1250A 3p

F F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	14 kg	11 kg
Product Net Width:	280 mm	210 mm	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	14 kg	11.2 kg	15.5 kg	12.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cw}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A

Release:	PR332/P LSI	PR332/P LSI	PR332/P LSI	PR332/P LSI
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7V 1250
PR332/P LSIRc4
In=1250A 4p F
F



T7V 1250
PR332/P LSIRc4
In=1250A 3p F
F



T7V 1250
PR332/P LSIRc4
In=1250A 3p F
F M



T7V 1250
PR332/P LSIRc4
In=1250A 4p F
F M

Dimensions

Product Net Depth / Length:	154 mm	154 mm	178 mm	178 mm
Product Net Height:	268 mm	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg	11 kg	14 kg
Product Net Width:	280 mm	210 mm	210 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	11.2 kg	12.5 kg	15.5 kg
Package Level 1 Height:	350 mm	350 mm	350 mm	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	280 mm	280 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7M	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P	3P	4P
Power Loss:	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W	at Rated Operating Conditions per Pole 78.3 W
Rated Current (I _n):	1250 A	1250 A	1250 A	1250 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 45 kA
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 60 kA
Rated Uninterrupted Current (I _u):	1250 A	1250 A	1250 A	1250 A
Release:	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc	PR332/P-LSIRc
Release Type:	EL	EL	EL	EL
Short-Circuit Performance Level:	V	V	V	V
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7X 800 PR331/P LSIG
In=800A 4p F F



T7X 800 PR331/P LSIG
In=800A 3p F F

Dimensions

Product Net Depth / Length:	154 mm	154 mm
Product Net Height:	268 mm	268 mm
Product Net Weight:	12.5 kg	9.7 kg
Product Net Width:	280 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	14 kg	11.2 kg
Package Level 1 Height:	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	3P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W

Rated Current (I _n):	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA
Rated Uninterrupted Current (I _u):	800 A	800 A
Release:	PR331/P LSIG	PR331/P LSIG
Release Type:	EL	EL
Short-Circuit Performance Level:	X	X
Standards:	IEC	IEC
Sub-type:	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



T7X 800
PR332/P LSI
In=800A 3p F F



T7X 800 PR332/
P LSIG In=800A
3p F F



T7X 800
PR332/P LI
In=800A 3p F
F

Dimensions

Product Net Depth / Length:	154 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm

Product Net Weight:	9.7 kg	9.7 kg	9.7 kg
Product Net Width:	210 mm	210 mm	210 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	11.2 kg	11.2 kg	11.2 kg
Package Level 1 Height:	350 mm	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	280 mm	280 mm	280 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	3P	3P	3P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA
Rated Uninterrupted Current (I_u):	800 A	800 A	800 A
Release:	PR332/P LSI	PR332/P L SIG	PR332/P LI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	X	X	X
Standards:	IEC	IEC	IEC
Sub-type:	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front



**T7X 800
PR332/P LI
In=800A 4p F F**



**T7X 800 PR332/
P L SIG In=800A
4p F F**



**T7X 800
PR332/P LSI
In=800A 4p F F**

Dimensions

Product Net Depth / Length:	154 mm	154 mm	154 mm
Product Net Height:	268 mm	268 mm	268 mm
Product Net Weight:	12.5 kg	12.5 kg	12.5 kg
Product Net Width:	280 mm	280 mm	280 mm

Container Information

Package Level 1 Depth / Length:	360 mm	360 mm	360 mm
Package Level 1 Gross Weight:	14 kg	14 kg	14 kg
Package Level 1 Height:	350 mm	350 mm	350 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	SACE Tmax T	SACE Tmax T	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker	Automatic Circuit Breaker	Automatic Circuit Breaker
Suitable For:	T7	T7	T7
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	F	F	F

Technical

Electrical Durability:	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour	3000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour	10000 cycle 60 cycles per hour
Number of Poles:	4P	4P	4P
Power Loss:	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W	at Rated Operating Conditions per Pole 32 W
Rated Current (I _n):	800 A	800 A	800 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA	(220 V AC) 170 kA (230 V AC) 170 kA (380 V AC) 170 kA (400 V AC) 170 kA (415 V AC) 170 kA (440 V AC) 170 kA (500 V AC) 170 kA (690 V AC) 75 kA
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A
Release:	PR332/P LI	PR332/P LSIG	PR332/P LSI
Release Type:	EL	EL	EL
Short-Circuit Performance Level:	X	X	X
Standards:	IEC	IEC	IEC
Sub-type:	T7	T7	T7
Terminal Connection Type:	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front	Fixed Circuit-Breakers Front

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>