

Реле контроля и управления УС, УО, УУ

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



YC E1.2..E6.2-
XT7M 110-120
VAC/DC



YC E1.2..E6.2-
XT7M 220-240
VAC/DC



YC E1.2..E6.2-
XT7M 120-127
VAC/DC



YC E1.2..E6.2-
XT7M 240-250
VAC/DC

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.15 kg	0.42 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	ACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U _r):	110...120 V	220...240 V	120...127 V	240...250 V
Standards:	IEC	IEC	IEC	IEC



YC E1.2..E6.2-
XT7M

380-400 VAC



YC E1.2..E6.2-
XT7M

415-440 VAC



YC E1.2..E6.2-
XT7M

480-500 VAC



YC E1.2..E6.2-
XT7M 24

VAC/DC

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg	0.4 kg
Product Net Width:	105 mm	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.15 kg	0.15 kg	0.15 kg	0.42 kg
Package Level 1 Height:	55 mm	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	ACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC	AC	AC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U _r):	380...400 V	415...440 V	480...500 V	24 V
Standards:	IEC	IEC	IEC	IEC



**YC E1.2..E6.2-
XT7M 48 VAC/
DC**



**YC E1.2..E6.2-
XT7M 30 VAC/
DC**



**YC E1.2..E6.2-
XT7M 60 VAC/
DC**

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	0.15 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece
Rated Voltage (U _r):	48 V	30 V	60 V
Standards:	IEC	IEC	IEC



**YO-C XT5-XT6
F/P**
**110..240Vac-1
10..250Vdc**



**YO-C XT5-XT6
F/P 24...60**
Vac/dc



YO-C XT6 W
110..240 Vac
- 110..250 Vdc



YO-C XT5 W
110..240 Vac
- 110..250 Vdc

Dimensions

Product Net Weight:	0.17 kg	0.17 kg	0.17 kg	0.17 kg
----------------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
Package Level 1 Gross Weight:	0.2 kg	0.2 kg	0.2 kg	0.2 kg
Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT6	XT5
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	110...240 V AC 110...250 V DC	24...60 V AC 24...60 V DC	110...240 V AC 110...250 V DC	110...240 V AC 110...250 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489



YO-C XT5-XT6
F/P 380...440
Vac



YO-C XT5-XT6
F/P 12 Vdc



YO-C XT6 W
24...604
Vac/dc



YO-C XT5
W24...604
Vac/dc

Dimensions

Product Net Weight:	0.17 kg	0.05 kg	0.17 kg	0.17 kg
----------------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	0.2 kg	0.05 kg	0.2 kg	0.2 kg
Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT6	XT5
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC	DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	380...525 V AC	12 V DC	24...60 V AC 24...60 V DC	24...60 V AC 24...60 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489



YO-C XT5
W 12 Vdc

YO-C XT6
W 12 Vdc

YO-C XT6 W
380...4404
Vac



YO-C XT5 W
380...4404
Vac

Dimensions

Product Net Weight:	0.05 kg	0.05 kg	0.17 kg	0.17 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	0.05 kg	0.05 kg	0.2 kg	0.2 kg
Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT5	XT6	XT6	XT5
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	DC	DC	AC	AC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U _r):	12 V DC	12 V DC	380...525 V AC	380...525 V AC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489



YO E1.2..E6.2-XT7-XT7M

**240-250 VAC/
DC**



YO E1.2..E6.2-XT7-XT7M

**220-240 VAC/
DC**



YO E1.2..E6.2-XT7-XT7M

**120-127 VAC/
DC**



YO E1.2..E6.2-XT7-XT7M

**110-120 VAC/
DC**

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.15 kg	0.346 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	240...250 V	220...240 V	120...127 V	110...120 V
Standards:	IEC	IEC	IEC	IEC



**YO E1.2..E6.2-
XT7-XT7M424
VAC/DC**



**YO E1.2..E6.2-
XT7-XT7M430
VAC/DC**



**YO E1.2..E6.2-
XT7-XT7M448
VAC/DC**



**YO E1.2..E6.2-
XT7-XT7M
415-440 VAC**

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm	55 mm
Product Net Weight:	0.4 kg	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.42 kg	0.15 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	ACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	24 V	30 V	48 V	415...440 V
Standards:	IEC	IEC	IEC	IEC



YO E1.2..E6.2-XT7-XT7M
480-500 VAC



YO E1.2..E6.2-XT7M 604VAC/DC



YO E1.2..E6.2-XT7-XT7M
380-400 VAC

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.15 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC	AC/DC	AC
Order Multiple:	1 piece	1 piece	1 piece
Rated Voltage (U _r):	480...500 V	60 V	380...400 V
Standards:	IEC	IEC	IEC



YO XT5-XT6
110..240 Vac
-110..250 Vdc



YO XT5-XT6
72 Vdc4
SPEC.VERS.



YO XT5-XT6
24...60 Vac/dc

Dimensions

Product Net Weight:	0.17 kg	0.101 kg	0.12 kg
---------------------	---------	----------	---------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm
Package Level 1 Gross Weight:	0.2 kg	0.106 kg	0.15 kg
Package Level 1 Height:	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT5 XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tmax XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	N/A	AC/DC
Order Multiple:	1 piece	N/A	1 piece
Rated Voltage (U _r):	110...240 V AC 110...250 V DC	N/A	24...60 V AC 24...60 V DC
Standards:	IEC60947-2 UL489	IEC60947-2	IEC60947-2 UL489



YO XT5-XT6
380...440 Vac



YO XT5-XT6
12 Vdc

Dimensions

Product Net Weight:	0.12 kg	0.05 kg
---------------------	---------	---------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm
Package Level 1 Gross Weight:	0.15 kg	0.05 kg
Package Level 1 Height:	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory
Product Type:	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable
Current Type:	AC	DC
Order Multiple:	1 piece	1 piece
Rated Voltage (U _r):	380...525 V AC	12 V DC
Standards:	IEC60947-2	IEC60947-2 UL489



**YU-C XT5-
XT6 F/P**
**110..127Vac-1
10..125Vdc**



**YU-C XT5-XT6
F/P**
**220..240Vac-2
20..250Vdc**



YU-C XT5 W
**220..240 Vac
- 220..250 Vdc**



YU-C XT5 W
**110..127 Vac
-110..125 Vdc**

Dimensions

Product Net Weight:	0.124 kg	0.143 kg	0.12 kg	0.115 kg
---------------------	----------	----------	---------	----------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
Package Level 1 Gross Weight:	0.13 kg	0.15 kg	0.126 kg	0.121 kg
Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT5	XT5
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U _r):	110...127 V AC 110...125 V DC	220...240 V AC 220...250 V DC	220...240 V AC 220...250 V DC	110...127 V AC 110...125 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489



**YU-C XT5-XT6
F/P 24...304
Vac/dc**



**YU-C XT5-XT6
F/P 48...604
Vac/dc**



**YU-C XT5-
XT6 F/P4
380...440
Vac**



**YU-C XT5-XT6
F/P 12 Vdc**

Dimensions

Product Net Weight:	0.109 kg	0.121 kg	0.123 kg	0.123 kg
----------------------------	----------	----------	----------	----------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
--	--------	--------	--------	--------

Package Level 1 Gross Weight:	0.115 kg	0.127 kg	0.129 kg	0.129 kg
--------------------------------------	----------	----------	----------	----------

Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
--------------------------------	-------	-------	-------	-------

Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
-------------------------------	-------------	-------------	-------------	-------------

Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm
-------------------------------	--------	--------	--------	--------

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT5 XT6	XT5 XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC	DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	24...30 V AC 24...30 V DC	48...60 V AC 48...60 V DC	380...440 V AC	12 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489



YU-C XT5
W 12 Vdc



YU-C XT5 W
380...440 V
Vac



YU-C XT5 W
48...60 V
Vac/dc



YU-C XT5 W
24...30 V
Vac/dc

Dimensions

Product Net Weight:	0.118 kg	0.116 kg	0.123 kg	0.118 kg
---------------------	----------	----------	----------	----------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	0.124 kg	0.122 kg	0.129 kg	0.124 kg
-------------------------------	----------	----------	----------	----------

Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	DC	AC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U _r):	12 V DC	380...440 V AC	48...60 V AC 48...60 V DC	24...30 V AC 24...30 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489

YU-C XT6 W 110..127 Vac -110..125 Vdc	YU-C XT6 W 220..240 Vac - 220..250 Vdc	YU-C XT6 W 24...304 Vac/dc	YU-C XT6 W 48...604 Vac/dc
---	--	----------------------------------	----------------------------------

Dimensions

Product Net Weight:	0.118 kg	0.116 kg	0.118 kg	0.12 kg
---------------------	----------	----------	----------	---------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm	140 mm
Package Level 1 Gross Weight:	0.124 kg	0.122 kg	0.124 kg	0.126 kg
Package Level 1 Height:	60 mm	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT6	XT6	XT6	XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U _r):	110...127 V AC 110...125 V DC	220...240 V AC 220...250 V DC	24...30 V AC 24...30 V DC	48...60 V AC 48...60 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489

YU-C XT6 W
380...440 Vac

YU-C XT6 W
12 Vdc

Dimensions

Product Net Weight:	0.123 kg	0.115 kg
---------------------	----------	----------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm
Package Level 1 Gross Weight:	0.129 kg	0.121 kg
Package Level 1 Height:	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory
Product Type:	Accessory	Accessory
Suitable For:	XT6	XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable
Current Type:	AC	DC
Order Multiple:	1 piece	1 piece
Rated Voltage (U _r):	380...440 V AC	12 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489



YU E1.2..E6.2-XT7-XT7M
120-127 VAC/DC

YU E1.2..E6.2-XT7-XT7M
110-120 VAC/DC

YU E1.2..E6.2-XT7-XT7M
220-240 VAC/DC

YU E1.2..E6.2-XT7-XT7M
240-250 VAC/DC

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.15 kg	0.15 kg	0.42 kg	0.442 kg
Package Level 1 Height:	55 mm	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	ACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	120...127 V	110...120 V	220...240 V	240...250 V
Standards:	IEC	IEC	IEC	IEC



**YU E1.2..E6.2-
XT7-XT7M424**
VAC/DC



**YU E1.2..E6.2-
XT7-XT7M430**
VAC/DC



**YU E1.2..E6.2-
XT7-XT7M460**
VAC/DC



**YU E1.2..E6.2-
XT7-XT7M448**
VAC/DC

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm	55 mm
Product Net Weight:	0.4 kg	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.42 kg	0.15 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	ACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Voltage (U_r):	24 V	30 V	60 V	48 V
Standards:	IEC	IEC	IEC	IEC



**YU E1.2..E6.2-
XT7-XT7M**
380-400 VAC



**YU E1.2..E6.2-
XT7-XT7M**
415-440 VAC



**YU E1.2..E6.2-
XT7-XT7M**
480-500 VAC

Dimensions

Product Net Depth / Length:	135 mm	135 mm	135 mm
Product Net Height:	55 mm	55 mm	55 mm
Product Net Weight:	0.12 kg	0.12 kg	0.12 kg
Product Net Width:	105 mm	105 mm	105 mm

Container Information

Package Level 1 Depth / Length:	135 mm	135 mm	135 mm
Package Level 1 Gross Weight:	0.15 kg	0.15 kg	0.15 kg
Package Level 1 Height:	55 mm	55 mm	55 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	105 mm	105 mm	105 mm

Additional Information

Product Main Type:	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT	Accessories for Emax 2, Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory
Suitable For:	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2	XT7-XT7M, E1.2, E2.2, E4.2, E6.2
Suitable for Product Class:	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2	SACE Tmax XT, SACE Emax 2

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC	AC	AC
Order Multiple:	1 piece	1 piece	1 piece
Rated Voltage (U_r):	380...400 V	415...440 V	480...500 V
Standards:	IEC	IEC	IEC



YU XT5-XT6
220..240 Vac
-220..250 Vdc



YU XT5-XT6
110..127 Vac
-110..125 Vdc



YU XT5-XT6
24...30 Vac/dc

Dimensions

Product Net Weight:	0.107 kg	0.108 kg	0.109 kg
---------------------	----------	----------	----------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	0.113 kg	0.114 kg	0.115 kg
Package Level 1 Height:	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT5 XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC/DC	AC/DC
Order Multiple:	1 piece	1 piece	1 piece
Rated Voltage (U _r):	220...240 V AC 220...250 V DC	110...127 V AC 110...125 V DC	24...30 V AC 24...30 V DC
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489



YU XT5-XT6
48...60 Vac/dc



YU XT5-XT6
380...440 Vac



YU XT5-XT6
12 Vdc

Dimensions

Product Net Weight:	0.123 kg	0.115 kg	0.109 kg
---------------------	----------	----------	----------

Container Information

Package Level 1 Depth / Length:	140 mm	140 mm	140 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	0.129 kg	0.121 kg	0.115 kg
Package Level 1 Height:	60 mm	60 mm	60 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	110 mm	110 mm	110 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Accessory	Accessory	Accessory
Suitable For:	XT5 XT6	XT5 XT6	XT5 XT6
Suitable for Product Class:	SACE Tamx XT	SACE Tamx XT	SACE Tamx XT

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Current Type:	AC/DC	AC	DC
Order Multiple:	1 piece	1 piece	1 piece
Rated Voltage (U _r):	48...60 V AC 48...60 V DC	380...440 V AC	12 V DC
Standards:	IEC60947-2 UL489	IEC60947-2	IEC60947-2 UL489

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>