

Части фиксированные

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>



**E1.2-A W FP 1200 3p
HR HR
1SDA079696R1**



**E1.2-A W FP 1200 4p
HR HR
1SDA079697R1**

Dimensions

Product Net Depth / Length:	281 mm	281 mm
Product Net Height:	363.5 mm	363.5 mm
Product Net Weight:	21.7 kg	24.6 kg
Product Net Width:	278 mm	348 mm

Container Information

Package Level 1 Depth / Length:	373 mm	388 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	24 kg	27 kg
Package Level 1 Height:	330 mm	330 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	320 mm	375 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP



Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _u]):	N/A	100 %
Number of Poles:	3P	4P
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	1200 A	1200 A
Rated Voltage (U _r):	600 V	600 V
Standards:	UL	UL
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal



E1.2 W FP Iu=1600 3p
HR HR
1SDA073907R1



E1.2 W FP Iu=1600 4p
HR HR
1SDA073908R1



Dimensions

Product Net Depth / Length:	271 mm	271 mm
Product Net Height:	363.5 mm	363.5 mm

Product Net Weight:	20 kg	23 kg
Product Net Width:	278 mm	348 mm

Container Information

Package Level 1 Depth / Length:	373 mm	388 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	23 kg	26 kg
Package Level 1 Height:	330 mm	330 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	320 mm	375 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP

Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _n]):	N/A	100 %
Number of Poles:	3P	4P
Rated Current (I _n):	1600 A	1600 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC	690 V AC 800 V AC
Rated Uninterrupted Current (I _u):	1600 A	1600 A
Rated Voltage (U _r):	690 V	690 V
Recommended Screw Driver:	Main Circuit M10	Main Circuit M10
Standards:	IEC	IEC
Sub-type:	E1.2	E1.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt
Tightening Torque:	45 N·m	45 N·m

**E1/
EWFP3p750VDCFL
-FLnew
1SDA059898R1**

**E1/
EWFP3p750VDCHR
-HRnew
1SDA059890R1**

**E1/
EWFP3p750VDCVR
-VRnew
1SDA059894R1**

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	26 kg	26 kg	26 kg
Product Net Width:	324 mm	324 mm	324 mm

Container Information

Package Level 1 Depth / Length:	600 mm	600 mm	600 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	40 kg	40 kg	40 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	440 mm	440 mm	440 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	3P	3P	3P
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A
Rated Voltage (U _r):	750 V	750 V	750 V
Standards:	IEC	IEC	IEC
Sub-type:	E1	E1	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical

	E1/ EWFP4p1000VDCF L-FLnew 1SDA059908R1	E1/ EWFP4p1000VDCH R-HRnew 1SDA059902R1	E1/ EWFP4p1000VDCV R-VRnew 1SDA059905R1
--	--	--	--

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	36 kg	36 kg	36 kg
Product Net Width:	414 mm	414 mm	414 mm

Container Information

Package Level 1 Depth / Length:	600 mm	600 mm	600 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	40 kg	40 kg	40 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	545 mm	545 mm	545 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	4P	4P	4P
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A
Rated Voltage (U _r):	1000 V	1000 V	1000 V
Standards:	IEC	IEC	IEC
Sub-type:	E1	E1	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical

**E1WFP3pF-
Fnew
1SDA059678R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Package Level 1 Gross Weight:	42 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E1/EWFP3p750VDCFL-
FLnew
1SDA059898R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Container Information

Package Level 1 Depth / Length:	600 mm
Package Level 1 EAN:	
Package Level 1 Gross Weight:	40 kg
Package Level 1 Height:	590 mm
Package Level 1 Units:	box 1 piece
Package Level 1 Width:	440 mm

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	DC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	1600 A
Rated Voltage (U _r):	750 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers

**E1WFP3pFL-
HRnew
1SDA059744R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Container Information

Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E1WFP3pHR-
FLnew
1SDA059702R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E1B/N-A W FP 3p HR-HR

new

1SDA061761R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Short-Circuit Performance Level:	B
Standards:	UL 1066
Sub-type:	E1

**E1WFP3pHR-
VRnew
1SDA059690R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Container Information

Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E1WFP3pVR-
HRnew
1SDA059708R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Container Information

Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E1WFP3pVR-
VRnew
1SDA059672R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Container Information

Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

E1WFP3pVR-
VRnew
1SDA059672R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	26 kg
Product Net Width:	324 mm

Container Information

Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	1600 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

E1WFP4pF-
Fnew4
1SDA059778R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm
Package Level 1 Gross Weight:	48 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E1WFP4pFL-
FLnew4
1SDA059786R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	1600 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers

**E1WFP4pFL-
HRnew4
1SDA059866R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E1WFP4pHR-
FLnew4
1SDA059810R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E1WFP4pHR-
HRnew4
1SDA059762R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E1WFP4pHR-
VRnew4
1SDA059794R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E1WFP4pVR-
HRnew4
1SDA059818R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E1WFP4pVR-
VRnew4
1SDA059770R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	36 kg
Product Net Width:	414 mm

Container Information

Package Level 1 Gross Weight:	40 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	1600 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical



**E2.2 W FP lu=2000 3p
HR HR
1SDA073909R1**



**E2.2 W FP lu=2000 4p
HR HR
1SDA073910R1**

Dimensions

Product Net Depth / Length:	383 mm	383 mm
Product Net Height:	425 mm	425 mm
Product Net Weight:	36 kg	44 kg
Product Net Width:	317 mm	407 mm

Container Information

Package Level 1 Depth / Length:	515 mm	615 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	41 kg	49 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP



Technical

Current Type:	AC	AC
Electrical Durability:	2000 cycle	2000 cycle
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour
Neutral Pole Current ([%I _u]):	N/A	100 %
Number of Poles:	3P	4P
Rated Current (I _n):	2000 A	2000 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC
Rated Uninterrupted Current (I _u):	2000 A	2000 A
Rated Voltage (U _r):	690 V	690 V
Recommended Screw Driver:	Main Circuit M12	Main Circuit M12
Standards:	IEC	IEC
Sub-type:	E2.2	E2.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt
Tightening Torque:	70 N·m	70 N·m



E2.2 W FP
I_u=2000 4p HR
HR
1SDA073910R1



E2.2 W FP
I_u=2000 3p HR
HR
1SDA073909R1



E2.2 W FP
I_u=2500 3p HR
HR
1SDA073911R1



E2.2 W FP
I_u=2500 4p HR
HR
1SDA073912R1



Dimensions

Product Net Depth / Length:	383 mm	383 mm	383 mm	383 mm
Product Net Height:	425 mm	425 mm	425 mm	425 mm
Product Net Weight:	44 kg	36 kg	36 kg	44 kg
Product Net Width:	407 mm	317 mm	317 mm	407 mm

Container Information

Package Level 1 Depth / Length:	615 mm	515 mm	515 mm	615 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	49 kg	41 kg	41 kg	49 kg
Package Level 1 Height:	610 mm	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Version:	W FP	W FP	W FP	W FP

Technical

Current Type:	AC	AC	AC	AC
Electrical Durability:	2000 cycle	2000 cycle	N/A	N/A
Mechanical Durability:	25000 cycle 60 cycles per hour	25000 cycle 60 cycles per hour	N/A	N/A
Neutral Pole Current ([%I _n]):	100 %	N/A	N/A	100 %
Number of Poles:	4P	3P	3P	4P
Rated Current (I _n):	2000 A	2000 A	2500 A	2500 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC 1000 V AC	690 V AC 800 V AC 900 V AC
Rated Uninterrupted Current (I _u):	2000 A	2000 A	2500 A	2500 A
Rated Voltage (U _r):	690 V	690 V	690 V	690 V
Recommended Screw Driver:	Main Circuit M12	Main Circuit M12	Main Circuit M12	Main Circuit M12
Standards:	IEC	IEC	IEC	IEC
Sub-type:	E2.2	E2.2	E2.2	E2.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt	Bolt	Bolt
Tightening Torque:	70 N·m	70 N·m	70 N·m	70 N·m

	E2/ EWFP3p750VDCVR -VRnew 1SDA059895R1	E2/ EWFP3p750VDCFL -FLnew 1SDA059899R1	E2/ EWFP3p750VDCHR -HRnew 1SDA059891R1
--	---	---	---

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	29 kg	29 kg	29 kg
Product Net Width:	324 mm	324 mm	324 mm

Container Information

Package Level 1 Depth / Length:	600 mm	600 mm	600 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	40 kg	40 kg	40 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	440 mm	440 mm	440 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	3P	3P	3P
Rated Uninterrupted Current (I _u):	2500 A	2500 A	2500 A
Rated Voltage (U _r):	750 V	750 V	750 V
Standards:	IEC	IEC	IEC
Sub-type:	E2	E2	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal

	E2/ EWFP4p1000VDCV R-VRnew 1SDA059906R1	E2/ EWFP4p1000VDCF L-FLnew 1SDA059909R1	E2/ EWFP4p1000VDCH R-HRnew 1SDA059903R1
--	--	--	--

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	39 kg	39 kg	39 kg
Product Net Width:	414 mm	414 mm	414 mm

Container Information

Package Level 1 Depth / Length:	600 mm	600 mm	600 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	40 kg	40 kg	40 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	545 mm	545 mm	545 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	4P	4P	4P
Rated Uninterrupted Current (I _u):	2500 A	2500 A	2500 A
Rated Voltage (U _r):	1000 V	1000 V	1000 V
Standards:	IEC	IEC	IEC
Sub-type:	E2	E2	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2SWFP3pF-
Fnew
1SDA059680R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	57 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E2SWFP3pF-
Fnew
1SDA059680R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	57 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

**E2SWFP3pFL-
HRnew
1SDA059746R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2SWFP3pHR-
FLnew
1SDA059704R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E2SWFP3pHR-
HRnew
1SDA059668R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2SWFP3pHR-
VRnew
1SDA059692R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	37 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E2SWFP3pVR-
HRnew
1SDA059710R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E2SWFP3pVR-
VRnew
1SDA059674R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

E2SWFP4pF-
Fnew4
1SDA059780R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	72 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E2SWFP4pFL-
FLnew4
1SDA059788R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers

**E2SWFP4pFL-
HRnew4
1SDA059868R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2SWFP4pHR-
FLnew4
1SDA059812R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2SWFP4pHR-
HRnew4
1SDA059764R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E2SWFP4pHR-
VRnew4
1SDA059796R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E2SWFP4pVR-
HRnew4
1SDA059820R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E2SWFP4pVR-
VRnew4
1SDA059772R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

**E2WFP3pHR-
FLnew
1SDA059703R1**



Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm



Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece



Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP



Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E2WFP3pHR-
FLnew
1SDA059703R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2WFP3pHR-
FLnew
1SDA059703R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2WFP3pVR-
HRnew
1SDA059709R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E2WFP3pVR-
VRnew
1SDA059673R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	29 kg
Product Net Width:	324 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	36 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

E2WFP4pF-
Fnew4
1SDA059779R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	72 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	2000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E2WFP4pFL-
FLnew4
1SDA059787R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers

**E2WFP4pFL-
HRnew4
1SDA059867R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2WFP4pHR-
FLnew4
1SDA059811R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2WFP4pHR-
FLnew4
1SDA059811R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E2WFP4pHR-
VRnew4
1SDA059795R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	39 kg
Product Net Width:	414 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	44 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E2SWFP4pVR-
HRnew4
1SDA059820R1**

**E2WFP4pVR-
HRnew4
1SDA059819R1**

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm
Product Net Weight:	39 kg	39 kg
Product Net Width:	414 mm	414 mm

Container Information

Package Level 1 EAN:		
Package Level 1 Gross Weight:	44 kg	44 kg
Package Level 1 Units:	1 piece	1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	WFP	WFP

Technical

Current Type:	AC	AC
Number of Poles:	4P	4P
Rated Uninterrupted Current (I _u):	2000 A	N/A
Rated Voltage (U _r):	690 V	690 V
Standards:	IEC	IEC
Sub-type:	E2	E2
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated	Withdrawable Circuit-Breakers Rear flat Orientated



**E3/
EWFP3p750VDCHR
-HRnew
1SDA059892R1**



**E3/
EWFP3p750VDCVR
-VRnew
1SDA059896R1**



**E3/
EWFP3p750VDCFL
-FLnew
1SDA059900R1**

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	37 kg	37 kg	37 kg
Product Net Width:	432 mm	432 mm	432 mm

Container Information

Package Level 1 Depth / Length:	600 mm	600 mm	600 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	40 kg	40 kg	40 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	545 mm	545 mm	545 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	3P	3P	3P
Rated Uninterrupted Current (I_u):	3200 A	3200 A	3200 A
Rated Voltage (U_r):	750 V	750 V	750 V
Standards:	IEC	IEC	IEC
Sub-type:	E3	E3	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers

	E3/ EWFP4p1000VDCV R-VRnew 1SDA059907R1	E3/ EWFP4p1000VDCH R-HRnew 1SDA059904R1	E3/ EWFP4p1000VDCFL -FLnew 1SDA059910R1
--	--	--	--

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	49 kg	49 kg	49 kg
Product Net Width:	558 mm	558 mm	558 mm

Container Information

Package Level 1 Depth / Length:	670 mm	670 mm	N/A
Package Level 1 EAN:			
Package Level 1 Gross Weight:	59 kg	59 kg	40 kg
Package Level 1 Height:	590 mm	590 mm	N/A
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	630 mm	630 mm	N/A

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	4P	4P	4P
Rated Uninterrupted Current (I _u):	3200 A	3200 A	3200 A
Rated Voltage (U _r):	1000 V	1000 V	1000 V
Standards:	IEC	IEC	IEC
Sub-type:	E3	E3	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers



E3N/S-A (08,12,16,20,25)
WFP 3p HR-HRnew
1SDA061545R1



E3H/V-A (08,12,16,20,25)
WFP 3p HR-HRnew
1SDA061565R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm
Product Net Weight:	37 kg	37 kg
Product Net Width:	432 mm	432 mm

Container Information

Package Level 1 EAN:

Additional Information

Product Main Type:	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part
Product Type:	FP	FP
Version:	W FP	W FP

Technical

Current Type:	AC	AC
Number of Poles:	3P	3P
Rated Voltage (U _r):	600 V	600 V
Standards:	UL 1066	UL 1066
Sub-type:	E3	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal



**E3H/
VFWFP3pVR-
VRnew
1SDA069589R1**



**E3H/
VFWFP3pVR-
HRnew
1SDA069511R1**



**E3H/
VFWFP3pHR-
VRnew
1SDA069510R1**



**E3H/
VFWFP3pHR-
HRnew
1SDA069588R1**

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm	461 mm
Product Net Weight:	37 kg	37 kg	37 kg	37 kg
Product Net Width:	432 mm	432 mm	432 mm	432 mm

Container Information

Package Level 1 EAN:				
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP	WFP

Technical

Current Type:	AC	AC	AC	AC
Number of Poles:	3P	3P	3P	3P
Rated Voltage (U _r):	690 V	690 V	690 V	690 V
Short-Circuit Performance Level:	H	H	H	H
Standards:	IEC	IEC	IEC	IEC
Sub-type:	E3	E3	E3	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Rear flat Orientated	Withdrawable Circuit-Breakers Rear flat Orientated	Withdrawable Circuit-Breakers Rear flat Horizontal



E3WFP3pF-Fnew
1SDA059681R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	85 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	3200 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Front



**E3WFP3pFL-
FLnew4
1SDA059687R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	51 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers



**E3WFP3pFL-
HRnew
1SDA059747R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	51 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal



**E3WFP3pHR-
FLnew
1SDA059705R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	51 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal



E3X-A W FP 3p HR-HR
new
1SDA063903R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Standards:	UL 1066
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal



**E3WFP3pHR-
VRnew
1SDA059693R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	51 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	3200 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated



**E3WFP3pVR-
HRnew
1SDA059711R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	51 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated



**E3WFP3pVR-
VRnew
1SDA059675R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	51 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	3200 A
Rated Voltage (U_r):	690 V
Release Type:	EL
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

**E3WFP4pF-
Fnew4
1SDA059781R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	101 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	3200 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E3WFP4pF-
Fnew4
1SDA059781R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	101 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	3200 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E3

Terminal Connection Type: Withdrawable Circuit-Breakers
Front

**E3WFP4pFL-
HRnew4
1SDA059869R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	56 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E3WFP4pHR-
FLnew4
1SDA059813R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	56 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E3WFP4pHR-
HRnew4
1SDA059765R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	56 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	3200 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E3WFP4pHR-
VRnew4
1SDA059797R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	56 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	3200 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E3WFP4pVR-
HRnew4
1SDA059821R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	56 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	3200 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E3WFP4pVR-
VRnew4
1SDA059773R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	49 kg
Product Net Width:	558 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	56 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	3200 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical



E3X-A W FP 3p HR-HR
new
1SDA063903R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	37 kg
Product Net Width:	432 mm

Container Information

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Standards:	UL 1066
Sub-type:	E3
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal



E4.2 /E12 W FP lu=4000 3p
SVR SVR
1SDA121089R1



E4.2 /E12 W FP lu=3200 3p
HR HR
1SDA121088R1

Dimensions

Product Net Depth / Length:	383 mm	383 mm
Product Net Height:	425 mm	425 mm
Product Net Weight:	50 kg	50 kg
Product Net Width:	425 mm	425 mm

Container Information

Package Level 1 Depth / Length:	710 mm	710 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	57 kg	57 kg
Package Level 1 Height:	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	630 mm	630 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP



Technical

Current Type:	AC	AC
Number of Poles:	3P	3P
Rated Current (I _n):	4000 A	3200 A
Rated Impulse Withstand Voltage (U _{imp}):	15 kV	15 kV
Rated Insulation Voltage (U _i):	1500 V	1500 V
Rated Operational Voltage:	1000 V AC 1200 V AC	1000 V AC 1200 V AC
Rated Uninterrupted Current (I _u):	4000 A	3200 A
Rated Voltage (U _r):	1200 V	1200 V
Remarks:	E12	E12
Standards:	IEC	IEC
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Horizontal



E4.2-A W FP 2500 4p
HR HR
1SDA079701R1



E4.2-A W FP 2500 3p
HR HR
1SDA079700R1



Dimensions

Product Net Depth / Length:	393 mm	393 mm
Product Net Height:	425 mm	425 mm

Product Net Weight:	67 kg	50 kg
Product Net Width:	551 mm	425 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	79 kg	52 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP

Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _n]):	100 %	N/A
Number of Poles:	4P	3P
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	2500 A	2500 A
Rated Voltage (U _r):	600 V	600 V
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal



**E4.2-A W FP 3200 3P
VR VR
1SDA079702R1**



**E4.2-A W FP 3200 4P
VR VR
1SDA079703R1**

Dimensions

Product Net Depth / Length:	393 mm	393 mm
Product Net Height:	425 mm	425 mm
Product Net Weight:	50 kg	67 kg
Product Net Width:	425 mm	551 mm

Container Information

Package Level 1 Depth / Length:	615 mm	785 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	52 kg	79 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP



Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _u]):	N/A	100 %
Number of Poles:	3P	4P
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	3200 A	3200 A
Rated Voltage (U _r):	600 V	600 V
Standards:	UL	UL
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Vertical	Rear flat Vertical



E4.2 W FP Iu=3200 3p
HR HR
1SDA073913R1



E4.2 W FP Iu=3200 4p
HR HR
1SDA073914R1



Dimensions

Product Net Depth / Length:	383 mm	383 mm
Product Net Height:	425 mm	425 mm

Product Net Weight:	50 kg	62 kg
Product Net Width:	425 mm	551 mm

Container Information

Package Level 1 Depth / Length:	615 mm	785 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	57 kg	69 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP

Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _n]):	N/A	100 %
Number of Poles:	3P	4P
Rated Current (I _n):	3200 A	3200 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC
Rated Uninterrupted Current (I _u):	3200 A	3200 A
Rated Voltage (U _r):	690 V	690 V
Recommended Screw Driver:	Main Circuit M12	Main Circuit M12
Standards:	IEC	IEC
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt
Tightening Torque:	70 N·m	70 N·m



**E4.2 W FP lu=4000 or V
version 4p HR HR
1SDA073916R1**



**E4.2 W FP lu=4000 or V
version 3p HR HR
1SDA073915R1**

Dimensions

Product Net Depth / Length:	383 mm	383 mm
Product Net Height:	425 mm	425 mm
Product Net Weight:	62 kg	50 kg
Product Net Width:	551 mm	425 mm

Container Information

Package Level 1 Depth / Length:	785 mm	615 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	69 kg	57 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP



Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _u]):	100 %	N/A
Number of Poles:	4P	3P
Rated Current (I _n):	4000 A	4000 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC 1000 V AC
Rated Uninterrupted Current (I _u):	4000 A	4000 A
Rated Voltage (U _r):	690 V	690 V
Recommended Screw Driver:	Main Circuit M12	Main Circuit M12
Standards:	IEC	IEC
Sub-type:	E4.2	E4.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt
Tightening Torque:	70 N·m	70 N·m

E4/E/
fWFP4p1000VDCVR-
VRnew
1SDA059137R1

E4/E/
fWFP4p1000VDCFL-
FLnew
1SDA059138R1

E4/E/
fWFP4p1000VDCHR4
HRnew
1SDA059136R1



Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	84 kg	84 kg	84 kg
Product Net Width:	774 mm	774 mm	774 mm

--	--	--	--

Container Information

Package Level 1 Depth / Length:	795 mm	795 mm	795 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	96 kg	96 kg	96 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	630 mm	630 mm	630 mm

--	--	--	--

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

--	--	--	--

Technical

Current Type:	DC	DC	DC
Number of Poles:	4 / f	4 / f	4 / f
Rated Uninterrupted Current (I _u):	4000 A	4000 A	4000 A
Rated Voltage (U _r):	1000 V	1000 V	1000 V
Standards:	IEC	IEC	IEC
Sub-type:	E4	E4	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal

E4/
EWFP3p750VDCVR
-VRnew4
1SDA059897R1

E4/
EWFP3p750VDCFL
-FLnew4
1SDA059901R1

E4/
EWFP3p750VDCHR
-HRnew4
1SDA059893R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	50 kg	50 kg	50 kg
Product Net Width:	594 mm	594 mm	594 mm

Container Information

Package Level 1 Depth / Length:	710 mm	710 mm	710 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	62 kg	62 kg	62 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	630 mm	630 mm	630 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	3P	3P	3P
Rated Uninterrupted Current (I _u):	4000 A	4000 A	4000 A
Rated Voltage (U _r):	750 V	750 V	750 V
Standards:	IEC	IEC	IEC
Sub-type:	E4	E4	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal

E4V/L-A W FP 3p HR-HR

new

1SDA061745R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	42 kg
Product Net Width:	594 mm

Container Information

--

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Standards:	UL 1066
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP3pF-
Fnew4
1SDA059682R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	117 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

**E4WFP3pFL-
FLnew4
1SDA059688R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers

E4WFP3pFL-
HRnew4
1SDA059748R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP3pHR-
FLnew4
1SDA059706R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP3pHR-
HRnew4
1SDA059670R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	4000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP3pHR-
VRnew4
1SDA059694R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	8015644609139
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	4000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E4WFP3pVR-
HRnew4
1SDA059712R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E4WFP3pVR-
VRnew4
1SDA059676R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	50 kg
Product Net Width:	594 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	65 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

E4WFP4pF-
Fnew4
1SDA059782R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	139 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	4000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

**E4WFP4pFL-
FLnew4
1SDA059790R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E4

Terminal Connection Type: Withdrawable Circuit-Breakers

**E4WFP4pFL-
HRnew4
1SDA059870R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP4pHR-
FLnew4
1SDA059814R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP4pHR-
HRnew4
1SDA059766R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E4WFP4pHR-
VRnew4
1SDA059798R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	4000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E4WFP4pVR-
HRnew4
1SDA059822R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I _u):	4000 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E4WFP4pVR-
VRnew4
1SDA059774R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	67 kg
Product Net Width:	684 mm

Container Information


Package Level 1 EAN:	
Package Level 1 Gross Weight:	70 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical



E6.2-A/f W FP 5000 4p HR

HR4

1SDA079708R1

Dimensions

Product Net Depth / Length:	393 mm
Product Net Height:	425 mm
Product Net Weight:	84 kg
Product Net Width:	1055 mm

Container Information

Package Level 1 Depth / Length:	1257 mm
Package Level 1 EAN:	
Package Level 1 Gross Weight:	110 kg
Package Level 1 Height:	610 mm
Package Level 1 Units:	box 1 piece
Package Level 1 Width:	570 mm


Additional Information

Product Main Type:	SACE Emax 2
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	W FP




Technical

Current Type:	AC
Neutral Pole Current ([%I _N]):	100 %
Number of Poles:	4 / f
Rated Insulation Voltage (U _i):	AC 635 V
Rated Operational Voltage:	600 V AC
Rated Uninterrupted Current (I _u):	5000 A
Rated Voltage (U _r):	600 V
Standards:	UL
Sub-type:	E6.2
Terminal Connection Type:	Rear flat Horizontal



E6.2-A W FP 5000 4p
HR HR
1SDA079707R1



E6.2-A W FP 5000 3p
HR HR
1SDA079706R1



Dimensions

Product Net Depth / Length:	393 mm	393 mm
Product Net Height:	425 mm	425 mm

Product Net Weight:	90 kg	70 kg
Product Net Width:	929 mm	425 mm

Container Information


Package Level 1 Depth / Length:	1127 mm	1000 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	100 kg	88 kg
Package Level 1 Height:	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP

Technical

Current Type:	AC	AC
Neutral Pole Current ([%I _n]):	50 %	N/A
Number of Poles:	4P	3P
Rated Insulation Voltage (U _i):	AC 635 V	AC 635 V
Rated Operational Voltage:	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	5000 A	5000 A
Rated Voltage (U _r):	600 V	600 V
Standards:	UL	UL
Sub-type:	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal



E6.2-A W FP 6000 3p

VR VR

1SDA079709R1

Dimensions

Product Net Depth / Length:	393 mm
Product Net Height:	425 mm
Product Net Weight:	70 kg
Product Net Width:	425 mm

Container Information


Package Level 1 Depth / Length:	1000 mm
Package Level 1 EAN:	
Package Level 1 Gross Weight:	88 kg
Package Level 1 Height:	610 mm
Package Level 1 Units:	box 1 piece
Package Level 1 Width:	570 mm

Additional Information


Product Main Type:	SACE Emax 2
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	W FP

Technical


Current Type:	AC
Number of Poles:	3P
Rated Insulation Voltage (U _i):	AC 635 V
Rated Operational Voltage:	600 V AC
Rated Uninterrupted Current (I _u):	6000 A
Rated Voltage (U _r):	600 V
Standards:	UL
Sub-type:	E6.2
Terminal Connection Type:	Rear flat Vertical



E6.2 W FP lu=5000
3p HR HR
1SDA073917R1



E6.2 W FP lu=5000
4p HR HR
1SDA073918R1



E6.2 W FP
lu=5000 4p/f HR
HR
1SDA073919R1

Dimensions

Product Net Depth / Length:	383 mm	383 mm	383 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	87 kg	100 kg	112 kg
Product Net Width:	803 mm	929 mm	1069 mm

Container Information


Package Level 1 Depth / Length:	1000 mm	1127 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	96 kg	109 kg	123 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm	570 mm

Additional Information


Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	W FP	W FP	W FP

Technical


Current Type:	AC	AC	AC
Neutral Pole Current ([%I _u]):	N/A	50 %	100 %
Number of Poles:	3P	4P	4 / f
Rated Current (I _n):	5000 A	5000 A	5000 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC	690 V AC
Rated Uninterrupted Current (I _u):	5000 A	5000 A	5000 A
Rated Voltage (U _r):	690 V	690 V	690 V
Recommended Screw Driver:	Main Circuit M12	Main Circuit M12	Main Circuit M12
Standards:	IEC	IEC	IEC
Sub-type:	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt	Bolt
Tightening Torque:	70 N·m	70 N·m	70 N·m



E6.2 W FP Iu=5000
4p HR HR
1SDA073918R1



E6.2 W FP Iu=5000
3p HR HR
1SDA073917R1



E6.2 W FP Iu=5000
4p/f HR HR
1SDA073919R1

Dimensions

Product Net Depth / Length:	383 mm	383 mm	383 mm
Product Net Height:	425 mm	425 mm	425 mm
Product Net Weight:	100 kg	87 kg	112 kg
Product Net Width:	929 mm	803 mm	1069 mm

Container Information

Package Level 1 Depth / Length:	1127 mm	1000 mm	1257 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	109 kg	96 kg	123 kg
Package Level 1 Height:	610 mm	610 mm	610 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	570 mm	570 mm	570 mm

Additional Information

Product Main Type:	SACE Emax 2	SACE Emax 2	SACE Emax 2
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	W FP	W FP	W FP

Technical

Current Type:	AC	AC	AC
Neutral Pole Current ([%I _n]):	50 %	N/A	100 %
Number of Poles:	4P	3P	4 / f
Rated Current (I _n):	5000 A	5000 A	5000 A
Rated Impulse Withstand Voltage (U _{imp}):	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i):	AC 1000 V	AC 1000 V	AC 1000 V
Rated Operational Voltage:	690 V AC 800 V AC 900 V AC	690 V AC 800 V AC 900 V AC	690 V AC
Rated Uninterrupted Current (I _u):	5000 A	5000 A	5000 A
Rated Voltage (U _r):	690 V	690 V	690 V
Recommended Screw Driver:	Main Circuit M12	Main Circuit M12	Main Circuit M12
Standards:	IEC	IEC	IEC
Sub-type:	E6.2	E6.2	E6.2
Terminal Connection Type:	Rear flat Horizontal	Rear flat Horizontal	Rear flat Horizontal
Terminal Type:	Bolt	Bolt	Bolt
Tightening Torque:	70 N·m	70 N·m	70 N·m

E6/E/
fWFP4p1000VDCVR-
VRnew
1SDA059143R1

E6/E/
fWFP4p1000VDCHR-
HRnew
1SDA059142R1

E6/E/
fWFP4p1000VDCFL4
FLnew
1SDA059144R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	115 kg	115 kg	115 kg
Product Net Width:	1062 mm	1062 mm	1062 mm

Container Information

Package Level 1 Depth / Length:	1050 mm	1050 mm	1050 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	127 kg	127 kg	127 kg
Package Level 1 Height:	590 mm	590 mm	590 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	630 mm	630 mm	630 mm

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	4 / f	4 / f	4 / f
Rated Uninterrupted Current (I _u):	6300 A	6300 A	6300 A
Rated Voltage (U _r):	1000 V	1000 V	1000 V
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers

E6/
EWFP3p750VDCFL
-FLnew
1SDA059141R1

E6/
EWFP3p750VDCVR
-VRnew
1SDA059140R1

E6/
EWFP3p750VDCHR
-HRnew
1SDA059139R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	70 kg	70 kg	70 kg
Product Net Width:	810 mm	810 mm	810 mm

Container Information

Package Level 1 Depth / Length:	N/A	935 mm	N/A
Package Level 1 EAN:			
Package Level 1 Gross Weight:	40 kg	82 kg	40 kg
Package Level 1 Height:	N/A	590 mm	N/A
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	N/A	630 mm	N/A

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	DC	DC	DC
Number of Poles:	3P	3P	3P
Rated Uninterrupted Current (I _u):	6300 A	6300 A	6300 A
Rated Voltage (U _r):	750 V	750 V	750 V
Release Type:	EL	N/A	N/A
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Brea Rear flat Horizontal

**E6/fWFP4pF-
Fnew4
1SDA059785R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	115 kg
Product Net Width:	1062 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	198 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4 / f
Rated Uninterrupted Current (I_u):	6300 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

	E6/fWFP4pFL- FLnew4 1SDA059793R1	E6/fWFP4pHR- FLnew4 1SDA059817R1	E6/fWFP4pFL- HRnew4 1SDA059873R1
--	--	--	--

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	115 kg	115 kg	115 kg
Product Net Width:	1062 mm	1062 mm	1062 mm

Container Information

Package Level 1 EAN:			
Package Level 1 Gross Weight:	87 kg	87 kg	87 kg
Package Level 1 Units:	1 piece	1 piece	1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	AC	AC	AC
Number of Poles:	4 / f	4 / f	4 / f
Rated Uninterrupted Current (I _u):	6300 A	N/A	N/A
Rated Voltage (U _r):	690 V	690 V	690 V
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal

E6/fWFP4pHR-
HRnew4
1SDA059769R1

E6/fWFP4pHR-
VRnew4
1SDA059801R1

E6/fWFP4pVR-
HRnew4
1SDA059825R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	115 kg	115 kg	115 kg
Product Net Width:	1062 mm	1062 mm	1062 mm

Container Information

Package Level 1 EAN:			
Package Level 1 Gross Weight:	87 kg	87 kg	87 kg
Package Level 1 Units:	1 piece	1 piece	1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	AC	AC	AC
Number of Poles:	4 / f	4 / f	4 / f
Rated Uninterrupted Current (I _u):	6300 A	6300 A	6300 A
Rated Voltage (U _r):	690 V	690 V	690 V
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Orientated	Withdrawable Circuit-Breakers Rear flat Orientated

**E6/fWFP4pVR-
VRnew4
1SDA059777R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	115 kg
Product Net Width:	1062 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	87 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4 / f
Rated Uninterrupted Current (I _u):	6300 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

E6H-A W FP 3p HR-HR

new

1SDA061579R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	82 kg
Product Net Width:	810 mm

Container Information

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Standards:	UL 1066
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E6V/L/X-A W FP 3p HR-HR
new
1SDA061753R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	82 kg
Product Net Width:	810 mm

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Standards:	UL 1066
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

E6WFP3pF-
Fnew
1SDA059683R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	70 kg
Product Net Width:	810 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	168 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	6300 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

**E6WFP3pFL-
FLnew
1SDA059689R1**

**E6WFP3pHR-
FLnew
1SDA059707R1**

**E6WFP3pFL-
HRnew
1SDA059749R1**

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	70 kg	70 kg	70 kg
Product Net Width:	810 mm	810 mm	810 mm

Container Information

Package Level 1 EAN:			
Package Level 1 Gross Weight:	92 kg	92 kg	92 kg
Package Level 1 Units:	1 piece	1 piece	1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	AC	AC	AC
Number of Poles:	3P	3P	3P
Rated Voltage (U _r):	690 V	690 V	690 V
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal

E6H-A W FP 3p HR-HR

new

1SDA061579R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	82 kg
Product Net Width:	810 mm

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	FP
Version:	W FP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	600 V
Standards:	UL 1066
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E6WFP3pHR-
VRnew
1SDA059695R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	70 kg
Product Net Width:	810 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	92 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I_u):	6300 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E6WFP3pVR-
HRnew
1SDA059713R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	70 kg
Product Net Width:	810 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	92 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

E6WFP3pVR-
VRnew
1SDA059677R1

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	70 kg
Product Net Width:	810 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	92 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	3P
Rated Uninterrupted Current (I _u):	6300 A
Rated Voltage (U _r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical

**E6WFP4pF-
Fnew4
1SDA059784R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	90 kg
Product Net Width:	936 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	198 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	6300 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Front

E6WFP4pFL-
FLnew4
1SDA059792R1

E6WFP4pFL-
HRnew4
1SDA059872R1

E6WFP4pHR-
FLnew4
1SDA059816R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	90 kg	90 kg	90 kg
Product Net Width:	936 mm	936 mm	936 mm

Container Information

Package Level 1 EAN:			
Package Level 1 Gross Weight:	97 kg	97 kg	97 kg
Package Level 1 Units:	1 piece	1 piece	1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	AC	AC	AC
Number of Poles:	4P	4P	4P
Rated Uninterrupted Current (I _u):	6300 A	N/A	N/A
Rated Voltage (U _r):	690 V	690 V	690 V
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal

**E6WFP4pHR-
HRnew4
1SDA059768R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	90 kg
Product Net Width:	936 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	87 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	6300 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal

**E6WFP4pHR-
VRnew4
1SDA059800R1**

Dimensions

Product Net Depth / Length:	396.5 mm
Product Net Height:	461 mm
Product Net Weight:	90 kg
Product Net Width:	936 mm

Container Information

Package Level 1 EAN:	
Package Level 1 Gross Weight:	97 kg
Package Level 1 Units:	1 piece

Additional Information

Product Main Type:	SACE Emax
Product Name:	Fixed Part
Product Type:	Fixed Part
Version:	WFP

Technical

Current Type:	AC
Number of Poles:	4P
Rated Uninterrupted Current (I_u):	6300 A
Rated Voltage (U_r):	690 V
Standards:	IEC
Sub-type:	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated

**E6WFP4pVR-
VRnew4**
1SDA059776R1

**E6WFP4pVR-
HRnew4**
1SDA059824R1

**E6WFP4pHR-
VRnew4**
1SDA059800R1

Dimensions

Product Net Depth / Length:	396.5 mm	396.5 mm	396.5 mm
Product Net Height:	461 mm	461 mm	461 mm
Product Net Weight:	90 kg	90 kg	90 kg
Product Net Width:	936 mm	936 mm	936 mm

Container Information

Package Level 1 EAN:			
Package Level 1 Gross Weight:	97 kg	97 kg	97 kg
Package Level 1 Units:	1 piece	1 piece	1 piece

Additional Information

Product Main Type:	SACE Emax	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	Fixed Part
Version:	WFP	WFP	WFP

Technical

Current Type:	AC	AC	AC
Number of Poles:	4P	4P	4P
Rated Uninterrupted Current (I _u):	6300 A	6300 A	6300 A
Rated Voltage (U _r):	690 V	690 V	690 V
Standards:	IEC	IEC	IEC
Sub-type:	E6	E6	E6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Rear flat Orientated	Withdrawable Circuit-Breakers Rear flat Orientated

	T2 P FP 3p F 1SDA051329R1	T2 P FP 4p F 1SDA051330R1	T2 P FP 3p F + Acc 1SDX170301R1
--	------------------------------	------------------------------	---------------------------------------

Dimensions

Product Net Depth / Length:	70 mm	70 mm	N/A
Product Net Height:	170 mm	170 mm	N/A
Product Net Weight:	0.798 kg	0.993 kg	N/A
Product Net Width:	90 mm	90 mm	N/A

Container Information

Package Level 1 Depth / Length:	185 mm	185 mm	N/A
Package Level 1 EAN:			
Package Level 1 Gross Weight:	0.854 kg	1.065 kg	N/A
Package Level 1 Height:	149 mm	149 mm	N/A
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	115 mm	115 mm	N/A

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Fixed Part	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part	N/A
Suitable For:	T2	T2	N/A
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	N/A
Version:	P	P	N/A

Technical

Device:	Fixed Part	Fixed Part	N/A
Number of Poles:	3P	4P	N/A
Rated Operational Voltage:	690 V AC 500 V DC	690 V AC 500 V DC	N/A
Standards:	IEC 60947	IEC	N/A
Sub-type:	T2	T2	N/A
Terminal Connection Type:	Plug-In Circuit-Breakers Front	Plug-In Circuit-Breakers Front	N/A
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	N/A



T3 P FP 3p F 1SDA051331R1

T3 P FP 4p F 1SDA051332R1

Dimensions

Product Net Depth / Length:	70 mm	70 mm
Product Net Height:	206 mm	206 mm
Product Net Weight:	1.112 kg	1.449 kg
Product Net Width:	105 mm	140 mm

Container Information

Package Level 1 Depth / Length:	220 mm	220 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	1.3 kg	1.6 kg
Package Level 1 Height:	170 mm	170 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	115 mm	115 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Suitable For:	T3	T3
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	P	P

Technical

Device:	Fixed Part	Fixed Part
Number of Poles:	3P	4P
Rated Operational Voltage:	690 V AC 500 V DC	690 V AC 500 V DC
Standards:	IEC 60947	IEC 60947
Sub-type:	T3	T3
Terminal Connection Type:	Plug-In Circuit-Breakers Front	Plug-In Circuit-Breakers Front
Test Voltage at Industrial Frequency for 1 Minute:	3000 V	3000 V

	T4L 250 P FP 4p FC Cu 1000V AC 1SDA063459R1	T4L 250 P FP 3p FC Cu 1000V AC 1SDA063458R1	T4L 250 W FP 3p FC Cu 1000V AC 1SDA063460R1	T4L 250 W FP 4p FC Cu 1000V AC 1SDA063461R1
--	--	--	--	--

Dimensions

Product Net Weight:	1.5 kg	1 kg	2.5 kg	2.5 kg
---------------------	--------	------	--------	--------

Container Information

Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
------------------------	---------	---------	---------	---------

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Version:	P	P	W	W

Technical

Current Type:	AC	AC	AC	AC
Number of Poles:	4P	3P	3P	4P
Rated Operational Voltage:	1000 V AC	1000 V AC	1000 V AC	1000 V AC
Rated Uninterrupted Current (I _u):	250 A	250 A	250 A	250 A
Short-Circuit Performance Level:	L	L	L	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T4	T4	T4	T4
Terminal Connection Type:	Plug-In Circuit-Breakers Front for Copper Cables	Plug-In Circuit-Breakers Front for Copper Cables	Withdrawable Circuit-Breakers Front for Copper Cables	Withdrawable Circuit-Breakers Front for Copper Cables

T4 P FP 3p HR

1SDA054739R1

T4 P FP 3p VR

1SDA054738R1

T4 P FP 4p EF

1SDA054740R1

T4 P FP 3p HR-
EF

1SDA057168R1

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm	209 mm
Product Net Weight:	1 kg	1 kg	1.5 kg	1 kg
Product Net Width:	105 mm	105 mm	140 mm	105 mm

Container Information

Package Level 1 Depth / Length:	240 mm	292 mm	313 mm	292 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1.2 kg	1.414 kg	1.7 kg	1.2 kg
Package Level 1 Height:	162 mm	167 mm	131 mm	167 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	162 mm	167 mm	131 mm	167 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T4	T4	T4	T4
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Air Circuit Breakers
Version:	P	P	P	P

Technical

Device:	Fixed Part	Fixed Part	Fixed Part	N/A
Number of Poles:	3P	3P	4P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T4	T4	T4	T4
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V	N/A

	T4 P FP 4p EF	T4 P FP 4p HR	T4 P FP 4p VR	T4 P FP 4p HR- EF
	1SDA054740R1	1SDA054742R1	1SDA054741R1	1SDA060466R1

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm	209 mm
Product Net Weight:	1.5 kg	1.5 kg	1.5 kg	1.5 kg
Product Net Width:	140 mm	140 mm	140 mm	140 mm

Container Information

Package Level 1 Depth / Length:	313 mm	240 mm	240 mm	359 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1.7 kg	1.7 kg	1.7 kg	1.7 kg
Package Level 1 Height:	131 mm	162 mm	162 mm	183 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	131 mm	162 mm	162 mm	183 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T4	T4	T4	T4
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	P	P	P	P

Technical

Device:	Fixed Part	Fixed Part	Fixed Part	N/A
Number of Poles:	4P	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Short-Circuit Performance Level:	N/A	N/A	N/A	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T4	T4	T4	T4
Terminal Connection Type:	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V	N/A

	T4 W FP 3p HR 1SDA054745 R1	T4 W FP 3p VR 1SDA054744 R1	T4 W FP 3p EF 1SDA054743 R1
--	--	--	--

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm
Product Net Weight:	2.5 kg	2.5 kg	2.5 kg
Product Net Width:	136.5 mm	136.5 mm	136.5 mm

Container Information

Package Level 1 Depth / Length:	344 mm	344 mm	344 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	2.8 kg	2.8 kg	2.733 kg
Package Level 1 Height:	228 mm	228 mm	228 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	228 mm	228 mm	228 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T4	T4	T4
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Device:	Fixed Part	Fixed Part	Fixed Part
Number of Poles:	3P	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Standards:	IEC	IEC	IEC
Sub-type:	T4	T4	T4
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V

	T4 W FP 4p EF 1SDA054746R1	T4 W FP 4p VR 1SDA054747R1	T4 W FP 4p HR 1SDA054748R1
--	---	---	---

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm
Product Net Weight:	2.5 kg	2.5 kg	2.5 kg
Product Net Width:	172 mm	172 mm	172 mm

Container Information

Package Level 1 Depth / Length:	344 mm	344 mm	344 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	2.8 kg	2.8 kg	2.8 kg
Package Level 1 Height:	228 mm	228 mm	228 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	228 mm	228 mm	228 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T4	T4	T4
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Device:	Fixed Part	Fixed Part	Fixed Part
Number of Poles:	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Short-Circuit Performance Level:	N/A	N/A	L
Standards:	IEC	IEC	IEC
Sub-type:	T4	T4	T4
Terminal Connection Type:	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Rear flat Horizontal
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V

T5 400 P FP
3p VR
1SDA05475
OR1

T5 400 P FP
3p HR
1SDA05475
1R1

T5 400 P FP
3p EF
1SDA05474
9R1

T5 400 P FP
3p HR-EF
1SDA060435R
1

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm	209 mm
Product Net Weight:	1.5 kg	1.5 kg	1.5 kg	1.5 kg
Product Net Width:	171 mm	171 mm	171 mm	171 mm

Container Information

Package Level 1 Depth / Length:	240 mm	240 mm	313 mm	359 mm
Package Level 1 Gross Weight:	1.7 kg	1.971 kg	1.708 kg	1.7 kg
Package Level 1 Height:	162 mm	162 mm	131 mm	183 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	162 mm	162 mm	131 mm	183 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	P	P	P	P

Technical

Device:	Fixed Part	Fixed Part	Fixed Part	N/A
Number of Poles:	3P	3P	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T5	T5	T5	T5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V	N/A

	T5 400 P FP 4p VR 1SDA054753 R1	T5 400 P FP 4p EF 1SDA054752 R1	T5 400 P FP 4p HR 1SDA054754 R1	T5 400 P FP 4p HR-EF 1SDA060467R1
--	--	--	--	--

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm	209 mm
Product Net Weight:	1.5 kg	2 kg	1.5 kg	1.5 kg
Product Net Width:	186 mm	186 mm	186 mm	171 mm

Container Information

Package Level 1 Depth / Length:	240 mm	313 mm	240 mm	344 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1.7 kg	2.2 kg	1.7 kg	1.7 kg
Package Level 1 Height:	162 mm	131 mm	162 mm	228 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	162 mm	131 mm	162 mm	228 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	P	P	P	P

Technical

Device:	N/A	N/A	Fixed Part	N/A
Number of Poles:	4P	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Short-Circuit Performance Level:	N/A	N/A	L	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T5	T5	T5	T5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	N/A	N/A	not applicable V	N/A

**T5 400 W FP 3p
VR
1SDA054756R1**

**T5 400 W FP 3p
EF
1SDA054755R1**

Dimensions

Product Net Depth / Length:	50 mm	50 mm
Product Net Height:	209 mm	209 mm
Product Net Weight:	3 kg	2.9 kg
Product Net Width:	171 mm	171 mm

Container Information

Package Level 1 Depth / Length:	344 mm	344 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	3.2 kg	3.2 kg
Package Level 1 Height:	228 mm	228 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	228 mm	228 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part
Suitable For:	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W



Technical

Device:	Fixed Part	Fixed Part
Number of Poles:	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	400 A	400 A
Standards:	IEC	IEC
Sub-type:	T5	T5
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V

T5 400 W FP 4p
VR
1SDA054759R1

T5 400 W FP 4p
EF
1SDA054758R1

T5 400 W FP 4p
HR
1SDA054761R1



Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm
Product Net Height:	209 mm	209 mm	209 mm
Product Net Weight:	2.9 kg	3.38 kg	3 kg
Product Net Width:	218 mm	218 mm	218 mm

Container Information

Package Level 1 Depth / Length:	369 mm	344 mm	369 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	3.2 kg	3.89 kg	3.2 kg
Package Level 1 Height:	280 mm	228 mm	280 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	280 mm	228 mm	280 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Device:	Fixed Part	Fixed Part	Fixed Part
Number of Poles:	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A
Short-Circuit Performance Level:	N/A	N/A	L
Standards:	IEC	IEC	IEC
Sub-type:	T5	T5	T5
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V

	T5 630 P FP 3p EF 1SDA054762R1	T5 630 P FP 3p VR 1SDA054763R1	T5 630 P FP 3p HR 1SDA054764R1
--	--------------------------------------	--------------------------------------	--------------------------------------

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm
Product Net Height:	273 mm	273 mm	273 mm
Product Net Weight:	1.5 kg	1.5 kg	1.5 kg
Product Net Width:	171 mm	171 mm	171 mm

Container Information

Package Level 1 Depth / Length:	359 mm	286 mm	286 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	4 kg	1.7 kg	1.7 kg
Package Level 1 Height:	183 mm	228 mm	228 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	183 mm	228 mm	228 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	P	P	P

Technical

Device:	N/A	Fixed Part	Fixed Part
Number of Poles:	3P	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A
Standards:	IEC	IEC	IEC
Sub-type:	T5	T5	T5
Terminal Connection Type:	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Rear flat Horizontal
Test Voltage at Industrial Frequency for 1 Minute:	N/A	not applicable V	not applicable V



**T5 630 P FP 3p
HR-EF
1SDA060436R1**

**T5 630 P FP 3p EF-
HR
1SDA115938R1**

Dimensions

Product Net Depth / Length:	50 mm	N/A
Product Net Height:	273 mm	N/A
Product Net Weight:	1.5 kg	1.5 kg
Product Net Width:	171 mm	N/A

Container Information

Package Level 1 Depth / Length:	359 mm	359 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	1.7 kg	1.7 kg
Package Level 1 Height:	183 mm	183 mm
Package Level 1 Units:	1 piece	1 piece
Package Level 1 Width:	183 mm	183 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part
Suitable For:	T5	N/A
Suitable for Product Class:	Moulded Case Circuit Breakers	N/A
Version:	P	P

Technical

Number of Poles:	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	N/A
Rated Uninterrupted Current (I _u):	630 A	630 A
Standards:	IEC	IEC
Sub-type:	T5	T5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended

	T5 630 P FP 4p VR4 1SDA054766 R1	T5 630 P FP 4p EF4 1SDA054765 R1	T5 630 P FP 4p HR4 1SDA054767 R1	T5 630 P FP 4p HR-EF4 1SDA060468R1
--	---	---	---	---

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm	50 mm
Product Net Height:	273 mm	273 mm	273 mm	273 mm
Product Net Weight:	1.5 kg	1.5 kg	1.5 kg	1.5 kg
Product Net Width:	186 mm	186 mm	186 mm	186 mm

Container Information

Package Level 1 Depth / Length:	286 mm	359 mm	286 mm	344 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1.7 kg	1.7 kg	1.7 kg	1.7 kg
Package Level 1 Height:	228 mm	183 mm	228 mm	228 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	228 mm	183 mm	228 mm	228 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	P	P	P	P

Technical

Device:	Fixed Part	Fixed Part	N/A	N/A
Number of Poles:	4P	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _n):	630 A	630 A	630 A	630 A
Short-Circuit Performance Level:	N/A	N/A	N/A	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T5	T5	T5	T5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Rear flat Horizontal Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	N/A	N/A

T5 630 W FP 3p
HR
1SDA054770R1

T5 630 W FP 3p
VR
1SDA054769R1

T5 630 W FP 3p
EF
1SDA054768R1

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm
Product Net Height:	273 mm	273 mm	273 mm
Product Net Weight:	2.9 kg	3 kg	2.9 kg
Product Net Width:	171 mm	171 mm	171 mm

Container Information

Package Level 1 Depth / Length:	321 mm	321 mm	369 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	3.2 kg	3.2 kg	3.2 kg
Package Level 1 Height:	288 mm	288 mm	280 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	321 mm	321 mm	280 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Device:	Fixed Part	Fixed Part	Fixed Part
Number of Poles:	3P	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A
Standards:	IEC	IEC	IEC
Sub-type:	T5	T5	T5
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	not applicable V	not applicable V

T5 630 W FP 4p
HR
1SDA054774R1

T5 630 W FP 4p
VR
1SDA054772R1

T5 630 W FP 4p
EF
1SDA054771R1

Dimensions

Product Net Depth / Length:	50 mm	50 mm	50 mm
Product Net Height:	273 mm	273 mm	273 mm
Product Net Weight:	3 kg	2.9 kg	3 kg
Product Net Width:	218 mm	218 mm	218 mm

Container Information

Package Level 1 Depth / Length:	321 mm	321 mm	369 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	3.2 kg	3.2 kg	3.2 kg
Package Level 1 Height:	288 mm	288 mm	280 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	321 mm	321 mm	280 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T5	T5	T5
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Device:	Fixed Part	N/A	Fixed Part
Number of Poles:	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	630 A	630 A	630 A
Short-Circuit Performance Level:	N/A	N/A	L
Standards:	IEC	IEC	IEC
Sub-type:	T5	T5	T5
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	not applicable V	N/A	not applicable V

	T5L 400 W FP 4p FC Cu 1000V AC 1SDA063465R1	T5L 400 W FP 3p FC Cu 1000V AC 1SDA063464R1	T5L 400 P FP 3p FC Cu 1000V AC 1SDA063462R1	T5L 400 P FP 4p FC Cu 1000V AC 1SDA063463R1
--	--	--	--	--

Dimensions

Product Net Weight:	3 kg	2.9 kg	1.5 kg	1.5 kg
---------------------	------	--------	--------	--------

Container Information

Package Level 1 Depth / Length:	223 mm	188 mm	0 mm	0 mm
Package Level 1 Gross Weight:	3.2 kg	3.2 kg	1.7 kg	1.7 kg
Package Level 1 Height:	179 mm	158 mm	0 mm	0 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	179 mm	158 mm	0 mm	0 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Version:	W	W	P	P

Technical

Number of Poles:	4P	3P	3P	4P
Rated Operational Voltage:	1000 V AC	1000 V AC	1000 V AC	1000 V AC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Short-Circuit Performance Level:	L	L	L	L
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T5	T5	T5	T5
Terminal Connection Type:	Withdrawable Circuit-Breakers Front for Copper Cables	Withdrawable Circuit-Breakers Front for Copper Cables	Plug-In Circuit-Breakers Front for Copper Cables	Plug-In Circuit-Breakers Front for Copper Cables

	T6 W FP 3p HR 1SDA06038 5R1	T6 W FP 3p EF 1SDA06038 4R1	T6 W FP 3p VR 1SDA06038 6R1
--	--	--	--

Dimensions

Product Net Depth / Length:	85.5 mm	85.5 mm	85.5 mm
Product Net Height:	295 mm	295 mm	295 mm
Product Net Weight:	8.7 kg	3 kg	3 kg
Product Net Width:	260 mm	260 mm	260 mm

Container Information

Package Level 1 Depth / Length:	439 mm	439 mm	439 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	9.8 kg	4.4 kg	4.5 kg
Package Level 1 Height:	322 mm	322 mm	322 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	322 mm	322 mm	322 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Number of Poles:	3P	3P	3P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Vertical

	T6 W FP 4p VR 1SDA06038 9R1	T6 W FP 4p EF 1SDA06038 7R1	T6 W FP 4p HR 1SDA06038 8R1
--	--	--	--

Dimensions

Product Net Depth / Length:	85.5 mm	85.5 mm	85.5 mm
Product Net Height:	295 mm	295 mm	295 mm
Product Net Weight:	9 kg	4 kg	10.3 kg
Product Net Width:	330 mm	330 mm	330 mm

Container Information

Package Level 1 Depth / Length:	439 mm	439 mm	439 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	4.1 kg	4 kg	11.35 kg
Package Level 1 Height:	322 mm	322 mm	322 mm
Package Level 1 Units:	1 piece	1 piece	1 piece
Package Level 1 Width:	322 mm	322 mm	322 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	T6	T6	T6
Suitable for Product Class:	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers	Moulded Case Circuit Breakers
Version:	W	W	W

Technical

Number of Poles:	4P	4P	4P
Rated Operational Voltage:	690 V AC 750 V DC	690 V AC 750 V DC	690 V AC 750 V DC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A
Standards:	IEC	IEC	IEC
Sub-type:	T6	T6	T6
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal



**T7-X1 W FP
3p EF-EF
1SDA062045
R1**



**T7-X1 W FP 3p
HR-HR
1SDA062044
R1**



**T7-X1 W FP
3p HR-EF
1SDA062046
R1**



**T7-X1 W FP
3p EF-HR
1SDA062047
R1**

Dimensions

Product Net Depth / Length:	251 mm	251 mm	251 mm	251 mm
Product Net Height:	343 mm	343 mm	343 mm	343 mm
Product Net Weight:	18 kg	20 kg	18 kg	18 kg
Product Net Width:	278 mm	278 mm	278 mm	278 mm

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	N/A	N/A
Package Level 1 EAN:				
Package Level 1 Gross Weight:	19.5 kg	21.7 kg	19.5 kg	19.5 kg
Package Level 1 Height:	340 mm	340 mm	N/A	N/A
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	360 mm	360 mm	N/A	N/A

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Version:	W	W	W	W

Technical

Number of Poles:	3P	3P	3P	3P
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7-X1	T7-X1	T7-X1	T7-X1
Terminal Connection Type:	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal Front Extended	Withdrawable Circuit-Breakers Front Extended Rear flat Horizontal

	T7-X1 W FP 4p	T7-X1 W FP 4p	T7-X1 W FP 4p	T7-X1 W FP 4p
	HR-HR	EF-HR	HR-EF	EF-EF
	1SDA062048R1	1SDA062051R1	1SDA062050R1	1SDA062049R1

Dimensions

Product Net Depth / Length:	251 mm	251 mm	251 mm	251 mm
Product Net Height:	343 mm	343 mm	343 mm	343 mm
Product Net Weight:	24.6 kg	24.6 kg	24.6 kg	24.6 kg
Product Net Width:	348 mm	348 mm	348 mm	348 mm

Container Information

Package Level 1 Depth / Length:	400 mm	N/A	N/A	400 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	26.1 kg	26.1 kg	26.1 kg	26.1 kg
Package Level 1 Height:	350 mm	N/A	N/A	350 mm
Package Level 1 Units:	1 piece	1 piece	1 piece	1 piece
Package Level 1 Width:	390 mm	N/A	N/A	390 mm

Additional Information

Product Main Type:	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T	Accessories for Tmax T
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Version:	W	W	W	W

Technical

Number of Poles:	4P	4P	4P	4P
Rated Operational Voltage:	690 V AC	690 V AC	690 V AC	690 V AC
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A	1600 A
Standards:	IEC	IEC	IEC	IEC
Sub-type:	T7-X1	T7-X1	T7-X1	T7-X1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Front Extended Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal Front Extended	Withdrawable Circuit-Breakers Front Extended



Product image
not available



**X1 W FP UL 4p HR-
HR
1SDA065717R1**

**X1 W FP UL 3p HR-
HR
1SDA065716R1**

Dimensions

Product Net Depth / Length:	251 mm	251 mm
Product Net Height:	343 mm	343 mm
Product Net Weight:	24.6 kg	18 kg
Product Net Width:	348 mm	278 mm

Container Information

Additional Information

Product Main Type:	SACE Emax	SACE Emax
Product Name:	Fixed Part	Fixed Part
Product Type:	Fixed Part	Fixed Part
Version:	W FP	W FP

Technical

Current Type:	AC	AC
Number of Poles:	4P	3P
Rated Voltage (U _r):	600 V	600 V
Standards:	UL	UL
Sub-type:	X1	X1
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal



XT1 P FP 3p EF

XT1 P FP 3p HR

XT1 P FP 4p HR

XT1 P FP 4p EF

1SDA068183R1

1SDA068184R1

1SDA068186R1

1SDA068185R1

Dimensions

Product Net Weight:	0.69 kg	0.84 kg	1.12 kg	0.89 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	190 mm	190 mm	190 mm	190 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	0.79 kg	0.94 kg	1.22 kg	0.99 kg
Package Level 1 Height:	155 mm	155 mm	155 mm	155 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	120 mm	120 mm	120 mm	120 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT1	XT1	XT1	XT1
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P	P

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	800 V	800 V	800 V	800 V
Rated Operational Voltage:	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC
Rated Uninterrupted Current (I _u):	160 A	160 A	160 A	160 A
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT1	XT1	XT1	XT1
Terminal Connection Type:	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Front Extended



XT2 P FP 3p EF

XT2 P FP 4p HR

XT2 P FP 4p EF

XT2 P FP 3p HR

1SDA068187R1

1SDA068191R1

1SDA068190R1

1SDA068189R1

Dimensions

Product Net Weight:	0.9 kg	1.35 kg	1.12 kg	0.97 kg
---------------------	--------	---------	---------	---------

Container Information


Package Level 1 Depth / Length:	225 mm	160 mm	225 mm	190 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1 kg	1.45 kg	1.22 kg	1.074 kg
Package Level 1 Height:	180 mm	185 mm	180 mm	155 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	120 mm	155 mm	120 mm	120 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT2	XT2	XT2	XT2
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P	P

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	4P	4P	3P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC
Rated Uninterrupted Current (I _u):	160 A	160 A	160 A	160 A
Standards:	IEC60947-2 UL489	IEC60947-2	IEC60947-2 UL489	IEC60947-2
Sub-type:	XT2	XT2	XT2	XT2
Terminal Connection Type:	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal



XT2 W FP 4p EF

XT2 W FP 3p HR

XT2 W FP 4p HR

XT2 W FP 3p EF

1SDA068202R1

1SDA068201R1

1SDA068203R1

1SDA068200R1

Dimensions

Product Net Weight:	1.59 kg	1.44 kg	1.7 kg	1.37 kg
---------------------	---------	---------	--------	---------

Container Information

Package Level 1 Depth / Length:	195 mm	295 mm	260 mm	195 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1.74 kg	1.59 kg	1.85 kg	1.506 kg
Package Level 1 Height:	225 mm	155 mm	220 mm	225 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	175 mm	145 mm	195 mm	175 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT2	XT2	XT2	XT2
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	3P	4P	3P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	1000 V	1000 V	1000 V	1000 V
Rated Operational Voltage:	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC
Rated Uninterrupted Current (I _u):	160 A	160 A	160 A	160 A
Standards:	IEC60947-2 UL489	IEC60947-2	IEC60947-2	IEC60947-2 UL489
Sub-type:	XT2	XT2	XT2	XT2
Terminal Connection Type:	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Front Extended



XT3 P FP 3p EF
1SDA068192R1

XT3 P FP 4p EF
1SDA068194R1

XT3 P FP 3p HR
1SDA068193R1

XT3 P FP 4p HR
1SDA068195R1

Dimensions

Product Net Weight:	0.99 kg	1.32 kg	1.04 kg	1.41 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	225 mm	225 mm	225 mm	195 mm
Package Level 1 EAN:				
Package Level 1 Gross Weight:	1.14 kg	1.47 kg	1.19 kg	1.56 kg
Package Level 1 Height:	180 mm	180 mm	180 mm	225 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	120 mm	120 mm	120 mm	175 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT3	XT3	XT3	XT3
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P	P

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	4P	3P	4P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	8 kV	8 kV	8 kV	8 kV
Rated Insulation Voltage (U _i):	800 V	800 V	800 V	800 V
Rated Operational Voltage:	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC	690 V AC 500 V DC
Rated Uninterrupted Current (I _u):	250 A	250 A	250 A	250 A
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT3	XT3	XT3	XT3
Terminal Connection Type:	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Rear flat Horizontal



XT5 P FP 400A
3p frame
configurable
1SDA112953R1

XT5 P FP 400A
3p EF EF IEC
1SDA104668R1

XT5 P FP 400A 3p
EF EF UL
1SDA104669R1

XT5 P FP 400A
3p HR HR IEC
1SDA104670R1

Dimensions

Product Net Weight:	21.7 kg	3.12 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	290 mm	380 mm	380 mm
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	249 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	248 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P	P

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	3P	3P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	690 V AC	600 V AC 600 V DC	690 V AC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Standards:	IEC60947-2	IEC60947-2	UL489	IEC60947-2
Sub-type:	XT5	XT5	XT5	XT5
Terminal Connection Type:	Plug-In Circuit-Breakers	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal



**XT5 P FP 400A 3p
HR HR UL
1SDA104671R1**



**XT5 P FP 400A 3p
VR VR IEC
1SDA112961R1**



**XT5 P FP 400A 3p
VR VR UL
1SDA112962R1**

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	3P
Order Multiple:	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	N/A	N/A
Rated Operational Voltage:	600 V AC 600 V DC	N/A	N/A
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A
Standards:	UL489	IEC60947-2	UL489
Sub-type:	XT5	XT5	XT5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers	Plug-In Circuit-Breakers



**XT5 P FP 400A
4p frame
configurable
1SDA112954R1**



**XT5 P FP 400A
4p EF EF IEC
1SDA104672R1**



**XT5 P FP 400A 4p
EF EF UL
1SDA104673R1**



**XT5 P FP 400A
4p HR HR IEC
1SDA104674R1**

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P	P

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	690 V AC	600 V AC 600 V DC	690 V AC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Standards:	IEC60947-2	IEC60947-2	UL489	IEC60947-2
Sub-type:	XT5	XT5	XT5	XT5
Terminal Connection Type:	Plug-In Circuit-Breakers	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Front Extended	Plug-In Circuit-Breakers Rear flat Horizontal



XT5 P FP 400A 4p
HR HR UL
1SDA104675R1



XT5 P FP 400A 4p
VR VR IEC
1SDA112963R1



XT5 P FP 400A 4p
VR VR UL
1SDA112964R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm
---------------------------------	--------	--------	--------

Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	N/A	N/A
Rated Operational Voltage:	600 V AC 600 V DC	N/A	N/A
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A
Standards:	UL489	IEC60947-2	UL489
Sub-type:	XT5	XT5	XT5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers	Plug-In Circuit-Breakers



**XT5 P FP 630A 3p
frame configurable
1SDA112955R1**



**XT5 W FP 630A 3p
frame configurable
1SDA112959R1**

Dimensions

Product Net Weight:	21.7 kg	21.7 kg
---------------------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm
Package Level 1 EAN:		
Package Level 1 Gross Weight:	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part
Suitable For:	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT
Version:	P	W

Technical

Configuration Type:	Mounted only	Mounted only
Number of Poles:	3P	3P
Order Multiple:	1 piece	1 piece
Rated Uninterrupted Current (I_u):	630 A 600 A	630 A 600 A
Standards:	IEC60947-2	IEC60947-2
Sub-type:	XT5	XT5
Terminal Connection Type:	Plug-In Circuit-Breakers	Withdrawable Circuit-Breakers



XT5 P FP 630A 4p
VR VR IEC/UL
1SDA104681R1

XT5 P FP 630A 4p
HR HR IEC/UL
1SDA104680R1

XT5 P FP 630A 4p
EF EF IEC/UL
1SDA104679R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	P	P	P

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	600 V AC 600 V DC	600 V AC 600 V DC	600 V AC 600 V DC
Rated Uninterrupted Current (I _u):	630 A 600 A	630 A 600 A	630 A 600 A
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT5	XT5	XT5
Terminal Connection Type:	Plug-In Circuit-Breakers Rear flat Vertical	Plug-In Circuit-Breakers Rear flat Horizontal	Plug-In Circuit-Breakers Front Extended



XT5 W FP 400A
3p frame
configurable
1SDA112957R1

XT5 W FP 400A
3p EF EF IEC
1SDA104682R1

XT5 W FP 400A
3p EF EF UL
1SDA104683R1

XT5 W FP 400A
3p HR HR IEC
1SDA104684R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	3P	3P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	690 V AC	600 V AC 600 V DC	690 V AC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Standards:	IEC60947-2	IEC60947-2	UL489	IEC60947-2
Sub-type:	XT5	XT5	XT5	XT5
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal



**XT5 W FP 400A 3p
HR HR UL
1SDA104685R1**

**XT5 W FP 400A 3p
VR VR IEC
1SDA112965R1**

**XT5 W FP 400A 3p
VR VR UL
1SDA112966R1**

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W



Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	3P
Order Multiple:	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	N/A	N/A
Rated Operational Voltage:	600 V AC 600 V DC	N/A	N/A
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A
Standards:	UL489	IEC60947-2	UL489
Sub-type:	XT5	XT5	XT5
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers



XT5 W FP 400A
4p frame
configurable
1SDA112958R1

XT5 W FP 400A
4p EF EF IEC
1SDA104686R1

XT5 W FP 400A
4p EF EF UL
1SDA104687R1

XT5 W FP 400A
4p HR HR IEC
1SDA104688R1



Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------



Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	690 V AC	600 V AC 600 V DC	690 V AC
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A	400 A
Standards:	IEC60947-2	IEC60947-2	UL489	IEC60947-2
Sub-type:	XT5	XT5	XT5	XT5
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal



XT5 W FP 400A 4p
HR HR UL
1SDA104689R1



XT5 W FP 400A 4p
VR VR IEC
1SDA112967R1



XT5 W FP 400A 4p
VR VR UL
1SDA112968R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm
---------------------------------	--------	--------	--------

Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece
Rated Frequency (f):	50 / 60 Hz	N/A	N/A
Rated Operational Voltage:	600 V AC 600 V DC	N/A	N/A
Rated Uninterrupted Current (I _u):	400 A	400 A	400 A
Standards:	UL489	IEC60947-2	UL489
Sub-type:	XT5	XT5	XT5
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers



XT5 W FP 630A
3p frame
configurable
1SDA112959R1



XT5 W FP 630A
3p VR VR IEC/
UL
1SDA104692R1



XT5 W FP 630A
3p EF EF IEC/
UL
1SDA104690R1



XT5 W FP 630A
3p HR HR IEC/
UL
1SDA104691R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	3P	3P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	600 V AC 600 V DC	600 V AC 600 V DC	600 V AC 600 V DC
Rated Uninterrupted Current (I _n):	630 A 600 A	630 A 600 A	630 A 600 A	630 A 600 A
Standards:	IEC60947-2	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT5	XT5	XT5	XT5
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal



XT5 W FP 630A
4p frame
configurable
1SDA112960R1

XT5 W FP 630A
4p VR VR IEC/
UL
1SDA104695R1

XT5 W FP 630A
4p HR HR IEC/
UL
1SDA104694R1

XT5 W FP 630A
4p EF EF IEC/
UL
1SDA104693R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
---------------------------------	--------	--------	--------	--------

Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT5	XT5	XT5	XT5
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	600 V AC 600 V DC	600 V AC 600 V DC	600 V AC 600 V DC
Rated Uninterrupted Current (I _u):	630 A 600 A	630 A 600 A	630 A 600 A	630 A 600 A
Standards:	IEC60947-2	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT5	XT5	XT5	XT5
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Vertical	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Front Extended



XT6 W FP 800A
3p frame
configurable
1SDA112969R1

XT6 W FP 800A
3p HR HR IEC/
UL
1SDA104697R1

XT6 W FP 800A
3p EF EF IEC/UL
1SDA104696R1

XT6 W FP 800A
3p VR VR IEC/UL
1SDA104698R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT6	XT6	XT6	XT6
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical

Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	3P	3P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Standards:	IEC60947-2	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT6	XT6	XT6	XT6
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Vertical



XT6 W FP 800A
4p frame
configurable
1SDA112970R1

XT6 W FP 800A
4p EF EF IEC/UL
1SDA104699R1

XT6 W FP 800A
4p HR HR IEC/
UL
1SDA104700R1

XT6 W FP 800A
4p VR VR IEC/
UL
1SDA104701R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	380 mm	380 mm	380 mm
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	340 mm	340 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	360 mm	360 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT6	XT6	XT6	XT6
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W	W

Technical


Configuration Type:	Mounted only	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	4P	4P	4P	4P
Order Multiple:	1 piece	1 piece	1 piece	1 piece
Rated Frequency (f):	N/A	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated Operational Voltage:	N/A	600 V AC	600 V AC	600 V AC
Rated Uninterrupted Current (I _u):	800 A	800 A	800 A	800 A
Standards:	IEC60947-2	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT6	XT6	XT6	XT6
Terminal Connection Type:	Withdrawable Circuit-Breakers	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Rear flat Horizontal	Withdrawable Circuit-Breakers Rear flat Vertical



XT7-XT7M W FP
3p HR IEC/UL
1SDA104703R1



XT7-XT7M W FP
3p EF IEC/UL
1SDA104702R1



XT7-XT7M W FP
4p EF IEC/UL
1SDA104704R1

Dimensions

Product Net Weight:	21.7 kg	21.7 kg	21.7 kg
---------------------	---------	---------	---------

Container Information

Package Level 1 Depth / Length:	380 mm	330 mm	380 mm
Package Level 1 EAN:			
Package Level 1 Gross Weight:	21.7 kg	21.7 kg	21.7 kg
Package Level 1 Height:	340 mm	375 mm	340 mm
Package Level 1 Units:	box 1 piece	box 1 piece	box 1 piece
Package Level 1 Width:	360 mm	320 mm	360 mm

Additional Information

Product Main Type:	Accessories for Tmax XT	Accessories for Tmax XT	Accessories for Tmax XT
Product Name:	Accessory	Accessory	Accessory
Product Type:	Fixed Part	Fixed Part	Fixed Part
Suitable For:	XT7, XT7M	XT7, XT7M	XT7, XT7M
Suitable for Product Class:	SACE Tmax XT	SACE Tmax XT	SACE Tmax XT
Version:	W	W	W

Technical

Configuration Type:	Loose or configurable	Loose or configurable	Loose or configurable
Number of Poles:	3P	3P	4P
Order Multiple:	1 piece	1 piece	1 piece
Rated Uninterrupted Current (I _u):	1600 A	1600 A	1600 A
Standards:	IEC60947-2 UL489	IEC60947-2 UL489	IEC60947-2 UL489
Sub-type:	XT7, XT7M	XT7, XT7M	XT7, XT7M
Terminal Connection Type:	Withdrawable Circuit-Breakers Rear flat Orientated	Withdrawable Circuit-Breakers Front Extended	Withdrawable Circuit-Breakers Front Extended

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ahk@nt-rt.ru || сайт: <https://abbswitch.nt-rt.ru>